

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.091	0.500	0.252	KC	R2
0.125	0.500	0.252	VC	R2
0.126	0.500	0.252	KC	R2
0.157	0.354	0.118	VC	R2
0.157	0.630	0.236	SC	R2
0.157	0.709	0.157	VC	R2
0.169	0.705	0.236	KC	V3
0.177	0.591	0.197	TC	R2
0.177	0.630	0.197	TC	R2
0.177	0.630	0.276	KC	R2
0.177	0.630	0.276	TC	R2
0.177	0.669	0.276	TC	R2
0.177	0.709	0.276	TC	R2
0.177	1.024	0.197	VC	R2
0.177	1.024	0.315	VC	R2
0.187	0.437	0.126	WPC	R4
0.188	0.394	0.126	WPC	R4
0.189	0.500	0.126	VB	C2
0.189	0.571	0.157	KC	R2
0.189	0.571	0.157	VC	R2
0.189	0.591	0.157	KC	R2
0.189	0.591	0.157	VC	R2
0.189	0.591	0.197	TC	R2
0.189	0.866	0.276	KC	R2
0.189	0.866	0.276	SC	R2
0.197	0.354	0.079	VB	G2
0.197	0.394	0.157	VC	R2
0.197	0.433	0.118	VC	R2
0.197	0.512	0.252	KBR	G2
0.197	0.512	0.315	KBR	G2
0.197	0.551	0.157	VC	R2
0.197	0.551	0.197	KB	G2
0.197	0.554	0.201	KBR	G2
0.197	0.591	0.236	SC	R2
0.197	0.591	0.236	TC	R2
0.197	0.591	0.236	VC	R2
0.197	0.630	0.236	TC	R2
0.197	0.630	0.315	KC	R2
0.197	0.669	0.276	TC	R2
0.197	0.709	0.236	TC	R2
0.197	0.709	0.276	TC	R2
0.197	0.709	0.394	TC	R2
0.197	0.748	0.276	TC	R2
0.197	0.866	0.276	TC	R2
0.197	1.181	0.236	TB	G2
0.217	0.354	0.118	VC	R2
0.217	0.433	0.157	VC	R2
0.217	0.709	0.315	TC	R2
0.217	0.866	0.315	TC	R2
0.236	0.394	0.079	VB	G2
0.236	0.394	0.079	VB	C2
0.236	0.394	0.098	VC	R2
0.236	0.394	0.157	VC	R2
0.236	0.433	0.157	VC	R2

Shaft	Bore	Width	Lip Style	Material
0.236	0.433	0.177	VC	RV
0.236	0.472	0.079	VB	G2
0.236	0.472	0.177	SC	R2
0.236	0.472	0.197	VC	R2
0.236	0.472	0.217	SC	R2
0.236	0.472	0.315	TC	R2
0.236	0.500	0.150	VBR	CV
0.236	0.512	0.189	WPC	R4
0.236	0.551	0.157	VC	R2
0.236	0.591	0.157	SC	R2
0.236	0.591	0.276	SC	R2
0.236	0.630	0.197	SC	R2
0.236	0.630	0.197	TC	R2
0.236	0.630	0.236	TC	R2
0.236	0.630	0.276	SC	R2
0.236	0.630	0.276	TC	R2
0.236	0.669	0.276	TC	R2
0.236	0.709	0.177	VC	R2
0.236	0.709	0.197	KC	R2
0.236	0.709	0.236	TC	R2
0.236	0.709	0.276	TC	R2
0.236	0.748	0.197	VC	R2
0.236	0.748	0.276	TC	R2
0.236	0.748	0.276	VC	R2
0.236	0.787	0.217	TC	R2
0.236	0.827	0.276	TC	R2
0.236	0.866	0.276	SC	R2
0.236	0.866	0.276	TC	R2
0.236	0.866	0.276	VC	R2
0.236	0.866	0.315	TC	R2
0.236	0.984	0.236	SC	R2
0.236	0.984	0.315	SC	R2
0.236	0.984	0.315	TC	R2
0.236	0.984	0.315	TC	R2
0.236	1.024	0.276	TC	R2
0.236	1.378	0.276	TC	R2
0.250	0.499	0.189	VC	R2
0.250	0.500	0.185	VB	CPA
0.250	0.750	0.252	SC	RV
0.250	0.750	0.252	SC	R2
0.250	0.875	0.126	SC	R2
0.250	0.875	0.252	SC	R2
0.250	1.000	0.500	DC	RV
0.252	0.437	0.126	WPB	G4
0.252	0.500	0.126	VC	R2
0.252	0.500	0.126	VC	R2
0.252	0.500	0.154	VBR	CPA
0.252	0.500	0.252	SC	R2
0.252	0.625	0.157	SC	R2
0.252	0.625	0.157	SC	R2
0.252	0.625	0.157	VB	P2
0.252	0.635	0.189	SC	R2
0.252	0.750	0.236	SB	C2
0.252	0.750	0.252	SB	G2
0.252	0.750	0.252	SB	PPA

Shaft	Bore	Width	Lip Style	Material
0.252	0.750	0.252	TB	G2
0.252	0.750	0.252	VC	R2
0.252	0.750	0.374	DC	R2
0.252	0.875	0.252	TB	P2
0.252	1.000	0.252	TC	R2
0.252	1.000	0.500	DC	R2
0.256	0.571	0.276	KC	R2
0.256	0.571	0.276	TC	R2
0.268	0.866	0.276	TC	R2
0.276	0.433	0.079	VB	C2
0.276	0.512	0.157	VC	R2
0.276	0.541	0.157	VC	R2
0.276	0.551	0.157	VC	R2
0.276	0.591	0.197	SC	R2
0.276	0.591	0.276	KC	R2
0.276	0.630	0.276	SC	RV
0.276	0.630	0.276	TC	R2
0.276	0.669	0.197	TC	R2
0.276	0.669	0.276	TC	R2
0.276	0.709	0.177	SC	R2
0.276	0.709	0.256	SC	R2
0.276	0.709	0.276	TC	R2
0.276	0.748	0.276	TC	R2
0.276	0.787	0.197	VC	R2
0.276	0.787	0.276	TC	R2
0.276	0.866	0.236	TC	R2
0.276	0.866	0.276	SC	R2
0.276	0.866	0.276	TC	R2
0.276	0.866	0.315	TC	R2
0.276	0.992	0.217	KC	R2
0.276	1.024	0.217	KC	R2
0.276	1.220	0.197	SC	R2
0.276	1.220	0.276	TC	R2
0.280	0.425	0.138	VB	C2
0.295	0.625	0.232	SC	R2
0.295	0.748	0.177	VC	R2
0.307	0.539	0.098	VC	R2
0.311	0.433	0.079	VC	RPA
0.311	0.500	0.098	VB	C2
0.311	0.562	0.236	VC	RV
0.311	0.563	0.126	SC	R2
0.311	0.566	0.126	WPB	G4
0.311	0.575	0.189	VBR	G2
0.311	0.624	0.252	TBR	GV
0.311	0.625	0.126	SC	R2
0.311	0.625	0.150	VB	G2
0.311	0.625	0.157	SC	R2
0.311	0.626	0.157	WPB	G4
0.311	0.750	0.252	KC	V3
0.311	0.750	0.252	TB	G2
0.311	1.125	0.315	DC	R2
0.312	0.750	0.252	TC	R2
0.313	0.500	0.126	VC	R2
0.313	0.750	0.252	SC	R2

Shaft	Bore	Width	Lip Style	Material
0.313	0.750	0.311	SC	RV
0.313	0.875	0.252	SC	R2
0.315	0.472	0.118	VB	G2
0.315	0.472	0.118	VC	R2
0.315	0.472	0.118	VC	R2
0.315	0.472	0.157	KC	R2
0.315	0.472	0.157	VC	R2
0.315	0.531	0.197	TB	G2
0.315	0.551	0.157	KC	R2
0.315	0.551	0.157	SB	GV
0.315	0.551	0.157	SC	R2
0.315	0.551	0.157	VB	C2
0.315	0.551	0.157	VB	C2
0.315	0.551	0.157	VC	R2
0.315	0.551	0.197	SC	R2
0.315	0.551	0.197	TC	R2
0.315	0.551	0.236	TB	G2
0.315	0.551	0.276	TC	R2
0.315	0.577	0.197	TB	G2
0.315	0.591	0.197	TB	G2
0.315	0.591	0.197	TC	R2
0.315	0.591	0.197	VC	R2
0.315	0.591	0.315	SB	G2
0.315	0.630	0.157	SC	R2
0.315	0.630	0.157	VC	R2
0.315	0.630	0.197	SB	G2
0.315	0.630	0.197	SC	R2
0.315	0.630	0.197	TC	R2
0.315	0.630	0.217	KC	V3
0.315	0.630	0.236	KC	R2
0.315	0.630	0.236	SC	R2
0.315	0.630	0.236	TC	R2
0.315	0.630	0.276	SB	G2
0.315	0.630	0.276	SC	R2
0.315	0.630	0.276	TC	R2
0.315	0.630	0.394	DC	R2
0.315	0.669	0.276	TC	R2
0.315	0.701	0.197	VC	R2
0.315	0.709	0.157	KC	R2
0.315	0.709	0.197	KC	R2
0.315	0.709	0.197	SC	R2
0.315	0.709	0.197	TC	R2
0.315	0.709	0.236	TC	R2
0.315	0.709	0.276	TC	R2
0.315	0.709	0.315	TC	R2
0.315	0.748	0.157	SC	R2
0.315	0.748	0.276	TC	R2
0.315	0.787	0.197	TC	R2
0.315	0.787	0.276	TC	R2
0.315	0.827	0.236	SC	R2
0.315	0.827	0.236	TC	R2
0.315	0.866	0.157	TB	G2
0.315	0.866	0.236	SC	R2
0.315	0.866	0.236	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.315	0.866	0.276	SB	G2
0.315	0.866	0.276	SC	RPA
0.315	0.866	0.276	SC	R2
0.315	0.866	0.276	TC	R2
0.315	0.866	0.315	SC	R2
0.315	0.866	0.394	TC	R2
0.315	0.906	0.197	TC	R2
0.315	0.906	0.276	TC	R2
0.315	0.945	0.177	SC	R2
0.315	0.945	0.276	SC	R2
0.315	0.945	0.276	TC	R2
0.315	0.984	0.236	SC	R2
0.315	0.984	0.276	SC	R2
0.315	0.984	0.276	TC	R2
0.315	0.984	0.315	TC	R2
0.315	0.984	0.354	TC	R2
0.315	1.024	0.236	SC	R2
0.315	1.024	0.276	TC	R2
0.315	1.102	0.197	SC	R2
0.315	1.102	0.197	TC	R2
0.315	1.181	0.236	TC	R2
0.315	1.181	0.276	TC	R2
0.315	1.339	0.315	TC	R2
0.315	1.339	0.315	TC	R2
0.327	0.750	0.252	SC	R2
0.327	0.836	0.311	SA2	G2
0.335	0.630	0.256	SC	R2
0.339	0.551	0.118	VC	R2
0.346	0.709	0.157	TC	RV
0.346	0.709	0.157	TC	RV
0.348	0.669	0.157	VC	R2
0.348	0.669	0.197	TC	RPA
0.348	0.787	0.157	VC	R2
0.348	0.787	0.197	TC	R2
0.348	0.827	0.197	TC	R2
0.354	0.498	0.118	VB	G2
0.354	0.512	0.118	VB	G2
0.354	0.630	0.157	SC	R2
0.354	0.630	0.197	SB	G2
0.354	0.630	0.217	TC	R2
0.354	0.669	0.177	SB	G2
0.354	0.689	0.157	VC	R2
0.354	0.709	0.197	VC	R2
0.354	0.709	0.236	SB	G2
0.354	0.709	0.276	SC	R2
0.354	0.709	0.276	TC	RPA
0.354	0.748	0.157	SC	RV
0.354	0.748	0.197	KC	R2
0.354	0.748	0.197	SB	G2
0.354	0.748	0.197	SC	R2
0.354	0.748	0.197	TC	R2
0.354	0.748	0.276	TB	G2
0.354	0.748	0.276	TC	R2
0.354	0.787	0.157	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.354	0.787	0.276	TC	R2
0.354	0.827	0.177	SC	R2
0.354	0.866	0.276	SC	RV
0.354	0.866	0.276	TC	R2
0.354	0.945	0.276	TC	R2
0.354	0.984	0.276	TC	R2
0.354	1.024	0.276	SC	R2
0.354	1.024	0.276	TC	R2
0.354	1.142	0.276	TC	R2
0.354	1.181	0.276	TC	R2
0.374	0.563	0.094	VB	G2
0.374	0.563	0.094	VB	P2
0.374	0.563	0.094	WPC	R4
0.374	0.563	0.126	KC	R2
0.374	0.625	0.126	WPB	G4
0.374	0.625	0.189	KC	R2
0.374	0.630	0.157	KC	R2
0.374	0.650	0.106	VB	C2
0.374	0.687	0.157	TBR	P2
0.374	0.687	0.157	TC	R2
0.374	0.687	0.157	VC	R2
0.374	0.687	0.157	WPB	G4
0.374	0.687	0.157	WPB	G4
0.374	0.687	0.311	VBR	G2
0.374	0.728	0.217	SB	G2
0.374	0.748	0.252	SC	R2
0.374	0.750	0.157	SC	R2
0.374	0.750	0.189	WPC	R4
0.374	0.750	0.252	DC	R2
0.374	0.750	0.252	SB	P2
0.374	0.750	0.252	SC	R2
0.374	0.750	0.252	TBR	G2
0.374	0.750	0.252	TC	R2
0.374	0.750	0.252	VB	G2
0.374	0.750	0.252	VC	R2
0.374	0.750	0.280	SC	R2
0.374	0.817	0.252	VC	R2
0.374	0.875	0.252	TB2	C2
0.374	0.875	0.252	TC	R2
0.374	0.875	0.252	VB	P2
0.374	0.875	0.311	SC	R2
0.374	0.937	0.189	VB	C2
0.374	0.999	0.311	SBR	C2
0.374	1.000	0.374	SC	R2
0.375	0.563	0.094	WPB	G4
0.375	0.625	0.126	VB	G2
0.375	0.700	0.150	SC	R2
0.375	0.750	0.169	VC	R2
0.375	0.750	0.252	TB	G2
0.375	0.750	0.252	TB2	P2
0.375	0.836	0.189	SB2	P2
0.375	0.875	0.252	SB2	C2
0.375	1.000	0.252	SC	R2
0.390	0.900	0.252	SC	R2

Shaft	Bore	Width	Lip Style	Material
0.391	0.700	0.157	SC	RPA
0.394	0.551	0.118	VB	G2
0.394	0.551	0.157	KC	R2
0.394	0.591	0.118	VB	GV
0.394	0.591	0.118	VC	R2
0.394	0.591	0.157	VC	R2
0.394	0.630	0.157	SC	R2
0.394	0.630	0.157	TC	R2
0.394	0.630	0.157	VB	G2
0.394	0.630	0.177	TC	R2
0.394	0.630	0.197	SC	R2
0.394	0.630	0.236	SB	C2
0.394	0.630	0.276	TC	R2
0.394	0.669	0.118	VB	G2
0.394	0.669	0.138	VC	R2
0.394	0.669	0.177	SB	G2
0.394	0.669	0.197	SB	G2
0.394	0.669	0.197	SBR	G2
0.394	0.669	0.197	TC	R2
0.394	0.669	0.197	VC	R2
0.394	0.669	0.236	SC	R2
0.394	0.669	0.276	TC	R2
0.394	0.709	0.157	SC	R2
0.394	0.709	0.157	TC	R2
0.394	0.709	0.197	KC	R2
0.394	0.709	0.197	SC	R2
0.394	0.709	0.197	TC	R2
0.394	0.709	0.236	SC	R2
0.394	0.709	0.236	TC	R2
0.394	0.709	0.276	TC	R2
0.394	0.740	0.205	SB2	CV
0.394	0.748	0.157	SC	R2
0.394	0.748	0.157	VC	R2
0.394	0.748	0.197	TBR	C2
0.394	0.748	0.236	SC	R2
0.394	0.748	0.276	SC	R2
0.394	0.748	0.276	TC	R2
0.394	0.748	0.394	TC	R2
0.394	0.787	0.157	SC	R2
0.394	0.787	0.197	SB	G2
0.394	0.787	0.197	SC	R2
0.394	0.787	0.197	TC	RPA
0.394	0.787	0.197	TC	R2
0.394	0.787	0.197	VC	R2
0.394	0.787	0.236	SC	R2
0.394	0.787	0.236	TC	R2
0.394	0.787	0.276	TB	G2
0.394	0.787	0.276	TC	R2
0.394	0.787	0.315	DC	R2
0.394	0.827	0.157	TC	R2
0.394	0.827	0.197	SC	R2
0.394	0.827	0.236	SC	RV
0.394	0.827	0.236	TC	R2
0.394	0.827	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.394	0.827	0.354	DC	R2
0.394	0.866	0.118	VC	R2
0.394	0.866	0.157	SC	RV
0.394	0.866	0.157	TC	R2
0.394	0.866	0.197	TC	R2
0.394	0.866	0.236	TC	R2
0.394	0.866	0.276	SC	R2
0.394	0.866	0.276	TC	R2
0.394	0.866	0.315	DC	R2
0.394	0.866	0.315	TC	R2
0.394	0.906	0.276	TC	R2
0.394	0.906	0.315	TC	R2
0.394	0.925	0.276	TC	R2
0.394	0.925	0.394	TC	R2
0.394	0.945	0.157	TC	R2
0.394	0.945	0.157	VC	R2
0.394	0.945	0.236	TC	R2
0.394	0.945	0.276	SC	R2
0.394	0.945	0.276	TC	R2
0.394	0.945	0.315	DC	R2
0.394	0.984	0.197	SC	R2
0.394	0.984	0.197	TC	R2
0.394	0.984	0.276	TC	R2
0.394	0.984	0.394	TC	R2
0.394	1.000	0.252	TB	GV
0.394	1.000	0.252	TC	RV
0.394	1.024	0.217	SC	R2
0.394	1.024	0.276	SC	RV
0.394	1.024	0.276	SC	R2
0.394	1.024	0.276	TC	R2
0.394	1.024	0.315	TC	R2
0.394	1.024	0.354	DC	R2
0.394	1.056	0.276	DC	R2
0.394	1.102	0.276	SC	R2
0.394	1.102	0.276	TC	R2
0.394	1.102	0.315	TC	R2
0.394	1.102	0.394	TC	R2
0.394	1.181	0.276	SB	G2
0.394	1.181	0.276	SC	R2
0.394	1.181	0.276	TC	R2
0.394	1.181	0.394	TC	R2
0.394	1.378	0.315	TC	R2
0.402	1.024	0.177	VB	C2
0.406	0.875	0.311	SC	R2
0.409	1.004	0.209	KB	PPA
0.422	0.623	0.118	VC	R2
0.425	0.787	0.354	SC	R2
0.425	0.787	0.354	VC	R2
0.426	0.823	0.252	SC	RV
0.426	0.875	0.311	SB	G2
0.433	0.591	0.118	VB	C2
0.433	0.669	0.118	VB	G2
0.433	0.669	0.118	VC	R2
0.433	0.669	0.157	SB	PV

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.433	0.669	0.157	SC	R2
0.433	0.669	0.157	TC	R2
0.433	0.669	0.236	VC	R2
0.433	0.709	0.157	SC	R2
0.433	0.709	0.197	SBR	G2
0.433	0.709	0.197	TBR	C2
0.433	0.709	0.236	SBR	G2
0.433	0.787	0.157	TB	G3
0.433	0.787	0.177	SBR	G2
0.433	0.787	0.177	TB	G3
0.433	0.787	0.276	TC	R2
0.433	0.827	0.276	TC	R2
0.433	0.827	0.315	DC	R2
0.433	0.827	0.315	TC	R2
0.433	0.866	0.236	TC	RV
0.433	0.866	0.276	SB	CS
0.433	0.866	0.276	SC	RPA
0.433	0.866	0.276	SC	R2
0.433	0.866	0.276	TC	R2
0.433	0.906	0.276	TC	R2
0.433	0.925	0.276	TC	R2
0.433	0.945	0.276	TC	R2
0.433	0.984	0.276	TC	R2
0.433	1.024	0.276	SC	R2
0.433	1.024	0.276	TC	R2
0.433	1.102	0.276	TC	R2
0.433	1.142	0.276	TC	R2
0.433	1.181	0.276	TC	R2
0.433	1.181	0.394	TC	R2
0.437	0.625	0.126	VB	C2
0.437	0.625	0.126	VB	C2
0.437	0.625	0.126	VC	R2
0.437	0.650	0.098	VB	C2
0.437	0.687	0.126	VB	C2
0.437	0.750	0.252	SBR	G2
0.437	0.750	0.287	KC	R2
0.437	0.750	0.295	KC	R2
0.437	0.836	0.189	VB	C2
0.437	0.836	0.189	VB	G2
0.437	0.875	0.189	TC	R2
0.437	0.875	0.189	WPB	G4
0.437	0.875	0.220	SC	R2
0.437	0.875	0.252	SB2	PPA
0.437	0.875	0.252	TB	G2
0.437	0.875	0.252	TB2	P2
0.437	0.875	0.252	TBR	G2
0.437	0.875	0.252	TC	R2
0.437	0.875	0.311	SB	G2
0.437	0.875	0.315	SBR	GPA
0.437	0.937	0.189	SB	P2
0.437	0.937	0.252	SC	R2
0.437	0.941	0.189	SB	G2
0.437	0.941	0.201	SB	C2
0.437	0.999	0.252	SB	PV

Shaft	Bore	Width	Lip Style	Material
0.437	0.999	0.374	SB	P2
0.437	0.999	0.374	SBR	G2
0.437	1.000	0.252	SBR	G2
0.437	1.000	0.252	SC	R2
0.437	1.000	0.374	SC	R2
0.437	1.124	0.252	SA2	P2
0.437	1.125	0.252	SB2	C2
0.437	1.259	0.252	TC	R2
0.453	0.875	0.189	VB	C2
0.457	0.748	0.236	TC	R2
0.457	0.866	0.276	TC	R2
0.457	0.945	0.394	SC	R2
0.457	0.945	0.394	TC	R2
0.465	0.866	0.276	SC	R2
0.469	0.703	0.126	VB	C2
0.469	0.718	0.126	VB	C2
0.469	0.750	0.295	KC	R2
0.469	0.750	0.295	KC	R2
0.469	0.836	0.189	WPB	G4
0.469	0.875	0.189	SC	R2
0.469	0.875	0.189	TC	R2
0.469	0.875	0.220	VB	G2
0.469	0.875	0.252	VB2	G2
0.469	0.875	0.311	TB2	P2
0.469	0.984	0.177	VC	R2
0.469	0.984	0.197	SC	R2
0.472	0.630	0.098	VC	R2
0.472	0.630	0.118	VB	G2
0.472	0.669	0.098	VC	R2
0.472	0.669	0.197	VC	R2
0.472	0.669	0.236	VC	R2
0.472	0.709	0.118	VB	G2
0.472	0.709	0.118	VC	R2
0.472	0.709	0.157	KC	R2
0.472	0.709	0.157	SB	G2
0.472	0.709	0.157	SC	R2
0.472	0.709	0.157	VC	R2
0.472	0.709	0.177	TBR	C2
0.472	0.709	0.197	TC	R2
0.472	0.709	0.197	VB	G2
0.472	0.709	0.197	VC	R2
0.472	0.709	0.236	SBR	G2
0.472	0.718	0.126	VC	R2
0.472	0.718	0.126	VC	R2
0.472	0.748	0.118	TC	R2
0.472	0.748	0.118	VB	G2
0.472	0.748	0.118	VC	R2
0.472	0.748	0.177	VBR	G2
0.472	0.748	0.197	SB	C2
0.472	0.748	0.197	SC	R2
0.472	0.748	0.197	TC	R2
0.472	0.748	0.197	TC	R2
0.472	0.748	0.276	TC	R2
0.472	0.787	0.157	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.472	0.787	0.157	VC	R2
0.472	0.787	0.197	SB	G2
0.472	0.787	0.197	SC	R2
0.472	0.787	0.197	TB	G2
0.472	0.787	0.197	TC	R2
0.472	0.787	0.197	VB	G2
0.472	0.787	0.217	TB	G2
0.472	0.787	0.236	SC	R2
0.472	0.787	0.236	TC	R2
0.472	0.787	0.276	DC	R2
0.472	0.787	0.276	TC	R2
0.472	0.827	0.157	KC	R2
0.472	0.827	0.157	SC	R2
0.472	0.827	0.157	TC	R2
0.472	0.827	0.197	SC	R2
0.472	0.827	0.276	TC	R2
0.472	0.866	0.118	VC	R2
0.472	0.866	0.142	KC	R2
0.472	0.866	0.157	SB	C2
0.472	0.866	0.157	SC	R2
0.472	0.866	0.157	TC	R2
0.472	0.866	0.157	VC	R2
0.472	0.866	0.177	TC	RV
0.472	0.866	0.197	SB	G2
0.472	0.866	0.197	SC	R2
0.472	0.866	0.197	TC	R2
0.472	0.866	0.236	SC	R2
0.472	0.866	0.236	TC	R2
0.472	0.866	0.276	KC	R2
0.472	0.866	0.276	SB	G2
0.472	0.866	0.276	SC	R2
0.472	0.866	0.276	SC	R2
0.472	0.866	0.276	SC	R2
0.472	0.866	0.276	TC	R2
0.472	0.866	0.276	TC	RV
0.472	0.866	0.276	TC	RPA
0.472	0.866	0.276	TC	R2
0.472	0.866	0.315	DC	R2
0.472	0.866	0.315	TC	R2
0.472	0.866	0.354	TC	R2
0.472	0.906	0.276	TC	R2
0.472	0.906	0.315	TB	G2
0.472	0.906	0.315	TC	R2
0.472	0.925	0.276	TC	R2
0.472	0.945	0.157	VC	R2
0.472	0.945	0.177	SC	R2
0.472	0.945	0.197	SC	R2
0.472	0.945	0.236	SC	R2
0.472	0.945	0.236	TC	R2
0.472	0.945	0.276	SB	G2
0.472	0.945	0.276	SC	RV
0.472	0.945	0.276	SC	R2
0.472	0.945	0.276	TC	R2
0.472	0.945	0.315	DC	R2

Shaft	Bore	Width	Lip Style	Material
0.472	0.945	0.315	TC	R2
0.472	0.984	0.157	SC	R2
0.472	0.984	0.177	SC	R2
0.472	0.984	0.177	VC	R2
0.472	0.984	0.197	SB2	G2
0.472	0.984	0.197	SC	R2
0.472	0.984	0.197	TC	R2
0.472	0.984	0.236	TC	R2
0.472	0.984	0.276	SC	R2
0.472	0.984	0.276	TC	R2
0.472	0.984	0.315	TC	R2
0.472	0.984	0.394	TC	R2
0.472	1.004	0.276	TC	R2
0.472	1.024	0.177	SC	R2
0.472	1.024	0.236	SC	R2
0.472	1.024	0.276	TC	R2
0.472	1.024	0.276	TC	R2
0.472	1.024	0.315	SC	R2
0.472	1.024	0.315	TC	R2
0.472	1.063	0.276	TC	R2
0.472	1.063	0.354	TC	R2
0.472	1.102	0.197	SC	R2
0.472	1.102	0.236	SC	R2
0.472	1.102	0.276	SB2	G2
0.472	1.102	0.276	SC	R2
0.472	1.102	0.276	TC	R2
0.472	1.102	0.315	DC	R2
0.472	1.102	0.315	SC	R2
0.472	1.102	0.315	TC	R2
0.472	1.122	0.197	SC	R2
0.472	1.122	0.217	SC	R2
0.472	1.122	0.276	TC	R2
0.472	1.181	0.197	SC	R2
0.472	1.181	0.197	TC	R2
0.472	1.181	0.236	SC	R2
0.472	1.181	0.276	SC	R2
0.472	1.181	0.276	TC	R2
0.472	1.181	0.354	TC	R2
0.472	1.181	0.394	TC	R2
0.472	1.260	0.197	SC	R2
0.472	1.260	0.197	TC	R2
0.472	1.260	0.236	SB2	C2
0.472	1.260	0.276	SB2	G2
0.472	1.260	0.276	SC	R2
0.472	1.260	0.276	TB2	G2
0.472	1.260	0.276	TC	R2
0.472	1.260	0.394	SC	R2
0.472	1.260	0.394	TC	R2
0.472	1.339	0.276	TC	R2
0.472	1.378	0.197	SC	R2
0.472	1.378	0.276	TC	R2
0.472	1.378	0.394	SC	R2
0.472	1.378	0.394	TC	R2
0.472	1.457	0.276	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.472	1.457	0.394	SC	R2
0.472	1.772	0.276	SC	R2
0.472	1.772	0.276	TC	R2
0.490	0.866	0.276	TC	R2
0.492	0.866	0.236	SC	RPA
0.492	0.866	0.236	TC	RPA
0.492	0.875	0.252	VC	R2
0.492	0.925	0.315	TC	R2
0.492	0.925	0.394	TC	R2
0.492	0.984	0.236	SB	C2
0.492	0.984	0.315	TC	R2
0.492	1.122	0.276	TC	R2
0.498	0.906	0.087	VC	R2
0.500	0.687	0.098	VC	R2
0.500	0.748	0.157	KC	R2
0.500	0.750	0.126	SB	C2
0.500	0.750	0.126	VB	G2
0.500	0.750	0.126	VC	R2
0.500	0.750	0.126	WPB	G4
0.500	0.750	0.173	VC	R2
0.500	0.750	0.193	VBR	C2
0.500	0.750	0.295	KC	P2
0.500	0.766	0.281	SC	R2
0.500	0.778	0.197	VB	C2
0.500	0.801	0.189	SB	C2
0.500	0.813	0.157	TC	R2
0.500	0.843	0.252	VB2	P2
0.500	0.863	0.189	SC	RV
0.500	0.874	0.311	SA2	CV
0.500	0.875	0.126	VC	R2
0.500	0.875	0.189	DC	R2
0.500	0.875	0.189	SB2	G2
0.500	0.875	0.220	VB	G2
0.500	0.875	0.252	SC	R2
0.500	0.875	0.252	TB	GV
0.500	0.875	0.252	VB	P2
0.500	0.875	0.311	SB	P2
0.500	0.875	0.311	SC	R2
0.500	0.875	0.311	TB	P2
0.500	0.875	0.315	TC	R2
0.500	0.886	0.217	TC	R2
0.500	0.900	0.252	SC	R2
0.500	0.999	0.252	TB2	P2
0.500	0.999	0.252	VC	R2
0.500	0.999	0.374	TB	P2
0.500	1.000	0.177	VC	R2
0.500	1.000	0.189	SB	G2
0.500	1.000	0.201	SC	R2
0.500	1.000	0.252	SB	G2
0.500	1.000	0.252	SB	P2
0.500	1.000	0.252	SB2	P2
0.500	1.000	0.252	SC	RV
0.500	1.000	0.252	SC	R2
0.500	1.000	0.252	TB	G2

Shaft	Bore	Width	Lip Style	Material
0.500	1.000	0.252	TB2	CPA
0.500	1.000	0.252	TC	R2
0.500	1.000	0.374	SA2	P2
0.500	1.000	0.374	SC	R2
0.500	1.024	0.236	TC	R2
0.500	1.124	0.252	SC	R2
0.500	1.125	0.252	SB2	PV
0.500	1.125	0.252	TB2	G2
0.500	1.125	0.311	TC	R2
0.500	1.125	0.374	SA2	G2
0.500	1.250	0.189	SB	G2
0.500	1.250	0.252	SB2	P2
0.500	1.250	0.311	SC	RV
0.500	1.250	0.311	TC	R2
0.500	1.375	0.252	SB	C2
0.500	1.375	0.252	TC	R2
0.504	0.764	0.098	VC	R2
0.512	0.748	0.118	VC	R2
0.512	0.748	0.128	KB	C2
0.512	0.748	0.157	TB	G2
0.512	0.787	0.177	SC	R2
0.512	0.787	0.197	TBR	G2
0.512	0.787	0.197	TC	R2
0.512	0.787	0.197	VB	G2
0.512	0.787	0.217	TB	G2
0.512	0.866	0.157	SC	R2
0.512	0.866	0.197	SC	R2
0.512	0.866	0.197	TB	G2
0.512	0.866	0.197	TC	R2
0.512	0.866	0.236	SC	R2
0.512	0.866	0.236	TC	R2
0.512	0.866	0.276	TC	R2
0.512	0.906	0.276	TC	R2
0.512	0.945	0.197	SC	R2
0.512	0.945	0.236	SB	G2
0.512	0.945	0.236	SC	R2
0.512	0.945	0.276	SC	R2
0.512	0.945	0.276	TC	R2
0.512	0.984	0.197	SC	R2
0.512	0.984	0.197	TC	R2
0.512	0.984	0.276	SB	G2
0.512	0.984	0.276	TB	G2
0.512	0.984	0.276	TC	R2
0.512	0.984	0.394	TB	G2
0.512	1.024	0.276	SC	R2
0.512	1.024	0.276	TC	R2
0.512	1.024	0.354	TC	R2
0.512	1.024	0.394	DC	R2
0.512	1.063	0.276	TC	R2
0.512	1.102	0.197	TC	R2
0.512	1.102	0.276	SB2	G2
0.512	1.102	0.276	SC	RS
0.512	1.102	0.276	TC	R2
0.512	1.181	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.512	1.181	0.315	SC	R2
0.512	1.181	0.315	TC	R2
0.512	1.220	0.335	VC	R2
0.512	1.260	0.236	SC	R2
0.512	1.260	0.276	SC	R2
0.512	1.260	0.276	TC	R2
0.512	1.260	0.354	VC	R2
0.512	1.260	0.413	VB	G2
0.512	1.378	0.276	TC	R2
0.525	0.750	0.118	WPC	R4
0.531	0.875	0.126	VB	C2
0.531	0.999	0.252	TB2	G2
0.535	1.130	0.244	TB2	P2
0.539	0.945	0.197	SC	R2
0.539	0.945	0.197	TC	R2
0.539	0.984	0.197	TC	R3
0.543	0.945	0.197	TC	R2
0.551	0.650	0.118	VB	CPA
0.551	0.709	0.079	KB	C2
0.551	0.709	0.118	VB	G2
0.551	0.787	0.118	VB	G2
0.551	0.787	0.126	KC	R2
0.551	0.787	0.157	KC	R2
0.551	0.787	0.157	VC	R2
0.551	0.787	0.197	SC	R2
0.551	0.787	0.276	TC	R2
0.551	0.827	0.157	SC	R2
0.551	0.827	0.157	TC	R2
0.551	0.827	0.236	KC	R2
0.551	0.866	0.118	VB	G2
0.551	0.866	0.157	SC	R2
0.551	0.866	0.157	TC	R2
0.551	0.866	0.157	VB	G2
0.551	0.866	0.157	VC	R2
0.551	0.866	0.197	SB	G2
0.551	0.866	0.197	SC	R2
0.551	0.866	0.197	TC	R2
0.551	0.866	0.236	SC	R2
0.551	0.866	0.236	TC	RPA
0.551	0.866	0.276	SC	R2
0.551	0.866	0.276	TC	R2
0.551	0.906	0.236	TC	R2
0.551	0.945	0.157	KC	R2
0.551	0.945	0.157	TC	R2
0.551	0.945	0.157	VB	CPA
0.551	0.945	0.157	VC	R2
0.551	0.945	0.197	SC	R2
0.551	0.945	0.197	TC	R2
0.551	0.945	0.236	KC	R2
0.551	0.945	0.236	SB	G2
0.551	0.945	0.236	SC	R2
0.551	0.945	0.236	TB	G2
0.551	0.945	0.236	TC	R2
0.551	0.945	0.276	SC	R2

Shaft	Bore	Width	Lip Style	Material
0.551	0.945	0.276	TB	G2
0.551	0.945	0.276	TC	R2
0.551	0.945	0.299	SC	R2
0.551	0.945	0.315	SC	R2
0.551	0.945	0.315	TC	R2
0.551	0.984	0.157	TC	R2
0.551	0.984	0.197	SC	R2
0.551	0.984	0.197	TC	R2
0.551	0.984	0.197	VC	R2
0.551	0.984	0.236	SC	R2
0.551	0.984	0.276	TB	G2
0.551	0.984	0.276	TC	R2
0.551	0.984	0.354	TC	R2
0.551	1.024	0.197	SC	R2
0.551	1.024	0.236	SC	R2
0.551	1.024	0.236	TC	R2
0.551	1.024	0.276	SC	R2
0.551	1.024	0.276	TC	R2
0.551	1.024	0.315	SC	R2
0.551	1.024	0.315	TC	R2
0.551	1.024	0.374	DC	R2
0.551	1.063	0.236	SC	R2
0.551	1.063	0.276	SC	R2
0.551	1.063	0.276	TC	R2
0.551	1.063	0.394	TC	R2
0.551	1.102	0.236	SC	R2
0.551	1.102	0.276	SB2	G2
0.551	1.102	0.276	SC	R2
0.551	1.102	0.276	TC	R2
0.551	1.102	0.276	TC	R2
0.551	1.102	0.315	TB2	G2
0.551	1.102	0.315	TC	R2
0.551	1.102	0.394	SC	RV
0.551	1.122	0.276	TC	R2
0.551	1.142	0.276	TC	R2
0.551	1.181	0.157	SC	R2
0.551	1.181	0.276	SC	R2
0.551	1.181	0.276	TC	R2
0.551	1.181	0.295	TC	RPA
0.551	1.181	0.315	TC	R2
0.551	1.181	0.354	TC	R2
0.551	1.181	0.394	TC	R2
0.551	1.220	0.335	VC	R2
0.551	1.260	0.197	SC	R2
0.551	1.260	0.276	DC	R2
0.551	1.260	0.276	TB2	G2
0.551	1.260	0.276	TC	R2
0.551	1.260	0.295	TC	RPA
0.551	1.260	0.354	SC	R2
0.551	1.260	0.394	TC	R2
0.551	1.276	0.291	SC	R2
0.551	1.299	0.236	TC	R2
0.551	1.378	0.177	SC	R2
0.551	1.378	0.276	TC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.551	1.378	0.315	TC	R2
0.551	1.378	0.394	TC	R2
0.551	1.417	0.276	TC	R2
0.551	1.575	0.276	TC	R2
0.551	1.575	0.394	TC	R2
0.551	1.654	0.236	SC	RV
0.554	0.999	0.252	SB2	G2
0.562	1.063	0.177	SBR	C2
0.562	1.124	0.252	TB2	P2
0.563	0.813	0.126	WPB	G4
0.563	0.813	0.189	VBR	CPA
0.563	0.860	0.157	TC	R2
0.563	0.875	0.189	VB	P2
0.563	0.961	0.197	VC	R2
0.563	0.999	0.252	SB	PV
0.563	0.999	0.252	SB	PV
0.563	0.999	0.252	TB	G2
0.563	1.000	0.252	TB	G2
0.563	1.000	0.252	TC	R2
0.563	1.000	0.374	TA2	G2
0.563	1.004	0.252	TBR	GPA
0.563	1.063	0.252	SC	RV
0.563	1.125	0.252	SC	RV
0.563	1.125	0.252	TC	R2
0.563	1.125	0.469	TA2	G2
0.563	1.375	0.252	SC	R2
0.563	1.378	0.252	TB2	P2
0.571	1.260	0.276	TC	R2
0.571	1.260	0.354	VC	R2
0.571	1.260	0.417	VB	G2
0.577	1.124	0.315	DB	PV
0.583	1.181	0.177	SC	R2
0.583	1.181	0.197	SC	R2
0.583	1.181	0.276	SC	R2
0.583	1.181	0.295	TC	RPA
0.583	1.260	0.295	TC	RPA
0.583	1.378	0.295	TC	RPA
0.590	1.377	0.189	TB2	C2
0.591	0.748	0.118	VB	C2
0.591	0.748	0.236	VC	R2
0.591	0.787	0.118	SB	G2
0.591	0.787	0.197	KB	G2
0.591	0.827	0.079	VB	G2
0.591	0.827	0.118	KB	C2
0.591	0.827	0.118	VB	G2
0.591	0.827	0.118	VC	R2
0.591	0.827	0.165	TBR	G2
0.591	0.827	0.197	SC	R2
0.591	0.827	0.197	TB	C2
0.591	0.827	0.197	TBR	G2
0.591	0.827	0.197	TC	R2
0.591	0.827	0.197	VC	R2
0.591	0.827	0.236	TBR	G2
0.591	0.827	0.157	SB2	P2

Shaft	Bore	Width	Lip Style	Material
0.591	0.866	0.157	TB	C2
0.591	0.866	0.157	TC	R2
0.591	0.866	0.157	VB	G2
0.591	0.866	0.197	TC	R2
0.591	0.866	0.197	VC	R2
0.591	0.866	0.236	SC	R2
0.591	0.866	0.276	SC	R2
0.591	0.866	0.276	TC	R2
0.591	0.906	0.118	VC	R2
0.591	0.906	0.157	VC	R2
0.591	0.906	0.276	TC	R2
0.591	0.945	0.157	SC	R2
0.591	0.945	0.197	KC	R2
0.591	0.945	0.197	SC	R2
0.591	0.945	0.197	SC	RS
0.591	0.945	0.197	SC	R2
0.591	0.945	0.197	TC	R2
0.591	0.945	0.236	TC	R2
0.591	0.945	0.276	DB	G2
0.591	0.945	0.276	DC	RS
0.591	0.945	0.276	SB	G2
0.591	0.945	0.276	SC	R2
0.591	0.945	0.276	TB	G2
0.591	0.945	0.276	TC	R2
0.591	0.984	0.118	KC	R2
0.591	0.984	0.157	VC	R2
0.591	0.984	0.197	SB	C2
0.591	0.984	0.197	SC	R2
0.591	0.984	0.197	TC	RPA
0.591	0.984	0.197	TC	R2
0.591	0.984	0.236	KC	R2
0.591	0.984	0.236	SB	G2
0.591	0.984	0.236	SC	R2
0.591	0.984	0.236	TC	R2
0.591	0.984	0.276	SC	R2
0.591	0.984	0.276	TB	G2
0.591	0.984	0.276	TC	R2
0.591	0.984	0.315	TC	R2
0.591	0.984	0.394	SC	RV
0.591	1.004	0.177	TC	RV
0.591	1.004	0.256	TBR	G2
0.591	1.004	0.276	SC	R2
0.591	1.004	0.276	TC	R2
0.591	1.024	0.138	VC	R2
0.591	1.024	0.157	SC	R2
0.591	1.024	0.157	TB2	C2
0.591	1.024	0.197	SC	R2
0.591	1.024	0.197	TC	RPA
0.591	1.024	0.236	KC	R2
0.591	1.024	0.236	SC	R2
0.591	1.024	0.236	TB	G2
0.591	1.024	0.236	TC	R2
0.591	1.024	0.276	SB2	G2

Shaft	Bore	Width	Lip Style	Material
0.591	1.024	0.276	SB2	C2
0.591	1.024	0.276	SC	R2
0.591	1.024	0.276	TB	C2
0.591	1.024	0.276	TC	R2
0.591	1.024	0.276	TC	R2
0.591	1.024	0.276	TC	R2
0.591	1.024	0.315	TC	R2
0.591	1.024	0.354	SB	G2
0.591	1.024	0.354	TC	R2
0.591	1.063	0.276	TC	R2
0.591	1.063	0.315	TC	R2
0.591	1.102	0.157	SC	R2
0.591	1.102	0.157	TC	R2
0.591	1.102	0.197	SC	R2
0.591	1.102	0.236	SC	R2
0.591	1.102	0.236	TC	R2
0.591	1.102	0.276	SB	G2
0.591	1.102	0.276	SC	R2
0.591	1.102	0.276	TC	R2
0.591	1.102	0.315	TC	R2
0.591	1.102	0.394	DC	R2
0.591	1.102	0.394	TC	R2
0.591	1.107	0.276	TC	RPA
0.591	1.122	0.276	TC	R2
0.591	1.142	0.276	TC	R2
0.591	1.165	0.157	TB	G2
0.591	1.181	0.177	SC	R2
0.591	1.181	0.197	SC	R2
0.591	1.181	0.197	TC	R2
0.591	1.181	0.197	VB2	G2
0.591	1.181	0.197	VC	R2
0.591	1.181	0.236	SC	R2
0.591	1.181	0.276	DB	G2
0.591	1.181	0.276	DC	R3
0.591	1.181	0.276	SB2	G2
0.591	1.181	0.276	SC	R2
0.591	1.181	0.276	TB	G2
0.591	1.181	0.276	TC	R2
0.591	1.181	0.295	TC	RPA
0.591	1.181	0.315	SC	R2
0.591	1.181	0.315	TB2	G2
0.591	1.181	0.315	TC	R2
0.591	1.181	0.394	SC	R2
0.591	1.181	0.394	TC	R2
0.591	1.220	0.157	TC	R2
0.591	1.220	0.276	TC	R2
0.591	1.260	0.197	TC	R2
0.591	1.260	0.236	VB	G2
0.591	1.260	0.276	DC	R2
0.591	1.260	0.276	SC	R2
0.591	1.260	0.276	TC	R2
0.591	1.260	0.295	TC	RPA
0.591	1.260	0.354	TC	R2
0.591	1.299	0.276	SC	R2

Shaft	Bore	Width	Lip Style	Material
0.591	1.299	0.276	TC	R2
0.591	1.378	0.157	SC	R2
0.591	1.378	0.197	SB2	G2
0.591	1.378	0.197	TC	R2
0.591	1.378	0.209	SC	RV
0.591	1.378	0.236	TC	R2
0.591	1.378	0.276	SB2	C2
0.591	1.378	0.276	SC	RV
0.591	1.378	0.276	SC	R2
0.591	1.378	0.276	TB	G2
0.591	1.378	0.276	TC	R2
0.591	1.378	0.276	TC	R2
0.591	1.378	0.315	SC	RV
0.591	1.378	0.315	SC	R2
0.591	1.378	0.315	TC	R2
0.591	1.378	0.394	TC	R2
0.591	1.417	0.236	SC	R2
0.591	1.417	0.276	TC	R2
0.591	1.436	0.315	DC	RH
0.591	1.457	0.276	TC	R2
0.591	1.496	0.276	TC	R2
0.591	1.496	0.394	TC	R2
0.591	1.575	0.276	TC	R2
0.591	1.575	0.315	SC	R2
0.591	1.575	0.315	TC	R2
0.591	1.575	0.394	SC	R2
0.591	1.575	0.394	TC	R2
0.591	1.654	0.276	SC	R2
0.591	1.654	0.276	TC	R2
0.591	1.654	0.315	TC	R2
0.591	1.654	0.394	TC	R2
0.593	0.937	0.189	VB2	P2
0.593	1.375	0.311	TB2	P2
0.594	0.935	0.177	VC	R2
0.594	1.048	0.189	VBR	G2
0.594	1.124	0.311	SB2	P2
0.594	1.124	0.311	TB2	P2
0.594	1.125	0.189	SB2	G2
0.594	1.375	0.240	SB	G2
0.603	0.810	0.094	VC	R2
0.603	0.810	0.094	VC	R2
0.610	0.925	0.217	SB	CV
0.610	1.185	0.276	SB	G2
0.614	0.999	0.252	VC	R2
0.614	1.004	0.276	TC	R2
0.621	1.024	0.085	VC	R2
0.621	1.024	0.085	VC	R2
0.622	1.122	0.157	TC	R2
0.625	0.813	0.094	VB	P2
0.625	0.813	0.094	VB	P2
0.625	0.813	0.094	VBR	C2
0.625	0.813	0.094	VC	R2
0.625	0.813	0.126	VC	R2
0.625	0.871	0.169	VBR	G2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.625	0.875	0.098	VC	R2
0.625	0.875	0.126	SB	G2
0.625	0.875	0.126	SB	P2
0.625	0.875	0.126	TBR	C2
0.625	0.875	0.126	VB	G2
0.625	0.875	0.126	VC	R2
0.625	0.875	0.126	WPB	G4
0.625	0.933	0.189	VB	PV
0.625	0.933	0.189	VB	PV
0.625	0.937	0.173	VB	G2
0.625	0.937	0.189	TC	R2
0.625	0.937	0.189	VC	RPA
0.625	0.937	0.189	WPB	G4
0.625	0.999	0.252	TB	G2
0.625	0.999	0.252	TBR	P2
0.625	0.999	0.252	TBR	P2
0.625	0.999	0.252	TC	R2
0.625	1.000	0.126	VB	G2
0.625	1.000	0.126	VBR	P2
0.625	1.000	0.189	SC	R2
0.625	1.000	0.252	SB	P2
0.625	1.000	0.252	SC	R2
0.625	1.000	0.252	SC	R2
0.625	1.000	0.252	TBR	G2
0.625	1.000	0.252	TBR	G2
0.625	1.000	0.252	TBR	P2
0.625	1.000	0.252	VB	C2
0.625	1.063	0.189	VB	C2
0.625	1.063	0.252	TB	C2
0.625	1.063	0.252	VB	GV
0.625	1.063	0.252	WPB	G4
0.625	1.124	0.189	SB	G2
0.625	1.124	0.252	SB2	P2
0.625	1.124	0.252	TB2	P2
0.625	1.124	0.531	KB2	C2
0.625	1.125	0.150	SC	R2
0.625	1.125	0.252	SB2	P2
0.625	1.125	0.252	SB2	P2
0.625	1.125	0.252	SC	R2
0.625	1.125	0.252	SC	RV
0.625	1.125	0.252	SC	R2
0.625	1.125	0.252	SC	R2
0.625	1.125	0.252	SC	R2
0.625	1.125	0.252	TB2	P2
0.625	1.125	0.252	TBR	P2
0.625	1.125	0.252	TC	RV
0.625	1.125	0.252	TC	R2
0.625	1.125	0.280	SC	R2
0.625	1.125	0.311	DC	R2
0.625	1.125	0.311	SC	R2
0.625	1.125	0.311	SC	R2
0.625	1.125	0.311	TB2	P2
0.625	1.125	0.311	TC	R2
0.625	1.125	0.374	SB	P2
0.625	1.125	0.374	TC	R2
0.625	1.240	0.252	TBR	G2

Shaft	Bore	Width	Lip Style	Material
0.625	1.250	0.252	SB2	PV
0.625	1.250	0.252	SBR	C2
0.625	1.250	0.252	TB2	G2
0.625	1.250	0.252	TC	R2
0.625	1.250	0.252	WPB	G4
0.625	1.250	0.276	TC	R2
0.625	1.250	0.311	SC	R2
0.625	1.250	0.406	SB2	GV
0.625	1.250	0.437	SA2	G2
0.625	1.260	0.252	SB2	G2
0.625	1.265	0.276	TC	R2
0.625	1.375	0.252	SB2	P2
0.625	1.375	0.252	SB2	P2
0.625	1.375	0.252	SC	R2
0.625	1.375	0.252	TB2	G2
0.625	1.375	0.252	TC	R2
0.625	1.375	0.252	VB2	G2
0.625	1.375	0.252	VB2	G2
0.625	1.375	0.311	TA2	G2
0.625	1.375	0.311	TB	G2
0.625	1.375	0.374	SC	R2
0.625	1.375	0.374	SC	R2
0.625	1.377	0.406	SA2	C2
0.625	1.500	0.250	TB2	P2
0.625	1.563	0.374	SB2	G2
0.625	1.575	0.311	TB2	P2
0.625	1.752	0.311	TB2	P2
0.626	1.378	0.374	DC	R2
0.630	0.787	0.098	VC	R2
0.630	0.827	0.157	KC	R2
0.630	0.827	0.177	TB	G2
0.630	0.827	0.236	TC	R2
0.630	0.866	0.118	SC	R2
0.630	0.866	0.118	VB	G2
0.630	0.866	0.118	VC	R2
0.630	0.866	0.157	SC	R2
0.630	0.866	0.157	TC	R2
0.630	0.866	0.276	TC	R2
0.630	0.878	0.094	VC	R2
0.630	0.894	0.079	VC	R2
0.630	0.906	0.118	KC	R2
0.630	0.906	0.118	VC	R2
0.630	0.906	0.197	VC	R2
0.630	0.906	0.256	SC	R2
0.630	0.945	0.118	VB	G2
0.630	0.945	0.157	KC	R2
0.630	0.945	0.157	SB	G2
0.630	0.945	0.157	SC	R2
0.630	0.945	0.157	TB	G2
0.630	0.945	0.157	TC	R2
0.630	0.945	0.157	VB	G2
0.630	0.945	0.157	VC	R2
0.630	0.945	0.197	SC	R2
0.630	0.945	0.197	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.630	0.945	0.236	SC	R2
0.630	0.945	0.236	TB	G2
0.630	0.945	0.236	TC	R2
0.630	0.945	0.276	SB	G2
0.630	0.945	0.276	SC	R2
0.630	0.945	0.276	TBR	C2
0.630	0.945	0.276	TC	R2
0.630	0.984	0.197	TC	R2
0.630	0.984	0.197	VC	R2
0.630	0.984	0.236	TC	R2
0.630	0.984	0.276	TB	G2
0.630	0.984	0.276	TC	R2
0.630	1.024	0.118	VC	R2
0.630	1.024	0.197	SC	R2
0.630	1.024	0.197	TC	R2
0.630	1.024	0.236	TC	RPA
0.630	1.024	0.236	TC	R2
0.630	1.024	0.276	SB	G2
0.630	1.024	0.276	SC	R2
0.630	1.024	0.276	TBR	G2
0.630	1.024	0.276	TC	R2
0.630	1.063	0.236	SC	RPA
0.630	1.063	0.276	TC	R2
0.630	1.102	0.236	TC	R2
0.630	1.102	0.276	SB	G2
0.630	1.102	0.276	SC	R2
0.630	1.102	0.276	SC	R2
0.630	1.102	0.276	TB	GV
0.630	1.102	0.276	TC	R2
0.630	1.122	0.315	TC	R2
0.630	1.142	0.276	TC	R2
0.630	1.181	0.118	VC	R2
0.630	1.181	0.177	SC	R2
0.630	1.181	0.177	TC	R2
0.630	1.181	0.177	VB	G2
0.630	1.181	0.197	SC	R2
0.630	1.181	0.197	TC	R2
0.630	1.181	0.197	VC	R2
0.630	1.181	0.236	TC	R2
0.630	1.181	0.252	SB2	G2
0.630	1.181	0.276	DC	R3
0.630	1.181	0.276	SC	R2
0.630	1.181	0.276	TB	GS
0.630	1.181	0.276	TB2	G2
0.630	1.181	0.276	TC	R2
0.630	1.181	0.315	KB2	G2
0.630	1.181	0.315	KC	R2
0.630	1.181	0.315	TBR	G2
0.630	1.181	0.315	TC	R2
0.630	1.181	0.394	SC	R2
0.630	1.181	0.394	TC	R2
0.630	1.260	0.276	SB	G2
0.630	1.260	0.276	SC	R2
0.630	1.260	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.630	1.260	0.315	TC	R2
0.630	1.260	0.394	TC	R2
0.630	1.339	0.157	TC	R2
0.630	1.378	0.276	SC	R2
0.630	1.378	0.276	TC	R2
0.630	1.378	0.315	SC	R2
0.630	1.378	0.315	TC	R2
0.630	1.378	0.394	SC	R2
0.630	1.378	0.394	TC	R2
0.630	1.417	0.276	TC	R2
0.630	1.457	0.276	TC	R2
0.630	1.496	0.276	SC	R2
0.630	1.496	0.315	TC	R2
0.630	1.575	0.276	SC	R2
0.630	1.575	0.276	TC	R2
0.630	1.575	0.315	SC	R2
0.630	1.575	0.394	SC	R2
0.630	1.575	0.394	TC	R2
0.630	1.654	0.236	TC	R2
0.630	1.850	0.276	TC	R2
0.646	1.181	0.197	TC	R2
0.650	0.844	0.118	VB	G2
0.650	0.906	0.197	KC	P2
0.650	1.220	0.276	TBR	GPA
0.656	1.250	0.252	SB	P2
0.656	1.250	0.252	SB	P2
0.656	1.575	0.252	SC	R2
0.656	1.575	0.252	TC	R2
0.657	1.124	0.311	SB2	P2
0.657	1.375	0.252	SB2	G2
0.657	1.575	0.252	SB	C2
0.661	1.299	0.374	DC	R2
0.665	1.102	0.197	SC	R2
0.665	1.142	0.315	TBR	CPA
0.669	0.819	0.126	VB	G2
0.669	0.827	0.126	VC	R4
0.669	0.846	0.118	VB	C2
0.669	0.866	0.197	VC	R2
0.669	0.866	0.236	VC	R2
0.669	0.906	0.118	KC	R2
0.669	0.906	0.118	VB	G2
0.669	0.906	0.118	VC	R2
0.669	0.906	0.157	KC	R2
0.669	0.945	0.098	KC	R2
0.669	0.945	0.118	KC	R2
0.669	0.945	0.157	KC	R2
0.669	0.945	0.197	KC	R2
0.669	0.945	0.197	SC	R2
0.669	0.945	0.197	TC	R2
0.669	0.945	0.236	KC	R2
0.669	0.945	0.276	TC	R2
0.669	0.984	0.157	SC	R2
0.669	0.984	0.157	TC	R2
0.669	0.984	0.197	KB	GP

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.669	0.984	0.197	SC	R2
0.669	0.984	0.197	VB	CV
0.669	0.984	0.236	TC	R2
0.669	0.984	0.276	SC	R2
0.669	0.984	0.276	TC	R2
0.669	0.984	0.394	TC	R2
0.669	0.984	0.472	KBR	C2
0.669	1.024	0.079	VC	R2
0.669	1.024	0.118	VC	RV
0.669	1.024	0.236	SC	R2
0.669	1.024	0.236	TC	R2
0.669	1.024	0.276	TB	G2
0.669	1.024	0.276	TC	R2
0.669	1.024	0.315	TC	R2
0.669	1.063	0.197	SC	R2
0.669	1.063	0.197	TC	R2
0.669	1.063	0.236	SC	R2
0.669	1.063	0.252	SB	C2
0.669	1.063	0.276	SC	R2
0.669	1.063	0.276	TC	R2
0.669	1.063	0.315	TC	R2
0.669	1.063	0.394	TC	R2
0.669	1.102	0.157	TC	R2
0.669	1.102	0.177	SC	R2
0.669	1.102	0.177	TC	R2
0.669	1.102	0.197	SB	G2
0.669	1.102	0.197	SC	R2
0.669	1.102	0.197	TC	R2
0.669	1.102	0.236	KC	R2
0.669	1.102	0.236	SB	G2
0.669	1.102	0.236	SC	R2
0.669	1.102	0.236	TB	G2
0.669	1.102	0.236	TC	R2
0.669	1.102	0.256	DB	G2
0.669	1.102	0.276	DB	G2
0.669	1.102	0.276	DC	R2
0.669	1.102	0.276	SB	G2
0.669	1.102	0.276	SC	RV
0.669	1.102	0.276	SC	R2
0.669	1.102	0.276	TB	G2
0.669	1.102	0.276	TB2	C2
0.669	1.102	0.276	TC	R2
0.669	1.102	0.287	SC	RV
0.669	1.102	0.315	DB	G2
0.669	1.102	0.315	DC	RV
0.669	1.102	0.315	TC	R2
0.669	1.114	0.276	SC	R2
0.669	1.122	0.276	DC	R2
0.669	1.122	0.276	TC	R2
0.669	1.122	0.315	DB	G2
0.669	1.122	0.394	TA2	C2
0.669	1.142	0.197	SC	R2
0.669	1.142	0.197	TC	R2
0.669	1.142	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.669	1.181	0.197	SC	R2
0.669	1.181	0.197	TC	R2
0.669	1.181	0.197	VC	R2
0.669	1.181	0.236	SC	R2
0.669	1.181	0.236	TB	G2
0.669	1.181	0.236	TC	RPA
0.669	1.181	0.236	TC	R2
0.669	1.181	0.276	DC	R2
0.669	1.181	0.276	SB2	P2
0.669	1.181	0.276	SB2	P2
0.669	1.181	0.276	SC	R2
0.669	1.181	0.276	TB	G2
0.669	1.181	0.276	TB2	G2
0.669	1.181	0.276	TC	R2
0.669	1.181	0.276	TC	R2
0.669	1.181	0.315	TA2	G2
0.669	1.181	0.315	TC	R2
0.669	1.181	0.354	DC	R2
0.669	1.181	0.394	TC	R2
0.669	1.187	0.185	SA2	G2
0.669	1.220	0.276	SC	R2
0.669	1.220	0.276	TC	R2
0.669	1.220	0.307	TBR	G2
0.669	1.220	0.315	TC	R2
0.669	1.250	0.252	VB2	G2
0.669	1.250	0.315	TC	R2
0.669	1.260	0.197	SC	R2
0.669	1.260	0.197	TC	R2
0.669	1.260	0.236	TC	R2
0.669	1.260	0.276	SC	R2
0.669	1.260	0.276	SC	R2
0.669	1.260	0.276	TB2	G2
0.669	1.260	0.276	TC	R2
0.669	1.260	0.315	DC	R3
0.669	1.260	0.315	SC	R2
0.669	1.260	0.315	TC	R2
0.669	1.260	0.354	TB	G2
0.669	1.299	0.276	DB	G2
0.669	1.299	0.276	SB2	C2
0.669	1.299	0.276	TB	G2
0.669	1.299	0.276	TC	R2
0.669	1.299	0.315	SB2	G2
0.669	1.339	0.157	TB	G2
0.669	1.339	0.157	TC	R2
0.669	1.339	0.177	SB	GPA
0.669	1.339	0.276	SC	R2
0.669	1.339	0.276	TC	R2
0.669	1.339	0.315	TB	G2
0.669	1.358	0.157	TC	R2
0.669	1.378	0.189	VC	R2
0.669	1.378	0.197	SC	R2
0.669	1.378	0.197	TC	R2
0.669	1.378	0.236	TC	R2
0.669	1.378	0.276	SB2	PV

Shaft	Bore	Width	Lip Style	Material
0.669	1.378	0.276	SC	R2
0.669	1.378	0.276	TC	R2
0.669	1.378	0.315	SB2	G2
0.669	1.378	0.315	SC	R2
0.669	1.378	0.315	TC	R2
0.669	1.378	0.394	TC	R2
0.669	1.417	0.276	TC	R2
0.669	1.457	0.276	SC	R2
0.669	1.457	0.276	TC	R2
0.669	1.457	0.394	TC	R2
0.669	1.496	0.276	SC	R2
0.669	1.496	0.276	TC	R2
0.669	1.496	0.315	TC	R2
0.669	1.496	0.394	TC	R2
0.669	1.571	0.197	TB	G2
0.669	1.575	0.197	TB	G2
0.669	1.575	0.197	TC	R2
0.669	1.575	0.236	SC	R2
0.669	1.575	0.236	TB2	G2
0.669	1.575	0.276	DC	R2
0.669	1.575	0.276	SC	R2
0.669	1.575	0.276	TC	R2
0.669	1.575	0.315	TC	R2
0.669	1.575	0.335	TC	R2
0.669	1.575	0.394	SB2	C2
0.669	1.575	0.394	TC	R2
0.669	1.654	0.276	TC	R2
0.669	1.772	0.276	TC	R2
0.669	1.811	0.236	TC	R2
0.669	1.850	0.276	SC	R2
0.669	1.850	0.276	TC	R2
0.669	1.850	0.315	TC	R2
0.669	1.850	0.394	SC	RPA
0.669	1.850	0.394	TC	R2
0.687	0.820	0.126	VB	GV
0.687	0.937	0.126	WPB	G4
0.687	0.999	0.189	VB	G2
0.687	0.999	0.189	WPB	G4
0.687	1.063	0.189	SB	C2
0.687	1.063	0.268	SBR	C2
0.687	1.124	0.252	VB	C2
0.687	1.125	0.252	SC	R2
0.687	1.125	0.252	TC	R2
0.687	1.125	0.311	DC	R2
0.687	1.125	0.374	SC	R2
0.687	1.129	0.311	TB	PPA
0.687	1.129	0.311	TB	PPA
0.687	1.156	0.252	SBR	C2
0.687	1.187	0.189	SB2	P2
0.687	1.187	0.252	SC	R2
0.687	1.249	0.252	SB	G2
0.687	1.250	0.252	SC	R2
0.687	1.250	0.252	TBR	G2
0.687	1.250	0.252	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.687	1.250	0.252	VC	R2
0.687	1.250	0.311	SBR	C2
0.687	1.250	0.374	TC	R2
0.687	1.375	0.311	SC	R2
0.688	1.003	0.189	WPB	G4
0.689	1.181	0.236	SC	R2
0.689	1.260	0.236	TC	R2
0.693	1.181	0.276	TC	R2
0.700	0.937	0.189	VB	C2
0.701	1.181	0.236	SC	R3
0.701	1.339	0.374	SC	R2
0.709	0.866	0.276	VC	R2
0.709	0.906	0.157	KC	R2
0.709	0.945	0.138	KC	R2
0.709	0.945	0.157	SC	R2
0.709	0.945	0.157	VB	GPA
0.709	0.945	0.157	VC	R2
0.709	0.945	0.197	TC	R2
0.709	0.945	0.236	KC	R2
0.709	0.945	0.276	TC	R2
0.709	0.984	0.157	TB	G2
0.709	0.984	0.276	TC	R2
0.709	1.024	0.157	KC	R2
0.709	1.024	0.157	VB	G2
0.709	1.024	0.236	SC	R2
0.709	1.024	0.276	TC	R2
0.709	1.039	0.150	TB2	C2
0.709	1.063	0.157	KC	R2
0.709	1.063	0.197	SC	R2
0.709	1.063	0.276	TC	R2
0.709	1.102	0.177	TC	RV
0.709	1.102	0.236	SC	R2
0.709	1.102	0.236	TC	R2
0.709	1.102	0.276	SC	R2
0.709	1.102	0.276	TB	G2
0.709	1.102	0.276	TC	R2
0.709	1.102	0.315	TB	G2
0.709	1.102	0.315	TC	R2
0.709	1.102	0.394	TC	R2
0.709	1.122	0.197	SB	P2
0.709	1.142	0.197	SC	R2
0.709	1.142	0.276	TC	R2
0.709	1.165	0.157	TB	G2
0.709	1.181	0.197	SC	R2
0.709	1.181	0.236	TC	R2
0.709	1.181	0.276	DC	R2
0.709	1.181	0.276	SC	R2
0.709	1.181	0.276	TB2	G2
0.709	1.181	0.276	TBR	G2
0.709	1.181	0.276	TC	R2
0.709	1.181	0.276	TC	R2
0.709	1.181	0.315	SBR	G2
0.709	1.181	0.315	TB2	G2
0.709	1.181	0.315	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.709	1.181	0.394	TC	R2
0.709	1.220	0.276	TC	R2
0.709	1.260	0.236	TC	R2
0.709	1.260	0.276	DC	R3
0.709	1.260	0.276	SC	R2
0.709	1.260	0.276	TB	G2
0.709	1.260	0.276	TC	R2
0.709	1.260	0.315	TBR	G2
0.709	1.260	0.315	TC	R2
0.709	1.260	0.394	TC	R2
0.709	1.339	0.276	TC	R2
0.709	1.339	0.315	TBR	G2
0.709	1.339	0.315	TBR	CPA
0.709	1.378	0.197	SC	R2
0.709	1.378	0.276	SC	R2
0.709	1.378	0.276	TC	R2
0.709	1.378	0.315	TC	R2
0.709	1.378	0.394	SC	R2
0.709	1.378	0.394	TC	R2
0.709	1.417	0.276	SC	R2
0.709	1.457	0.197	SC	R2
0.709	1.457	0.276	TC	R2
0.709	1.457	0.315	TC	R2
0.709	1.496	0.197	SC	R2
0.709	1.496	0.276	TC	R2
0.709	1.496	0.394	TC	R2
0.709	1.575	0.276	SC	R2
0.709	1.575	0.276	TC	R2
0.709	1.575	0.354	TC	R2
0.709	1.575	0.394	SC	R2
0.709	1.575	0.394	TC	R2
0.709	1.654	0.276	TC	R2
0.709	1.654	0.394	TC	R2
0.709	1.850	0.394	SC	R2
0.719	1.250	0.252	TB2	PPA
0.719	1.250	0.252	TC	R2
0.719	1.250	0.264	SB2	C2
0.719	1.375	0.350	TA2	G2
0.720	1.500	0.252	VB	P2
0.724	1.039	0.142	TB2	C2
0.728	1.024	0.177	VC	R2
0.728	1.102	0.276	TC	RPA
0.728	1.260	0.417	VB	G2
0.730	1.130	0.217	WPC	R4
0.734	1.625	0.374	DBR	G2
0.735	1.315	0.252	SC	RV
0.736	1.181	0.177	VB	G2
0.744	1.063	0.189	SBR	C2
0.744	1.102	0.197	SC	R2
0.744	1.181	0.197	SC	R2
0.748	0.925	0.236	KC	R2
0.748	0.984	0.236	TC	R2
0.748	1.004	0.236	KC	R2
0.748	1.024	0.118	KC	R2

Shaft	Bore	Width	Lip Style	Material
0.748	1.024	0.157	VC	R2
0.748	1.063	0.157	VB	G2
0.748	1.063	0.197	KC	R2
0.748	1.063	0.197	TC	R2
0.748	1.063	0.236	SC	R2
0.748	1.063	0.276	TC	R2
0.748	1.063	0.394	TC	R2
0.748	1.102	0.236	SC	R2
0.748	1.102	0.276	TC	R2
0.748	1.122	0.197	TB	G3
0.748	1.142	0.276	TC	R2
0.748	1.181	0.197	SC	R2
0.748	1.181	0.276	SC	R2
0.748	1.181	0.276	TB	G2
0.748	1.181	0.276	TC	R2
0.748	1.181	0.315	SC	R2
0.748	1.220	0.276	TC	R2
0.748	1.240	0.315	KC	R2
0.748	1.260	0.197	SC	R2
0.748	1.260	0.197	TC	R2
0.748	1.260	0.236	TC	R2
0.748	1.260	0.276	DC	R2
0.748	1.260	0.276	SB	G2
0.748	1.260	0.276	SC	R2
0.748	1.260	0.276	TC	R2
0.748	1.260	0.315	TB	G2
0.748	1.260	0.315	TC	R2
0.748	1.260	0.394	TC	R2
0.748	1.299	0.276	TC	R2
0.748	1.299	0.315	TC	R2
0.748	1.319	0.276	TC	R2
0.748	1.339	0.276	TC	R2
0.748	1.378	0.197	TC	R2
0.748	1.378	0.236	SC	R2
0.748	1.378	0.276	SC	R2
0.748	1.378	0.276	TC	R2
0.748	1.378	0.315	SC	R2
0.748	1.378	0.315	TB2	G2
0.748	1.378	0.315	TC	R2
0.748	1.378	0.394	SC	R2
0.748	1.378	0.394	TC	R2
0.748	1.417	0.236	TBR	G2
0.748	1.417	0.276	TC	R2
0.748	1.417	0.335	SC	R2
0.748	1.457	0.276	TC	R2
0.748	1.457	0.394	SB	G4
0.748	1.457	0.394	TC	R2
0.748	1.496	0.276	TC	R2
0.748	1.496	0.315	TC	R2
0.748	1.496	0.394	TC	R2
0.748	1.575	0.276	TC	R2
0.748	1.575	0.315	SC	R2
0.748	1.575	0.394	TC	R2
0.748	1.614	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.748	1.654	0.276	SC	R2
0.748	1.654	0.276	TC	R2
0.748	1.850	0.276	TC	R2
0.748	1.850	0.394	SC	R2
0.748	1.850	0.394	TC	R2
0.750	0.999	0.126	SB	C2
0.750	0.999	0.126	VB	P2
0.750	1.000	0.126	SC	R2
0.750	1.000	0.126	VB	G2
0.750	1.000	0.126	VB	C2
0.750	1.000	0.126	VB	C2
0.750	1.000	0.126	VC	R2
0.750	1.000	0.126	WPB	G4
0.750	1.000	0.156	TC	R2
0.750	1.000	0.252	TC	R2
0.750	1.042	0.161	VB	C2
0.750	1.063	0.181	VC	R2
0.750	1.063	0.189	SB	C2
0.750	1.063	0.189	TB	G2
0.750	1.065	0.181	VC	R2
0.750	1.124	0.157	VB	C2
0.750	1.124	0.157	VB	C2
0.750	1.124	0.189	SB	G2
0.750	1.125	0.157	SC	R2
0.750	1.125	0.173	VB	G2
0.750	1.125	0.189	DC	R2
0.750	1.125	0.189	SB	G2
0.750	1.125	0.189	SBR	G2
0.750	1.125	0.189	SBR	P2
0.750	1.125	0.189	SC	R2
0.750	1.125	0.189	SC	R2
0.750	1.125	0.189	WPB	G4
0.750	1.125	0.252	SB	G2
0.750	1.125	0.252	SC	R2
0.750	1.125	0.252	TC	R2
0.750	1.125	0.289	TC	R2
0.750	1.142	0.252	SC	R2
0.750	1.181	0.197	TC	R2
0.750	1.187	0.157	VB	C2
0.750	1.187	0.250	SB2	C2
0.750	1.187	0.252	SC	R2
0.750	1.250	0.189	SB	GV
0.750	1.250	0.189	SC	R2
0.750	1.250	0.252	KC	V3
0.750	1.250	0.252	SB	G2
0.750	1.250	0.252	SB	P2
0.750	1.250	0.252	SC	R2
0.750	1.250	0.252	SC	R2
0.750	1.250	0.252	TB	G2
0.750	1.250	0.252	TB	P2
0.750	1.250	0.252	TC	R2
0.750	1.250	0.252	VC	R2
0.750	1.250	0.252	WPB	G4
0.750	1.250	0.252	WPC	R4

Shaft	Bore	Width	Lip Style	Material
0.750	1.250	0.260	TB2	P2
0.750	1.250	0.311	SA2	G2
0.750	1.250	0.311	SBR	G2
0.750	1.250	0.311	TB	G2
0.750	1.250	0.311	TBR	G2
0.750	1.250	0.311	TBR	P2
0.750	1.250	0.374	SA2	P2
0.750	1.250	0.374	TA2	P2
0.750	1.250	0.406	KB	C2
0.750	1.250	0.437	KBR	C2
0.750	1.252	0.189	SB2	P2
0.750	1.254	0.252	TB2	P2
0.750	1.301	0.252	KB	C2
0.750	1.312	0.252	SB2	P2
0.750	1.312	0.311	TC	R2
0.750	1.313	0.252	TC	R2
0.750	1.313	0.311	TBR	G2
0.750	1.318	0.311	TBR	GPA
0.750	1.375	0.252	SC	R2
0.750	1.375	0.252	TB2	G2
0.750	1.375	0.252	TB2	P2
0.750	1.375	0.252	TBR	G2
0.750	1.375	0.252	TC	R2
0.750	1.375	0.252	VBR	C2
0.750	1.375	0.311	SA2	G2
0.750	1.375	0.311	TB2	P2
0.750	1.375	0.374	SB2	C2
0.750	1.375	0.374	TB2	P2
0.750	1.375	0.390	DC	R2
0.750	1.375	0.406	SC	R2
0.750	1.499	0.252	SB2	P2
0.750	1.499	0.252	VB	P2
0.750	1.500	0.189	TC	R2
0.750	1.500	0.252	SB2	P2
0.750	1.500	0.252	TB2	P2
0.750	1.500	0.252	TC	R2
0.750	1.575	0.252	SB2	C2
0.750	1.575	0.311	TC	R2
0.750	1.624	0.252	TB2	C2
0.750	1.624	0.252	TC	R2
0.750	1.625	0.311	SC	R2
0.750	1.750	0.252	SB2	G2
0.750	1.750	0.311	TBR	G2
0.750	1.752	0.252	TB2	P2
0.750	1.752	0.252	TC	R2
0.750	1.781	0.252	TB2	P2
0.750	1.783	0.252	TC	R2
0.750	1.828	0.252	SB2	P2
0.750	1.828	0.252	SB2	P2
0.750	1.874	0.252	TB2	G2
0.750	2.047	0.311	SB2	C2
0.750	2.441	0.394	TC	R2
0.760	1.232	0.177	SB	C2
0.760	1.378	0.224	TC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.762	1.156	0.252	SBR	C2
0.766	1.850	0.512	DC	R2
0.768	1.063	0.189	WPB	GV
0.768	1.142	0.197	SC	R2
0.768	1.969	0.197	TC	R2
0.780	1.181	0.197	TC	R2
0.780	1.181	0.276	TC	R2
0.781	1.067	0.181	VB	G2
0.781	1.250	0.126	VB	C2
0.781	1.250	0.252	TB2	G2
0.781	1.250	0.252	TC	R2
0.781	1.375	0.189	VB2	P2
0.781	1.375	0.252	SBR	G2
0.781	1.375	0.252	TB2	P2
0.781	1.375	0.311	SB2	G2
0.781	1.500	0.252	SB2	G2
0.781	1.625	0.252	SC	R2
0.781	1.750	0.311	SB2	G2
0.781	1.828	0.252	SB2	PPA
0.781	1.850	0.252	TC	R2
0.781	1.850	0.311	TC	R2
0.781	1.850	0.374	TC	R2
0.787	0.984	0.098	VC	R2
0.787	0.984	0.197	TC	R2
0.787	0.984	0.276	TC	R2
0.787	0.984	0.315	TC	R2
0.787	1.000	0.126	VC	R2
0.787	1.024	0.118	KBR	C2
0.787	1.024	0.157	SB	G2
0.787	1.024	0.157	SC	R2
0.787	1.024	0.157	TC	R2
0.787	1.024	0.157	VB	G2
0.787	1.024	0.157	VC	R2
0.787	1.024	0.177	KC	R2
0.787	1.024	0.197	KC	R2
0.787	1.024	0.197	TC	R2
0.787	1.024	0.220	TC	R2
0.787	1.063	0.157	KC	R2
0.787	1.063	0.197	TC	R2
0.787	1.063	0.236	TB	G2
0.787	1.102	0.157	SC	R2
0.787	1.102	0.157	TB	G2
0.787	1.102	0.157	TC	R2
0.787	1.102	0.157	VB	G2
0.787	1.102	0.157	WPB	G4
0.787	1.102	0.197	SC	R2
0.787	1.102	0.197	VC	R2
0.787	1.102	0.236	SC	R2
0.787	1.102	0.236	TB	G2
0.787	1.102	0.236	TC	R2
0.787	1.102	0.276	SC	R2
0.787	1.102	0.276	TC	R2
0.787	1.102	0.315	SB	G2
0.787	1.125	0.189	SB	G2

Shaft	Bore	Width	Lip Style	Material
0.787	1.181	0.157	SC	R2
0.787	1.181	0.157	VC	R2
0.787	1.181	0.177	TC	R2
0.787	1.181	0.197	SB	G2
0.787	1.181	0.197	SC	R2
0.787	1.181	0.197	TC	R2
0.787	1.181	0.217	TC	R2
0.787	1.181	0.236	SC	R2
0.787	1.181	0.236	TB2	G2
0.787	1.181	0.236	TBR	GPA
0.787	1.181	0.236	TC	R2
0.787	1.181	0.276	KC	R2
0.787	1.181	0.276	SB	G2
0.787	1.181	0.276	SC	RV
0.787	1.181	0.276	SC	R2
0.787	1.181	0.276	SC	RS
0.787	1.181	0.276	SC	R2
0.787	1.181	0.276	TB	G2
0.787	1.181	0.276	TBR	G2
0.787	1.181	0.276	TC	R2
0.787	1.181	0.276	TC	R2
0.787	1.181	0.276	VC	R2
0.787	1.181	0.315	DB	G2
0.787	1.181	0.315	TC	R2
0.787	1.181	0.354	TC	R2
0.787	1.181	0.394	DC	R2
0.787	1.181	0.394	TC	R2
0.787	1.220	0.197	TC	R2
0.787	1.220	0.276	SB	C2
0.787	1.220	0.276	SBR	G2
0.787	1.220	0.276	TB	G2
0.787	1.220	0.276	TBR	G2
0.787	1.220	0.276	TC	R2
0.787	1.260	0.197	SB	G2
0.787	1.260	0.197	SC	R2
0.787	1.260	0.197	TC	R2
0.787	1.260	0.197	VC	R2
0.787	1.260	0.236	SC	R2
0.787	1.260	0.236	TC	R2
0.787	1.260	0.276	SB	G2
0.787	1.260	0.276	SC	R2
0.787	1.260	0.276	TB	G2
0.787	1.260	0.276	TC	R2
0.787	1.260	0.295	TC	R2
0.787	1.260	0.315	TB	G2
0.787	1.260	0.315	TC	R2
0.787	1.260	0.394	TC	R2
0.787	1.299	0.276	TC	R2
0.787	1.299	0.394	TC	R2
0.787	1.339	0.157	SC	R2
0.787	1.339	0.197	SC	R2
0.787	1.339	0.236	SC	R2
0.787	1.339	0.256	SC	R2
0.787	1.339	0.276	SC	R2

Shaft	Bore	Width	Lip Style	Material
0.787	1.339	0.276	SC	R2
0.787	1.339	0.276	TC	R2
0.787	1.378	0.157	SC	R2
0.787	1.378	0.197	TC	R2
0.787	1.378	0.217	SC	R2
0.787	1.378	0.236	SC	R2
0.787	1.378	0.236	SC	R2
0.787	1.378	0.236	TC	R2
0.787	1.378	0.276	DB	G2
0.787	1.378	0.276	DC	R2
0.787	1.378	0.276	SB2	G2
0.787	1.378	0.276	SC	RV
0.787	1.378	0.276	SC	R2
0.787	1.378	0.276	TB2	G2
0.787	1.378	0.276	TC	RV
0.787	1.378	0.276	TC	R2
0.787	1.378	0.315	DC	R2
0.787	1.378	0.315	TB	G2
0.787	1.378	0.315	TC	R2
0.787	1.378	0.354	TC	R2
0.787	1.378	0.394	DC	RP
0.787	1.378	0.394	SC	R2
0.787	1.378	0.394	TB	G2
0.787	1.378	0.394	TC	R2
0.787	1.378	0.472	TC	R2
0.787	1.409	0.157	TB	G2
0.787	1.417	0.276	SC	R2
0.787	1.417	0.276	TC	R2
0.787	1.417	0.315	SC	R2
0.787	1.417	0.315	TC	R2
0.787	1.417	0.394	DC	R2
0.787	1.417	0.394	TC	R2
0.787	1.417	0.472	TC	R2
0.787	1.457	0.236	TC	R2
0.787	1.457	0.276	SC	R2
0.787	1.457	0.276	TC	R2
0.787	1.457	0.315	SC	R2
0.787	1.457	0.315	TC	R2
0.787	1.457	0.394	TC	R2
0.787	1.484	0.276	TC	R2
0.787	1.496	0.197	SC	R2
0.787	1.496	0.197	TC	R2
0.787	1.496	0.276	KC	R2
0.787	1.496	0.276	SC	R2
0.787	1.496	0.276	TC	R2
0.787	1.496	0.315	SC	R2
0.787	1.496	0.315	TC	R2
0.787	1.496	0.394	TC	R2
0.787	1.496	0.591	TC	R2
0.787	1.535	0.236	TC	R2
0.787	1.547	0.217	SC	R2
0.787	1.567	0.256	TC	R2
0.787	1.575	0.157	TB2	G3
0.787	1.575	0.197	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.787	1.575	0.197	VC	R2
0.787	1.575	0.276	DC	R2
0.787	1.575	0.276	SB2	G2
0.787	1.575	0.276	SC	R2
0.787	1.575	0.276	TB	G2
0.787	1.575	0.276	TC	R2
0.787	1.575	0.315	DC	RV
0.787	1.575	0.315	TC	R2
0.787	1.575	0.354	TC	R2
0.787	1.575	0.394	DC	R2
0.787	1.575	0.394	SB2	G2
0.787	1.575	0.394	SC	R2
0.787	1.575	0.394	TB2	G2
0.787	1.575	0.394	TC	R2
0.787	1.575	0.472	TC	R2
0.787	1.622	0.197	TC	R2
0.787	1.624	0.276	TC	R2
0.787	1.634	0.276	TB2	G3
0.787	1.654	0.217	SC	R2
0.787	1.654	0.236	SC	R2
0.787	1.654	0.236	SC	R2
0.787	1.654	0.236	SC	R2
0.787	1.654	0.236	TC	R2
0.787	1.654	0.276	SB2	C2
0.787	1.654	0.276	SC	R2
0.787	1.654	0.276	SC	R2
0.787	1.654	0.276	TC	R2
0.787	1.654	0.315	SB	G2
0.787	1.654	0.315	TC	R2
0.787	1.654	0.394	SA2	G2
0.787	1.654	0.394	TC	R2
0.787	1.654	0.472	TC	R2
0.787	1.673	0.394	SA2	G2
0.787	1.693	0.276	TC	R2
0.787	1.732	0.276	TC	R2
0.787	1.772	0.276	TC	R2
0.787	1.772	0.315	TC	R2
0.787	1.772	0.394	TC	R2
0.787	1.772	0.472	TC	R2
0.787	1.811	0.315	TC	R2
0.787	1.850	0.209	SC	RV
0.787	1.850	0.236	TC	R2
0.787	1.850	0.276	DC	R2
0.787	1.850	0.276	SB2	C2
0.787	1.850	0.276	SC	R2
0.787	1.850	0.276	TB2	P2
0.787	1.850	0.276	TC	R2
0.787	1.850	0.315	TC	R2
0.787	1.850	0.335	SC	RPA
0.787	1.850	0.354	TC	R2
0.787	1.850	0.394	SA2	G2
0.787	1.850	0.394	SC	R2
0.787	1.850	0.394	TC	R2
0.787	1.850	0.472	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.787	1.850	0.512	TC	R2
0.787	1.854	0.500	TB2	G2
0.787	1.890	0.276	SC	RV
0.787	1.890	0.276	TC	R2
0.787	1.890	0.315	TC	R2
0.787	1.890	0.394	TC	R2
0.787	1.929	0.276	TC	R2
0.787	1.969	0.315	TC	R2
0.787	1.969	0.354	TC	R2
0.787	1.969	0.394	TC	R2
0.787	2.047	0.157	VC	R2
0.787	2.047	0.236	SC	R2
0.787	2.047	0.236	TC	R2
0.787	2.047	0.276	SC	R2
0.787	2.047	0.276	TC	R2
0.787	2.047	0.315	SC	R2
0.787	2.047	0.315	TBR	G2
0.787	2.047	0.315	TC	R2
0.787	2.047	0.354	TC	R2
0.787	2.047	0.394	SC	R2
0.787	2.047	0.394	TC	R2
0.787	2.047	0.472	TC	R2
0.787	2.441	0.276	TC	R2
0.803	1.063	0.079	VC	R2
0.807	1.102	0.197	TB	G2
0.807	1.622	0.197	TB2	C2
0.813	1.063	0.126	WPB	G4
0.813	1.241	0.169	SB	C2
0.813	1.250	0.189	SB	G2
0.813	1.250	0.252	SB2	GV
0.813	1.250	0.252	TBR	G2
0.813	1.250	0.252	TBR	C2
0.813	1.375	0.236	VB2	P2
0.813	1.375	0.252	TC	R2
0.813	1.375	0.311	TB2	PV
0.813	1.375	0.311	TBR	C2
0.813	1.375	0.374	SB2	G2
0.813	1.375	0.374	SB2	P2
0.813	1.375	0.374	TB	G2
0.813	1.437	0.252	TB2	G2
0.813	1.499	0.252	SB2	C2
0.813	1.500	0.252	SC	R2
0.813	1.624	0.252	TB	G2
0.813	1.625	0.252	TC	R2
0.813	1.750	0.189	SC	R2
0.827	1.063	0.197	KC	R2
0.827	1.102	0.157	SC	R2
0.827	1.102	0.217	TB	G2
0.827	1.142	0.157	KC	R2
0.827	1.181	0.256	TC	R2
0.827	1.181	0.394	TC	R2
0.827	1.220	0.276	TC	R2
0.827	1.260	0.197	TC	R2
0.827	1.260	0.236	TB	G2

Shaft	Bore	Width	Lip Style	Material
0.827	1.299	0.276	TC	R2
0.827	1.378	0.236	SC	R2
0.827	1.378	0.256	SC	R2
0.827	1.378	0.276	TC	R2
0.827	1.417	0.276	SC	R2
0.827	1.417	0.276	TC	R2
0.827	1.457	0.217	TC	R2
0.827	1.457	0.276	TC	R2
0.827	1.457	0.276	VB2	C2
0.827	1.457	0.276	VC	R2
0.827	1.575	0.276	TC	R2
0.827	1.890	0.315	TC	R2
0.843	1.375	0.252	SB2	P2
0.844	1.375	0.311	SB2	C2
0.844	1.828	0.311	TB2	C2
0.846	1.378	0.315	TC	R2
0.854	1.378	0.256	TC	R2
0.866	1.024	0.236	VC	R2
0.866	1.102	0.157	KC	R2
0.866	1.102	0.157	TC	R2
0.866	1.102	0.157	VB	G2
0.866	1.102	0.315	SC	R2
0.866	1.142	0.157	KC	R2
0.866	1.142	0.157	VC	R2
0.866	1.142	0.197	KC	R2
0.866	1.142	0.197	VC	R4
0.866	1.181	0.157	KC	R2
0.866	1.181	0.157	TC	R2
0.866	1.181	0.157	VB	G2
0.866	1.181	0.157	VC	R2
0.866	1.181	0.276	TC	R2
0.866	1.181	0.315	TC	R2
0.866	1.181	0.394	TC	R3
0.866	1.220	0.197	SC	R2
0.866	1.220	0.197	VC	R2
0.866	1.220	0.276	SB	C2
0.866	1.220	0.276	TC	R2
0.866	1.260	0.118	VB	G2
0.866	1.260	0.177	TC	R2
0.866	1.260	0.197	SC	R2
0.866	1.260	0.197	TC	R2
0.866	1.260	0.217	SB	G2
0.866	1.260	0.217	SC	R2
0.866	1.260	0.236	SC	R2
0.866	1.260	0.236	TC	R2
0.866	1.260	0.276	SB2	G2
0.866	1.260	0.276	SC	RS
0.866	1.260	0.276	SC	R2
0.866	1.260	0.276	TC	R2
0.866	1.260	0.315	TC	R2
0.866	1.299	0.276	TC	R2
0.866	1.299	0.394	TC	R2
0.866	1.339	0.276	SC	R2
0.866	1.339	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.866	1.358	0.236	SC	R2
0.866	1.378	0.197	TC	R2
0.866	1.378	0.217	SC	R2
0.866	1.378	0.236	SC	RV
0.866	1.378	0.236	SC	R2
0.866	1.378	0.236	TC	R2
0.866	1.378	0.252	SC	R2
0.866	1.378	0.276	DB	G2
0.866	1.378	0.276	DC	RS
0.866	1.378	0.276	SB2	P2
0.866	1.378	0.276	SC	RV
0.866	1.378	0.276	SC	R2
0.866	1.378	0.276	TB2	G2
0.866	1.378	0.276	TB2	P2
0.866	1.378	0.276	TC	R2
0.866	1.378	0.315	SA2	G2
0.866	1.378	0.315	SB	G2
0.866	1.378	0.315	SC	R2
0.866	1.378	0.315	TC	R2
0.866	1.378	0.354	TC	R2
0.866	1.378	0.394	SA2	G2
0.866	1.378	0.394	SC	R2
0.866	1.378	0.394	TC	R2
0.866	1.398	0.236	SC	R2
0.866	1.417	0.197	TC	R2
0.866	1.417	0.236	SC	R2
0.866	1.417	0.276	SC	R2
0.866	1.417	0.276	TC	R2
0.866	1.417	0.315	TB2	G2
0.866	1.417	0.315	TC	R2
0.866	1.417	0.394	SB2	C2
0.866	1.417	0.394	TC	R2
0.866	1.457	0.197	TC	R2
0.866	1.457	0.236	TC	R2
0.866	1.457	0.276	TC	R2
0.866	1.457	0.315	TC	R2
0.866	1.496	0.197	TC	R2
0.866	1.496	0.236	SC	R2
0.866	1.496	0.276	TC	R2
0.866	1.496	0.315	SBR	G2
0.866	1.496	0.315	SC	R2
0.866	1.496	0.315	TB	G2
0.866	1.496	0.315	TC	R2
0.866	1.496	0.394	TB2	G3
0.866	1.496	0.394	TC	R2
0.866	1.535	0.276	TC	R2
0.866	1.575	0.157	TC	R2
0.866	1.575	0.276	DC	R2
0.866	1.575	0.276	SC	R2
0.866	1.575	0.276	TC	R2
0.866	1.575	0.315	TBR	C2
0.866	1.575	0.315	TC	R2
0.866	1.575	0.335	DC	R2
0.866	1.575	0.394	DC	R2

Shaft	Bore	Width	Lip Style	Material
0.866	1.575	0.394	SC	R2
0.866	1.575	0.394	TC	R2
0.866	1.575	0.433	TC	R2
0.866	1.575	0.472	TC	R2
0.866	1.624	0.236	TC	R2
0.866	1.624	0.276	TB2	G2
0.866	1.634	0.236	TC	R2
0.866	1.634	0.276	TB2	G2
0.866	1.654	0.197	TC	R2
0.866	1.654	0.236	TC	R2
0.866	1.654	0.276	SC	R2
0.866	1.654	0.276	TB2	P2
0.866	1.654	0.276	TC	R2
0.866	1.654	0.315	TC	R2
0.866	1.654	0.394	SB2	G2
0.866	1.654	0.394	TB2	G2
0.866	1.654	0.394	TC	R2
0.866	1.654	0.433	TC	R2
0.866	1.693	0.236	TC	R2
0.866	1.732	0.276	TC	R2
0.866	1.772	0.197	TC	R2
0.866	1.772	0.276	SC	R2
0.866	1.772	0.276	TC	R2
0.866	1.772	0.315	TC	R2
0.866	1.772	0.394	TC	R2
0.866	1.811	0.315	TC	R2
0.866	1.850	0.276	SC	R2
0.866	1.850	0.276	TC	R2
0.866	1.850	0.394	SC	R2
0.866	1.850	0.394	TC	R2
0.866	1.850	0.472	TC	R2
0.866	1.890	0.276	TC	R2
0.866	1.890	0.433	TC	R2
0.866	1.969	0.197	TC	R2
0.866	1.969	0.276	SC	R2
0.866	1.969	0.276	TC	R2
0.866	1.969	0.394	TC	R2
0.866	2.047	0.315	TC	R2
0.866	2.047	0.394	TC	R2
0.866	2.165	0.276	TC	R2
0.866	2.205	0.276	TC	R2
0.866	2.441	0.213	SC	R2
0.866	2.441	0.394	TC	RV
0.875	1.125	0.126	VB	G2
0.875	1.125	0.126	WPB	G4
0.875	1.125	0.126	WPB	G4
0.875	1.125	0.252	VB	G2
0.875	1.127	0.126	VC	R2
0.875	1.187	0.157	VB	G2
0.875	1.187	0.189	VB	C2
0.875	1.187	0.189	VC	R2
0.875	1.248	0.295	SBR	C2
0.875	1.250	0.181	VBR	P2
0.875	1.250	0.189	SB	G2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.875	1.250	0.189	SB	P2
0.875	1.250	0.189	SB	G2
0.875	1.250	0.189	SBR	G2
0.875	1.250	0.189	SC	RPA
0.875	1.250	0.189	TB	PPA
0.875	1.250	0.189	TC	R2
0.875	1.250	0.189	WPB	G4
0.875	1.250	0.252	SB2	GV
0.875	1.250	0.252	TBR	C2
0.875	1.250	0.276	SBR	G2
0.875	1.250	0.374	DB	G2
0.875	1.255	0.181	VB	PPA
0.875	1.260	0.252	TC	R2
0.875	1.308	0.252	VB	C2
0.875	1.313	0.220	SC	R2
0.875	1.313	0.252	KC	R2
0.875	1.313	0.252	SB	C2
0.875	1.313	0.252	VB2	P2
0.875	1.313	0.311	SC	RV
0.875	1.370	0.311	TC	R2
0.875	1.375	0.189	SB2	G2
0.875	1.375	0.252	SB2	G2
0.875	1.375	0.252	SBR	P2
0.875	1.375	0.252	SC	R2
0.875	1.375	0.252	SC	R2
0.875	1.375	0.252	TB2	G2
0.875	1.375	0.252	TB2	P2
0.875	1.375	0.252	TC	R2
0.875	1.375	0.252	VB	G2
0.875	1.375	0.252	VB2	G2
0.875	1.375	0.252	VC	R2
0.875	1.375	0.311	DC	R2
0.875	1.375	0.311	SA2	P2
0.875	1.375	0.311	SB	PPA
0.875	1.375	0.311	SB2	P2
0.875	1.375	0.311	SBR	G2
0.875	1.375	0.311	TB	P2
0.875	1.375	0.374	DBR	CV
0.875	1.375	0.374	DC	RH
0.875	1.375	0.374	SC	R2
0.875	1.375	0.390	TB	G2
0.875	1.437	0.252	VB	P2
0.875	1.499	0.252	SB2	P2
0.875	1.499	0.311	SA2	P2
0.875	1.499	0.311	SC	R2
0.875	1.500	0.252	SB2	G2
0.875	1.500	0.252	SC	R2
0.875	1.500	0.252	TB2	C2
0.875	1.500	0.252	VC	R2
0.875	1.500	0.311	DBR	C2
0.875	1.500	0.311	SB2	C2
0.875	1.500	0.311	SB2	C2
0.875	1.500	0.311	SBR	G2
0.875	1.500	0.311	SBR	G2

Shaft	Bore	Width	Lip Style	Material
0.875	1.500	0.311	TC	R2
0.875	1.500	0.374	SC	R2
0.875	1.524	0.126	SC	R2
0.875	1.575	0.185	SB	C2
0.875	1.575	0.185	SB	C2
0.875	1.575	0.252	SB2	P2
0.875	1.625	0.189	KB2	G2
0.875	1.625	0.252	TB2	G2
0.875	1.625	0.252	TB2	P2
0.875	1.625	0.311	SB2	P2
0.875	1.625	0.374	SC	R2
0.875	1.686	0.374	TC	R2
0.875	1.750	0.311	TB2	PV
0.875	1.750	0.374	SC	R2
0.875	1.874	0.252	TB2	G2
0.875	1.875	0.252	SB2	P2
0.875	1.875	0.252	TC	R2
0.875	1.875	0.374	SC	R2
0.875	2.000	0.252	SB2	P2
0.875	2.000	0.252	SC	R2
0.875	2.000	0.437	TB2	G2
0.875	2.047	0.311	TC	RV
0.875	2.050	0.374	SA2	GV
0.875	2.063	0.354	SC	R2
0.875	2.063	0.437	SC	R2
0.878	1.249	0.189	SA2	G2
0.882	1.378	0.236	SC	R2
0.886	1.142	0.197	VC	R2
0.894	1.850	0.276	SC	R2
0.900	1.500	0.252	VB	P2
0.900	1.500	0.252	VB2	P2
0.900	1.500	0.252	VC	R2
0.906	1.102	0.118	WPB	G4
0.906	1.181	0.157	VC	R2
0.906	1.252	0.217	VC	R2
0.906	1.260	0.197	KC	R2
0.906	1.260	0.197	TBR	G2
0.906	1.260	0.276	TC	R2
0.906	1.378	0.276	TC	R2
0.906	1.378	0.315	TB	G2
0.906	1.378	0.315	TC	R2
0.906	1.398	0.236	SC	R2
0.906	1.417	0.236	SC	RV
0.906	1.417	0.236	TC	R2
0.906	1.417	0.276	TC	R2
0.906	1.417	0.394	TC	R2
0.906	1.417	0.512	TC	R2
0.906	1.457	0.236	SC	R2
0.906	1.457	0.276	SC	R2
0.906	1.457	0.276	TC	R2
0.906	1.496	0.236	TC	R2
0.906	1.496	0.276	TC	R2
0.906	1.496	0.394	TC	R2
0.906	1.499	0.390	TB2	P2

Shaft	Bore	Width	Lip Style	Material
0.906	1.575	0.236	SC	R2
0.906	1.575	0.236	TC	R2
0.906	1.575	0.315	SC	R2
0.906	1.575	0.315	TC	R2
0.906	1.575	0.394	SC	R2
0.906	1.575	0.394	TC	R2
0.906	1.654	0.236	TC	R2
0.906	1.654	0.276	TC	R2
0.906	1.654	0.315	TC	R2
0.906	1.654	0.394	SC	R2
0.906	1.693	0.315	TC	R2
0.906	1.693	0.394	TC	R2
0.906	1.850	0.276	TC	R2
0.906	1.850	0.315	TC	R2
0.906	1.850	0.394	TC	R2
0.910	1.375	0.311	SB	G2
0.917	1.169	0.157	VC	R2
0.937	1.187	0.126	VC	R2
0.937	1.187	0.126	WPB	G4
0.937	1.375	0.252	TB	P2
0.937	1.375	0.252	TB	P2
0.937	1.375	0.252	VC	RV
0.937	1.437	0.252	SC	RV
0.937	1.437	0.252	VC	R2
0.937	1.499	0.252	TB2	P2
0.937	1.500	0.252	SC	RV
0.937	1.500	0.252	TB2	G2
0.937	1.500	0.374	TC	R2
0.937	1.578	0.311	TC	R2
0.937	1.624	0.252	TB2	P2
0.937	1.625	0.413	SC	R2
0.937	1.625	0.413	SC	R2
0.937	1.750	0.311	TC	R2
0.937	1.750	0.374	SC	R2
0.937	1.752	0.252	SB2	P2
0.937	1.828	0.252	SB2	C2
0.937	1.831	0.437	SA2	P2
0.937	1.850	0.311	TB2	P2
0.937	2.000	0.500	DB2	G2
0.938	1.375	0.252	VB2	P2
0.938	1.375	0.252	VB2	P2
0.938	1.500	0.252	SB2	P2
0.945	1.165	0.157	VC	R2
0.945	1.181	0.197	TB2	C2
0.945	1.220	0.157	VC	R2
0.945	1.220	0.197	KC	R2
0.945	1.248	0.157	VC	R4
0.945	1.260	0.157	TB	G2
0.945	1.260	0.157	TC	R2
0.945	1.260	0.276	SB	G2
0.945	1.260	0.276	TC	R2
0.945	1.299	0.276	TC	R2
0.945	1.307	0.157	VC	R2
0.945	1.339	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.945	1.358	0.276	SB2	C2
0.945	1.378	0.236	SC	R2
0.945	1.378	0.236	TC	R2
0.945	1.378	0.276	SC	R2
0.945	1.378	0.276	TC	R2
0.945	1.378	0.315	TC	R2
0.945	1.378	0.335	TB	C2
0.945	1.417	0.157	VC	R2
0.945	1.417	0.236	SC	R2
0.945	1.417	0.236	TB	G2
0.945	1.417	0.276	TC	R2
0.945	1.417	0.315	KC	R2
0.945	1.417	0.315	TC	R2
0.945	1.437	0.433	TC	R2
0.945	1.457	0.197	SC	R2
0.945	1.457	0.276	SC	R2
0.945	1.457	0.276	TC	R2
0.945	1.496	0.197	VC	R2
0.945	1.496	0.236	TBR	C2
0.945	1.496	0.276	TC	R2
0.945	1.496	0.315	TC	R2
0.945	1.496	0.335	TC	R2
0.945	1.496	0.394	TC	R2
0.945	1.575	0.256	SC	R2
0.945	1.575	0.276	SC	R2
0.945	1.575	0.276	TC	R2
0.945	1.575	0.315	SC	R2
0.945	1.575	0.315	TB2	G2
0.945	1.575	0.315	TC	R2
0.945	1.575	0.394	SC	R2
0.945	1.622	0.276	TB	G2
0.945	1.654	0.276	TC	R2
0.945	1.654	0.315	TC	R2
0.945	1.654	0.394	SC	R2
0.945	1.693	0.236	KC	R2
0.945	1.693	0.236	TC	R2
0.945	1.693	0.276	TC	R2
0.945	1.693	0.335	TBR	GPA
0.945	1.693	0.335	TC	R2
0.945	1.772	0.236	TC	R2
0.945	1.772	0.276	TC	R2
0.945	1.772	0.315	TC	R2
0.945	1.772	0.394	TC	R2
0.945	1.772	0.433	TC	R2
0.945	1.811	0.315	TC	R2
0.945	1.811	0.394	TC	R2
0.945	1.850	0.236	SC	R2
0.945	1.850	0.252	SC	R2
0.945	1.850	0.252	SC	R2
0.945	1.850	0.276	SC	R2
0.945	1.850	0.276	TC	R2
0.945	1.850	0.276	TC	R2
0.945	1.850	0.394	SC	R2
0.945	1.850	0.394	TC	R2
0.945	1.890	0.276	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.945	1.929	0.315	TC	R2
0.945	1.929	0.472	TC	R2
0.945	1.969	0.472	TC	R2
0.945	2.047	0.276	TC	R2
0.945	2.047	0.315	TC	R2
0.945	2.047	0.394	SC	R2
0.945	2.165	0.394	TC	R2
0.945	2.441	0.189	TB2	PV
0.945	2.441	0.276	TC	R2
0.945	3.031	0.709	TC	R2
0.953	1.356	0.276	SB	P2
0.965	1.750	0.311	TC	R2
0.965	1.969	0.354	TC	R2
0.965	2.000	0.374	SC	R2
0.965	2.000	0.374	SC	R2
0.968	1.499	0.311	SA2	G2
0.968	1.750	0.311	SBR	CV
0.969	1.250	0.126	VB	G2
0.969	1.406	0.252	TB	G2
0.969	1.500	0.252	SB2	C2
0.969	1.500	0.311	SB	G2
0.969	1.503	0.252	SB2	P2
0.969	1.624	0.252	SB2	PV
0.969	1.624	0.252	SB2	PV
0.969	1.624	0.252	TC	R2
0.969	1.750	0.311	SB2	G2
0.969	1.850	0.311	TB2	P2
0.969	1.850	0.311	TC	R2
0.969	1.850	0.374	SB2	C2
0.969	2.047	0.374	TC	R2
0.969	2.440	0.252	TB2	PPA
0.969	2.440	0.252	TC	RPA
0.976	1.654	0.189	WPB	G4
0.976	1.654	0.189	WPB	G4
0.984	1.181	0.157	VC	R2
0.984	1.220	0.197	VC	R4
0.984	1.260	0.157	KB	G2
0.984	1.260	0.157	KC	R2
0.984	1.260	0.157	TC	R2
0.984	1.260	0.157	VB	G2
0.984	1.260	0.157	VC	R2
0.984	1.260	0.157	WPB	G4
0.984	1.260	0.197	VB	G2
0.984	1.260	0.236	SC	R2
0.984	1.260	0.236	TC	R2
0.984	1.260	0.276	TB	G2
0.984	1.260	0.276	TC	R2
0.984	1.299	0.157	SC	R2
0.984	1.299	0.157	VB	C2
0.984	1.299	0.197	TB	G2
0.984	1.299	0.236	SC	R2
0.984	1.299	0.236	TC	R2
0.984	1.339	0.197	TB	G2
0.984	1.339	0.197	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.984	1.339	0.197	VB	G2
0.984	1.339	0.276	SC	R2
0.984	1.339	0.276	TC	R2
0.984	1.375	0.189	SC	R2
0.984	1.378	0.157	VB	G2
0.984	1.378	0.157	WPC	R4
0.984	1.378	0.197	SC	R2
0.984	1.378	0.197	TC	R2
0.984	1.378	0.197	VB	G2
0.984	1.378	0.236	SB	G2
0.984	1.378	0.236	SC	R2
0.984	1.378	0.236	TC	R2
0.984	1.378	0.276	DB	G2
0.984	1.378	0.276	DC	R2
0.984	1.378	0.276	KC	R2
0.984	1.378	0.276	SB2	C2
0.984	1.378	0.276	SC	RV
0.984	1.378	0.276	SC	R2
0.984	1.378	0.276	TB	GV
0.984	1.378	0.276	TB2	C2
0.984	1.378	0.276	TC	RV
0.984	1.378	0.276	TC	RV
0.984	1.378	0.276	TC	R2
0.984	1.378	0.276	VC	R2
0.984	1.378	0.315	DC	RV
0.984	1.378	0.315	TB	GPA
0.984	1.378	0.315	TC	R2
0.984	1.378	0.335	TC	R2
0.984	1.378	0.354	SC	R2
0.984	1.378	0.354	TC	R2
0.984	1.378	0.394	DC	R2
0.984	1.378	0.394	TB	G2
0.984	1.378	0.394	TC	R2
0.984	1.417	0.236	TC	R2
0.984	1.417	0.276	SC	R2
0.984	1.417	0.276	TC	R2
0.984	1.417	0.287	SB2	GV
0.984	1.417	0.315	TC	R2
0.984	1.456	0.276	SB2	P2
0.984	1.457	0.197	SC	R2
0.984	1.457	0.197	SC	R2
0.984	1.457	0.197	TC	R2
0.984	1.457	0.236	SC	R2
0.984	1.457	0.236	TC	R2
0.984	1.457	0.276	DC	R2
0.984	1.457	0.276	KC	R2
0.984	1.457	0.276	SC	RS
0.984	1.457	0.276	SC	R2
0.984	1.457	0.276	TB	G2
0.984	1.457	0.276	TC	R2
0.984	1.457	0.295	SC	R2
0.984	1.457	0.315	SC	R2
0.984	1.457	0.315	TC	R2
0.984	1.496	0.157	VB	G2

Shaft	Bore	Width	Lip Style	Material
0.984	1.496	0.197	KB2	G2
0.984	1.496	0.197	SC	R2
0.984	1.496	0.197	VB2	G2
0.984	1.496	0.197	VC	R2
0.984	1.496	0.236	TC	R2
0.984	1.496	0.276	SC	R2
0.984	1.496	0.276	TB2	G2
0.984	1.496	0.276	TB2	P2
0.984	1.496	0.276	TC	R2
0.984	1.496	0.315	DC	R2
0.984	1.496	0.315	SA2	G2
0.984	1.496	0.315	TC	R2
0.984	1.496	0.394	TC	R2
0.984	1.498	0.252	SB2	CV
0.984	1.499	0.252	DC	R2
0.984	1.499	0.252	TB2	P2
0.984	1.499	0.252	TC	R2
0.984	1.500	0.252	TB2	P2
0.984	1.500	0.252	TC	R2
0.984	1.535	0.256	VB	G2
0.984	1.535	0.315	TC	R2
0.984	1.575	0.197	SC	R2
0.984	1.575	0.197	TC	R2
0.984	1.575	0.236	TC	RPA
0.984	1.575	0.236	TC	R2
0.984	1.575	0.276	SB2	P2
0.984	1.575	0.276	SC	R2
0.984	1.575	0.276	TB2	G2
0.984	1.575	0.276	TB2	P2
0.984	1.575	0.276	TC	R2
0.984	1.575	0.315	DC	R2
0.984	1.575	0.315	SC	R2
0.984	1.575	0.315	TB2	G2
0.984	1.575	0.315	TC	R2
0.984	1.575	0.354	DC	R2
0.984	1.575	0.354	TC	R2
0.984	1.575	0.394	DC	R2
0.984	1.575	0.394	SA2	G2
0.984	1.575	0.394	SB2	G2
0.984	1.575	0.394	SC	R2
0.984	1.575	0.394	TC	R2
0.984	1.575	0.394	TC	R2
0.984	1.575	0.433	TC	R2
0.984	1.575	0.472	DC	R2
0.984	1.575	0.472	TC	R2
0.984	1.585	0.276	TC	R2
0.984	1.614	0.236	TC	R2
0.984	1.614	0.276	TC	R2
0.984	1.624	0.236	TC	R2
0.984	1.624	0.276	TB2	G2
0.984	1.624	0.276	TC	R2
0.984	1.624	0.315	TC	R2
0.984	1.634	0.276	TA2	G2
0.984	1.634	0.276	TB2	G3
0.984	1.634	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.984	1.634	0.394	TC	R2
0.984	1.654	0.157	SC	R2
0.984	1.654	0.197	TC	R2
0.984	1.654	0.197	VC	R2
0.984	1.654	0.217	TC	R2
0.984	1.654	0.236	SC	R2
0.984	1.654	0.236	TC	R2
0.984	1.654	0.276	SC	R2
0.984	1.654	0.276	TC	R2
0.984	1.654	0.315	SB2	G2
0.984	1.654	0.315	SC	R2
0.984	1.654	0.315	TC	R2
0.984	1.654	0.335	SC	R2
0.984	1.654	0.335	TC	R2
0.984	1.654	0.394	SA2	C2
0.984	1.654	0.394	SC	R2
0.984	1.654	0.394	TC	R2
0.984	1.654	0.472	TC	R2
0.984	1.689	0.374	TC	R2
0.984	1.693	0.236	TC	R2
0.984	1.693	0.276	TC	R2
0.984	1.693	0.315	TB2	G2
0.984	1.693	0.315	TC	R2
0.984	1.693	0.354	TC	R2
0.984	1.693	0.394	SC	R2
0.984	1.693	0.394	TC	R2
0.984	1.693	0.472	TC	R2
0.984	1.732	0.276	TC	R2
0.984	1.732	0.315	TC	R2
0.984	1.732	0.331	TC	RV
0.984	1.732	0.394	TC	R2
0.984	1.750	0.394	TC	R2
0.984	1.772	0.256	SC	R2
0.984	1.772	0.276	TC	R2
0.984	1.772	0.315	TC	R2
0.984	1.772	0.354	TC	R2
0.984	1.772	0.394	DC	RP
0.984	1.772	0.394	SB2	G2
0.984	1.772	0.394	SC	R2
0.984	1.772	0.394	TB2	G2
0.984	1.772	0.394	TC	R2
0.984	1.772	0.433	TC	R2
0.984	1.772	0.472	TC	R2
0.984	1.811	0.276	SC	R2
0.984	1.811	0.276	TC	R2
0.984	1.828	0.189	WPB	G4
0.984	1.850	0.197	SC	R2
0.984	1.850	0.197	TC	R2
0.984	1.850	0.209	SC	RV
0.984	1.850	0.236	SC	R2
0.984	1.850	0.236	TB2	G2
0.984	1.850	0.236	TC	RPA
0.984	1.850	0.236	TC	R2
0.984	1.850	0.252	SB2	P2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
0.984	1.850	0.276	SC	RS
0.984	1.850	0.276	SC	RS
0.984	1.850	0.276	SC	R2
0.984	1.850	0.276	TB2	C2
0.984	1.850	0.276	TC	R2
0.984	1.850	0.315	DC	R2
0.984	1.850	0.315	SC	R2
0.984	1.850	0.315	TC	R2
0.984	1.850	0.394	DC	R2
0.984	1.850	0.394	SC	R2
0.984	1.850	0.394	TC	R2
0.984	1.850	0.472	TC	R2
0.984	1.890	0.276	TC	R2
0.984	1.890	0.315	SB2	P2
0.984	1.890	0.315	SC	R2
0.984	1.890	0.315	TC	R2
0.984	1.890	0.394	TC	R2
0.984	1.929	0.394	TC	R2
0.984	1.969	0.276	TC	R2
0.984	1.969	0.315	TC	R2
0.984	1.969	0.394	SC	R2
0.984	1.969	0.394	TC	R2
0.984	1.969	0.472	TC	R2
0.984	2.008	0.394	TC	R2
0.984	2.047	0.197	TC	R2
0.984	2.047	0.276	SC	R2
0.984	2.047	0.276	TC	R2
0.984	2.047	0.311	TB2	P2
0.984	2.047	0.315	DC	R2
0.984	2.047	0.315	SC	R2
0.984	2.047	0.315	TC	R2
0.984	2.047	0.354	DC	R2
0.984	2.047	0.374	TC	R2
0.984	2.047	0.394	SC	R2
0.984	2.047	0.394	TC	R2
0.984	2.047	0.394	TC	R2
0.984	2.047	0.394	TC	R2
0.984	2.047	0.472	SB2	G2
0.984	2.047	0.472	TC	R2
0.984	2.087	0.394	TC	R2
0.984	2.126	0.315	TC	R2
0.984	2.165	0.315	TC	R2
0.984	2.165	0.354	TC	R2
0.984	2.165	0.394	TC	R2
0.984	2.165	0.472	TC	R2
0.984	2.185	0.256	SB2	PV
0.984	2.205	0.472	TC	R2
0.984	2.283	0.394	TC	R2
0.984	2.362	0.276	TC	R3
0.984	2.362	0.394	TC	R2
0.984	2.441	0.236	SC	R2
0.984	2.441	0.236	TC	R2
0.984	2.441	0.276	SC	R2
0.984	2.441	0.276	TC	R2
0.984	2.441	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
0.984	2.441	0.315	SC	R2
0.984	2.441	0.315	TC	R2
0.984	2.441	0.394	SC	R2
0.984	2.441	0.394	TC	R2
0.984	2.441	0.472	TC	R2
0.984	2.520	0.512	TB2	G2
0.984	2.559	0.394	TC	R2
0.984	2.598	0.335	TC	R2
0.984	2.756	0.394	TC	R2
0.984	2.835	0.276	SC	R3
0.984	2.835	0.276	TC	R2
0.984	2.835	0.315	TC	R2
0.984	3.150	0.394	TC	R2
0.985	2.000	0.406	TA2	C2
0.987	1.500	0.252	TB2	G2
0.996	1.540	0.291	VC	R2
0.998	1.250	0.126	SBR	P2
0.998	1.250	0.126	SBR	P2
1.000	1.250	0.118	VB	G2
1.000	1.250	0.125	KB	G2
1.000	1.250	0.126	SC	R2
1.000	1.250	0.126	VB	C2
1.000	1.250	0.126	VB	C2
1.000	1.250	0.126	VC	R2
1.000	1.250	0.126	WPB	G4
1.000	1.250	0.126	WPC	R4
1.000	1.250	0.252	TC	R2
1.000	1.313	0.126	VB2	C2
1.000	1.319	0.220	KC	P2
1.000	1.322	0.209	SB2	C2
1.000	1.375	0.187	TC	R2
1.000	1.375	0.189	SBR	C2
1.000	1.375	0.189	SC	R2
1.000	1.375	0.189	VB	P2
1.000	1.375	0.189	VB	P2
1.000	1.375	0.189	VBR	G2
1.000	1.375	0.189	WPB	G4
1.000	1.375	0.220	KC	P2
1.000	1.375	0.250	TC	R2
1.000	1.375	0.252	SB	G2
1.000	1.375	0.252	SB	G2
1.000	1.375	0.252	SC	R2
1.000	1.375	0.252	TB2	P2
1.000	1.378	0.197	TC	R2
1.000	1.437	0.252	SB2	P2
1.000	1.437	0.252	SC	R2
1.000	1.437	0.252	TB2	G2
1.000	1.437	0.252	TC	R2
1.000	1.437	0.390	SB2	C2
1.000	1.449	0.228	TC	R2
1.000	1.455	0.276	TC	R2
1.000	1.455	0.441	TC	R2
1.000	1.459	0.220	TC	R2
1.000	1.469	0.189	SC	R2

Shaft	Bore	Width	Lip Style	Material
1.000	1.499	0.252	SB2	G2
1.000	1.499	0.252	TB	C2
1.000	1.499	0.252	TB2	P2
1.000	1.499	0.252	TC	R2
1.000	1.499	0.311	TB2	G2
1.000	1.500	0.189	TC	R2
1.000	1.500	0.189	WPB	G4
1.000	1.500	0.252	SB2	P2
1.000	1.500	0.252	SB2	PPA
1.000	1.500	0.252	SBR	GV
1.000	1.500	0.252	SC	R2
1.000	1.500	0.252	TB2	G2
1.000	1.500	0.252	TB2	P2
1.000	1.500	0.252	TC	R2
1.000	1.500	0.252	VC	R2
1.000	1.500	0.252	VC	R2
1.000	1.500	0.311	SB2	C2
1.000	1.500	0.311	TB2	G2
1.000	1.500	0.311	WPB	G4
1.000	1.500	0.327	TB	G2
1.000	1.500	0.374	SC	R2
1.000	1.500	0.374	TC	R2
1.000	1.500	0.390	DC	R2
1.000	1.500	0.390	SB	G2
1.000	1.500	0.390	TA2	G2
1.000	1.561	0.252	TB2	G2
1.000	1.563	0.189	VC	R2
1.000	1.575	0.252	TB2	P2
1.000	1.575	0.276	TC	R2
1.000	1.618	0.354	DC	R2
1.000	1.620	0.374	SA2	G2
1.000	1.624	0.189	VC	R2
1.000	1.624	0.250	SB2	P2
1.000	1.624	0.252	TC	R2
1.000	1.624	0.252	VB2	G2
1.000	1.624	0.252	WPB	G4
1.000	1.624	0.311	TC	R2
1.000	1.625	0.374	SC	R2
1.000	1.625	0.374	TC	R2
1.000	1.686	0.252	TB2	C2
1.000	1.686	0.311	TB	G2
1.000	1.687	0.311	SC	R2
1.000	1.687	0.311	TBR	C2
1.000	1.750	0.189	SB	G2
1.000	1.750	0.189	TC	R2
1.000	1.750	0.252	SC	R2
1.000	1.750	0.252	TB2	G2
1.000	1.750	0.252	TB2	P2
1.000	1.750	0.252	TC	R2
1.000	1.750	0.311	TB2	P2
1.000	1.750	0.327	SA2	G2
1.000	1.750	0.374	SB2	P2
1.000	1.750	0.374	SC	R2
1.000	1.750	0.437	TB2	C2

Shaft	Bore	Width	Lip Style	Material
1.000	1.752	0.252	SB2	PPA
1.000	1.752	0.252	SB2	PPA
1.000	1.752	0.252	TB2	P2
1.000	1.752	0.311	SB2	C2
1.000	1.752	0.374	SB2	G2
1.000	1.752	0.374	TC	R2
1.000	1.752	0.437	SA2	CV
1.000	1.781	0.374	VB2	C2
1.000	1.782	0.252	TC	R2
1.000	1.826	0.374	SB2	P2
1.000	1.828	0.252	SB2	G2
1.000	1.828	0.374	SA2	G2
1.000	1.833	0.252	TC	R2
1.000	1.851	0.252	SB2	P2
1.000	1.874	0.437	TB2	G2
1.000	1.875	0.252	TC	R2
1.000	1.875	0.437	SC	R2
1.000	1.967	0.252	TC	R2
1.000	1.979	0.252	TC	R2
1.000	1.980	0.311	TB2	P2
1.000	1.980	0.374	TB2	P2
1.000	1.983	0.252	TB2	G2
1.000	2.000	0.252	SC	R2
1.000	2.000	0.252	TB2	G2
1.000	2.000	0.252	TC	R2
1.000	2.000	0.252	VC	R2
1.000	2.000	0.311	TB2	P2
1.000	2.000	0.374	SC	R2
1.000	2.000	0.374	TBR	G2
1.000	2.000	0.374	TC	R2
1.000	2.000	0.500	SC	R2
1.000	2.000	0.500	TC	R2
1.000	2.040	0.252	TB2	G2
1.000	2.047	0.276	TC	R2
1.000	2.047	0.311	TB2	G2
1.000	2.062	0.252	TB2	P2
1.000	2.062	0.374	SA2	P2
1.000	2.063	0.252	SC	R2
1.000	2.063	0.374	SC	R2
1.000	2.125	0.374	SC	R2
1.000	2.313	0.311	TC	R2
1.000	2.362	0.315	TC	R2
1.000	2.441	0.374	TB2	G2
1.000	2.441	0.374	TB2	P2
1.000	2.441	0.374	TC	R2
1.000	2.500	0.311	TC	R2
1.012	1.378	0.276	TC	R2
1.016	1.499	0.252	SB2	P2
1.024	1.220	0.118	VB	G2
1.024	1.260	0.157	KC	R2
1.024	1.260	0.157	VBR	G2
1.024	1.260	0.197	SB	G2
1.024	1.339	0.157	KC	P2
1.024	1.339	0.157	SC	RV

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.024	1.339	0.157	VB	G2
1.024	1.339	0.354	KC	R2
1.024	1.378	0.157	VC	R2
1.024	1.378	0.276	TC	R2
1.024	1.417	0.197	TC	R2
1.024	1.417	0.276	TC	R2
1.024	1.457	0.236	SC	R2
1.024	1.457	0.236	TB	G2
1.024	1.457	0.276	SC	R2
1.024	1.457	0.276	TB	G2
1.024	1.457	0.276	TC	R2
1.024	1.457	0.315	TC	R2
1.024	1.496	0.197	SC	R2
1.024	1.496	0.197	TC	R2
1.024	1.496	0.236	SB	CPA
1.024	1.496	0.276	TC	R2
1.024	1.496	0.315	SC	R2
1.024	1.496	0.315	TC	R2
1.024	1.535	0.197	SC	R2
1.024	1.575	0.197	TC	R2
1.024	1.575	0.197	VC	R2
1.024	1.575	0.236	SC	R2
1.024	1.575	0.276	TC	R2
1.024	1.575	0.315	TC	R2
1.024	1.575	0.394	TC	R2
1.024	1.614	0.276	TC	R2
1.024	1.626	0.394	TC	R2
1.024	1.654	0.236	SC	R2
1.024	1.654	0.276	SC	R2
1.024	1.654	0.276	TC	R2
1.024	1.654	0.315	SB2	C2
1.024	1.654	0.315	SC	R2
1.024	1.654	0.315	TC	RPA
1.024	1.654	0.315	TC	R2
1.024	1.654	0.394	TA2	G2
1.024	1.654	0.394	TC	R2
1.024	1.693	0.236	TB	G2
1.024	1.693	0.276	TC	R2
1.024	1.693	0.315	TC	R2
1.024	1.732	0.276	TC	R2
1.024	1.772	0.276	TC	R2
1.024	1.772	0.315	TC	R2
1.024	1.772	0.394	SB	G2
1.024	1.772	0.394	TC	R2
1.024	1.850	0.197	TC	R2
1.024	1.850	0.236	TC	R2
1.024	1.850	0.276	SC	R2
1.024	1.850	0.315	DC	R2
1.024	1.850	0.315	TC	R2
1.024	1.850	0.354	SC	R2
1.024	1.850	0.394	SC	R2
1.024	1.850	0.394	TC	R2
1.024	1.850	0.433	TC	R2
1.024	1.850	0.472	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.024	1.890	0.276	TC	R2
1.024	1.890	0.315	TC	R2
1.024	1.969	0.276	TC	R2
1.024	1.969	0.394	TC	R2
1.024	2.047	0.276	SC	R2
1.024	2.047	0.276	TC	R2
1.024	2.047	0.315	DC	R2
1.024	2.047	0.315	SC	R2
1.024	2.441	0.354	TC	R2
1.024	2.835	0.394	TC	R2
1.031	1.575	0.311	TB2	G2
1.031	1.575	0.311	TB2	P2
1.031	1.575	0.311	TB2	P2
1.031	1.575	0.311	TC	R2
1.031	1.575	0.311	TC	R2
1.043	1.457	0.276	SC	RV
1.045	1.261	0.177	VB	GV
1.061	1.312	0.126	WPB	GV
1.061	1.328	0.161	WPC	R4
1.062	1.625	0.311	SBR	CPA
1.062	1.687	0.343	SB	C2
1.063	1.260	0.126	VB	G2
1.063	1.260	0.126	VC	R2
1.063	1.327	0.157	KB	C2
1.063	1.339	0.118	VB2	G2
1.063	1.339	0.157	KC	R2
1.063	1.371	0.189	TBR	P2
1.063	1.378	0.157	VB	G2
1.063	1.378	0.236	TC	R2
1.063	1.417	0.236	TC	R2
1.063	1.417	0.276	SC	R2
1.063	1.417	0.394	DC	R2
1.063	1.457	0.197	SC	R2
1.063	1.457	0.236	TC	R2
1.063	1.457	0.276	SB	G2
1.063	1.457	0.276	SC	R2
1.063	1.457	0.276	TC	R2
1.063	1.457	0.315	TC	R2
1.063	1.457	0.335	TC	R2
1.063	1.496	0.197	TC	R2
1.063	1.496	0.236	TC	R2
1.063	1.496	0.276	TC	R2
1.063	1.499	0.252	SB	P2
1.063	1.500	0.126	WPB	G4
1.063	1.500	0.189	WPB	G4
1.063	1.500	0.189	WPB	G4
1.063	1.500	0.252	VC	R2
1.063	1.561	0.126	VC	R2
1.063	1.563	0.126	VB	G2
1.063	1.575	0.177	TC	R2
1.063	1.575	0.197	TC	R2
1.063	1.575	0.236	KC	R2
1.063	1.575	0.236	SC	R2
1.063	1.575	0.236	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.063	1.575	0.276	TC	R2
1.063	1.575	0.315	TC	R2
1.063	1.575	0.394	TC	R2
1.063	1.575	0.472	TC	R2
1.063	1.614	0.276	TC	R2
1.063	1.614	0.394	SC	R2
1.063	1.625	0.189	VC	RPA
1.063	1.625	0.252	TB2	P2
1.063	1.625	0.311	SA2	P2
1.063	1.625	0.374	SC	R2
1.063	1.634	0.374	SB	G2
1.063	1.654	0.197	TC	R2
1.063	1.654	0.276	TC	R2
1.063	1.654	0.315	TC	R2
1.063	1.654	0.394	SC	R2
1.063	1.654	0.394	TC	R2
1.063	1.686	0.311	TBR	C2
1.063	1.693	0.315	SC	R2
1.063	1.693	0.315	TC	R2
1.063	1.693	0.354	TB	G2
1.063	1.693	0.354	TC	R2
1.063	1.750	0.252	TB2	P2
1.063	1.750	0.374	SC	R2
1.063	1.772	0.315	TC	R2
1.063	1.850	0.236	SC	R2
1.063	1.850	0.276	TC	R2
1.063	1.850	0.315	TC	R2
1.063	1.850	0.394	SC	R2
1.063	1.874	0.252	TB2	P2
1.063	1.890	0.315	TB	G2
1.063	1.890	0.315	TC	R2
1.063	1.929	0.295	TC	R2
1.063	1.929	0.394	SC	R2
1.063	1.969	0.394	TC	R2
1.063	1.980	0.374	TB2	P2
1.063	1.983	0.311	SA2	G2
1.063	2.000	0.252	TC	RV
1.063	2.047	0.315	SB2	P2
1.063	2.047	0.315	TC	R2
1.063	2.087	0.276	TC	R2
1.063	2.165	0.276	TC	R2
1.063	2.441	0.472	TA2	G2
1.087	1.575	0.217	TC	R2
1.088	1.625	0.276	SB	G2
1.094	1.875	0.374	SC	R2
1.100	1.563	0.252	SC	R2
1.100	1.572	0.307	SBR	CPA
1.102	1.260	0.276	VC	R2
1.102	1.339	0.157	KC	R2
1.102	1.378	0.098	VB	G2
1.102	1.378	0.118	VB	G2
1.102	1.378	0.157	KB	G2
1.102	1.378	0.157	KC	R2
1.102	1.378	0.157	VB	G2

Shaft	Bore	Width	Lip Style	Material
1.102	1.378	0.197	KB	C2
1.102	1.378	0.197	SC	R2
1.102	1.378	0.197	TC	R2
1.102	1.378	0.197	VC	R2
1.102	1.378	0.236	TC	R2
1.102	1.378	0.276	TC	R2
1.102	1.378	0.315	TC	R2
1.102	1.378	0.354	TC	R2
1.102	1.378	0.394	TC	R2
1.102	1.417	0.118	KB	C2
1.102	1.417	0.236	TB	G2
1.102	1.417	0.276	TC	R2
1.102	1.457	0.157	SB	C3
1.102	1.457	0.157	TC	R2
1.102	1.457	0.157	VC	R2
1.102	1.457	0.236	TB	G2
1.102	1.457	0.236	TC	R2
1.102	1.457	0.236	VB	G2
1.102	1.457	0.236	VBR	G2
1.102	1.457	0.236	VC	R2
1.102	1.457	0.276	SC	R2
1.102	1.457	0.276	TC	R2
1.102	1.457	0.315	TC	R2
1.102	1.496	0.157	VB	G2
1.102	1.496	0.197	TC	R2
1.102	1.496	0.197	VC	R2
1.102	1.496	0.217	SC	R2
1.102	1.496	0.236	SC	RV
1.102	1.496	0.256	SC	R2
1.102	1.496	0.256	VBR	C2
1.102	1.496	0.276	SB	G2
1.102	1.496	0.276	SC	R2
1.102	1.496	0.276	TC	R2
1.102	1.496	0.315	TA2	PPA
1.102	1.496	0.315	TC	R2
1.102	1.496	0.394	SB	G2
1.102	1.496	0.394	TC	R2
1.102	1.535	0.236	VBR	C2
1.102	1.535	0.252	VB	G2
1.102	1.575	0.197	TC	R2
1.102	1.575	0.197	VC	R2
1.102	1.575	0.276	SB	CPA
1.102	1.575	0.276	SBR	G2
1.102	1.575	0.276	SC	R2
1.102	1.575	0.276	TC	R2
1.102	1.575	0.315	DC	R2
1.102	1.575	0.315	TB	G2
1.102	1.575	0.315	TBR	G2
1.102	1.575	0.315	TC	R2
1.102	1.575	0.354	TC	R2
1.102	1.575	0.394	TC	R2
1.102	1.614	0.276	TC	R2
1.102	1.614	0.315	TB	G2
1.102	1.624	0.236	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.102	1.626	0.276	TBR	G2
1.102	1.634	0.276	TB	G2
1.102	1.634	0.315	TC	R2
1.102	1.654	0.157	VC	R2
1.102	1.654	0.217	SC	RPA
1.102	1.654	0.236	TC	R2
1.102	1.654	0.276	SA2	G2
1.102	1.654	0.276	SC	R2
1.102	1.654	0.276	TC	R2
1.102	1.654	0.315	TC	R2
1.102	1.654	0.394	TC	R2
1.102	1.654	0.433	TC	R2
1.102	1.673	0.315	TC	R2
1.102	1.693	0.236	TC	R2
1.102	1.693	0.276	SC	R2
1.102	1.693	0.394	SB	G4
1.102	1.693	0.394	TC	R2
1.102	1.732	0.236	TC	RPA
1.102	1.732	0.276	TC	R2
1.102	1.732	0.315	TC	R2
1.102	1.772	0.197	TC	R2
1.102	1.772	0.236	SC	R2
1.102	1.772	0.276	TC	R2
1.102	1.772	0.315	SC	R2
1.102	1.772	0.315	SC	R2
1.102	1.772	0.315	TC	R2
1.102	1.772	0.343	TC	R2
1.102	1.772	0.394	TC	R2
1.102	1.811	0.276	TC	R2
1.102	1.850	0.157	VC	R2
1.102	1.850	0.197	SC	R2
1.102	1.850	0.197	TC	R2
1.102	1.850	0.236	TC	R2
1.102	1.850	0.276	SC	R2
1.102	1.850	0.276	TC	R2
1.102	1.850	0.315	DC	R2
1.102	1.850	0.315	TA2	C2
1.102	1.850	0.315	TC	R2
1.102	1.850	0.354	TC	R2
1.102	1.850	0.394	DB	GV
1.102	1.850	0.394	SB2	G2
1.102	1.850	0.394	SC	R2
1.102	1.850	0.394	TC	R2
1.102	1.870	0.394	TA2	PPA
1.102	1.870	0.394	TB2	P3
1.102	1.890	0.276	TC	R2
1.102	1.890	0.315	TC	R2
1.102	1.890	0.394	TC	R2
1.102	1.890	0.433	SB2	G2
1.102	1.890	0.433	TB2	G2
1.102	1.890	0.433	TBR	C2
1.102	1.890	0.433	TC	R2
1.102	1.921	0.315	TB	G2
1.102	1.969	0.197	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.102	1.969	0.236	SC	R2
1.102	1.969	0.236	VB2	G2
1.102	1.969	0.276	TC	R2
1.102	1.969	0.315	SC	R2
1.102	1.969	0.315	TC	R2
1.102	1.969	0.394	TC	R2
1.102	2.008	0.315	TC	R3
1.102	2.008	0.394	TC	R2
1.102	2.047	0.197	SC	R2
1.102	2.047	0.236	TC	R2
1.102	2.047	0.276	SC	R2
1.102	2.047	0.276	TC	R2
1.102	2.047	0.315	TC	R2
1.102	2.047	0.394	SC	R2
1.102	2.047	0.394	TC	R2
1.102	2.126	0.394	TC	R2
1.102	2.126	0.472	SA2	C2
1.102	2.165	0.315	TC	R2
1.102	2.165	0.394	TC	R2
1.102	2.205	0.236	TC	R2
1.102	2.205	0.276	TC	R2
1.102	2.205	0.315	DC	R2
1.102	2.205	0.315	TC	R2
1.102	2.244	0.276	TC	R2
1.102	2.283	0.236	TC	R2
1.102	2.283	0.394	TC	R2
1.102	2.441	0.394	SC	R2
1.102	2.441	0.394	TC	R2
1.102	2.835	0.394	SC	R2
1.107	1.576	0.276	SC	R2
1.109	1.367	0.138	WPC	R4
1.110	1.500	0.197	SC	RPA
1.122	1.555	0.374	TC	R2
1.122	2.047	0.197	TC	R2
1.122	2.244	0.197	TC	R2
1.125	1.375	0.126	VB	G2
1.125	1.375	0.126	VB	G2
1.125	1.375	0.126	VB	G2
1.125	1.375	0.126	VC	R2
1.125	1.375	0.126	WPB	G4
1.125	1.375	0.189	KC	R2
1.125	1.437	0.205	VB	G2
1.125	1.438	0.217	VBR	G2
1.125	1.499	0.189	SB	P2
1.125	1.499	0.189	VB	P2
1.125	1.499	0.252	TC	R2
1.125	1.500	0.189	SC	R2
1.125	1.500	0.189	VBR	G2
1.125	1.500	0.189	VBR	P2
1.125	1.500	0.189	WPB	G4
1.125	1.500	0.252	KB	G2
1.125	1.500	0.252	KC	R2
1.125	1.500	0.252	SC	RPA
1.125	1.500	0.252	SC	R2

Shaft	Bore	Width	Lip Style	Material
1.125	1.500	0.252	TC	R2
1.125	1.500	0.252	VB	P2
1.125	1.561	0.252	VC	R2
1.125	1.561	0.252	WPB	G4
1.125	1.562	0.189	WPC	R4
1.125	1.562	0.252	SC	R2
1.125	1.563	0.252	SB	G2
1.125	1.563	0.252	VB2	G2
1.125	1.563	0.280	SC	R2
1.125	1.563	0.374	SA2	P2
1.125	1.563	0.374	SC	R2
1.125	1.624	0.252	TB2	P2
1.125	1.624	0.311	TA2	C2
1.125	1.625	0.189	SB2	C2
1.125	1.625	0.189	WPB	G4
1.125	1.625	0.220	KC	R2
1.125	1.625	0.252	KB2	G2
1.125	1.625	0.252	SB	G2
1.125	1.625	0.252	SB2	P2
1.125	1.625	0.252	SC	R2
1.125	1.625	0.252	TB2	G2
1.125	1.625	0.252	TC	R2
1.125	1.625	0.252	WPB	G4
1.125	1.625	0.311	SB	C2
1.125	1.625	0.311	SC	R2
1.125	1.625	0.374	SB	G2
1.125	1.625	0.374	SC	R2
1.125	1.625	0.374	TC	R2
1.125	1.661	0.311	SB	G2
1.125	1.687	0.311	TC	R2
1.125	1.750	0.252	SB	G2
1.125	1.750	0.374	DB	G2
1.125	1.750	0.374	SC	R2
1.125	1.752	0.252	TB2	P2
1.125	1.752	0.252	TC	R2
1.125	1.752	0.437	SB2	P2
1.125	1.752	0.437	TB	G2
1.125	1.778	0.406	KC	R2
1.125	1.780	0.252	TC	R2
1.125	1.781	0.311	TC	R2
1.125	1.781	0.406	TC	R2
1.125	1.781	0.500	TC	R2
1.125	1.813	0.252	SC	R2
1.125	1.819	0.268	TC	R2
1.125	1.828	0.252	TB	G2
1.125	1.850	0.311	SC	R2
1.125	1.850	0.437	SB2	C2
1.125	1.851	0.311	TC	R2
1.125	1.874	0.252	SB2	P2
1.125	1.874	0.252	TB2	PV
1.125	1.874	0.437	TB2	P2
1.125	1.875	0.252	SC	R2
1.125	1.875	0.252	TB2	G2
1.125	1.875	0.252	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.125	1.875	0.374	SB2	C2
1.125	1.875	0.374	SC	R2
1.125	1.875	0.374	TC	R2
1.125	1.937	0.189	VC	R2
1.125	1.937	0.343	KB2	P2
1.125	1.937	0.374	VC	R2
1.125	1.983	0.252	TB2	P2
1.125	2.000	0.252	TB2	G2
1.125	2.000	0.252	TC	R2
1.125	2.000	0.374	SB2	G2
1.125	2.000	0.374	SC	R2
1.125	2.000	0.374	TB2	G2
1.125	2.000	0.374	TB2	P2
1.125	2.000	0.406	TA2	C2
1.125	2.000	0.437	TB2	P2
1.125	2.047	0.311	TC	R2
1.125	2.063	0.252	TB2	P2
1.125	2.063	0.374	SB2	C2
1.125	2.067	0.335	SC	R2
1.125	2.125	0.252	SB2	P2
1.125	2.125	0.311	SB2	G2
1.125	2.125	0.311	TC	R2
1.125	2.250	0.500	SC	R2
1.125	2.437	0.437	TC	R2
1.125	2.440	0.374	TC	R2
1.125	2.441	0.252	TC	R2
1.125	2.441	0.311	TC	R2
1.125	2.441	0.374	TB2	P2
1.125	2.835	0.374	SC	R2
1.125	2.835	0.374	TB2	P2
1.125	2.844	0.374	SC	R2
1.125	2.875	0.374	TC	R2
1.126	1.575	0.197	SB	C2
1.126	1.575	0.315	TC	R2
1.126	1.693	0.256	TB	G2
1.126	1.831	0.437	TC	R2
1.126	2.063	0.437	SA2	G2
1.126	2.063	0.437	TB2	P2
1.142	1.378	0.173	KC	R2
1.142	1.417	0.276	TB	G2
1.142	1.417	0.276	TC	R2
1.142	1.417	0.315	TC	R2
1.142	1.417	0.315	VB	G2
1.142	1.496	0.157	TC	R2
1.142	1.496	0.157	VB	G2
1.142	1.500	0.236	WPC	R4
1.142	1.575	0.276	SC	R2
1.142	1.575	0.276	TC	R2
1.142	1.614	0.197	SC	R2
1.142	1.614	0.276	TB	G3
1.142	1.654	0.236	TC	R2
1.142	1.654	0.276	TC	R2
1.142	1.693	0.315	TC	R2
1.142	1.732	0.276	TC	R2



Shaft	Bore	Width	Lip Style	Material
1.181	1.693	0.354	TC	R2
1.181	1.732	0.197	TC	R2
1.181	1.732	0.276	TBR	G2
1.181	1.732	0.276	TC	R2
1.181	1.732	0.315	TC	R2
1.181	1.732	0.354	SB	G2
1.181	1.732	0.354	SC	R2
1.181	1.732	0.354	TC	R2
1.181	1.732	0.394	SC	R2
1.181	1.732	0.394	TC	R2
1.181	1.752	0.276	TC	R2
1.181	1.772	0.157	VB	G2
1.181	1.772	0.197	SC	R2
1.181	1.772	0.236	SC	R2
1.181	1.772	0.236	TB2	G2
1.181	1.772	0.236	TC	R2
1.181	1.772	0.236	VB	G2
1.181	1.772	0.276	SB2	G2
1.181	1.772	0.276	SC	R2
1.181	1.772	0.276	TC	R2
1.181	1.772	0.315	SB2	C2
1.181	1.772	0.315	SC	R2
1.181	1.772	0.315	SC	R2
1.181	1.772	0.315	TB2	G2
1.181	1.772	0.315	TC	R2
1.181	1.772	0.354	TC	R2
1.181	1.772	0.394	SC	R2
1.181	1.772	0.394	TC	R2
1.181	1.772	0.472	TC	R2
1.181	1.772	0.512	TC	R2
1.181	1.811	0.276	TC	R2
1.181	1.811	0.315	SC	R2
1.181	1.811	0.315	TC	R2
1.181	1.811	0.394	TC	R2
1.181	1.850	0.197	SC	R2
1.181	1.850	0.197	TC	R2
1.181	1.850	0.236	SC	R2
1.181	1.850	0.236	TC	R2
1.181	1.850	0.236	VBR	P2
1.181	1.850	0.256	SB2	GV
1.181	1.850	0.276	SC	RV
1.181	1.850	0.276	SC	R2
1.181	1.850	0.276	TB	G2
1.181	1.850	0.276	TC	RV
1.181	1.850	0.276	TC	RV
1.181	1.850	0.276	TC	R2
1.181	1.850	0.315	SB2	G2
1.181	1.850	0.315	SC	R2
1.181	1.850	0.315	TC	R2
1.181	1.850	0.394	DC	RV
1.181	1.850	0.394	SA2	G2
1.181	1.850	0.394	SC	RV
1.181	1.850	0.394	SC	R2
1.181	1.850	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.181	1.870	0.394	TB2	P3
1.181	1.873	0.252	VBR	C2
1.181	1.890	0.276	SC	RV
1.181	1.890	0.276	TBR	G2
1.181	1.890	0.276	TC	R2
1.181	1.890	0.315	SC	R2
1.181	1.890	0.315	TC	R2
1.181	1.890	0.394	TC	R2
1.181	1.890	0.472	TC	R2
1.181	1.909	0.315	TC	R2
1.181	1.929	0.315	TC	R2
1.181	1.969	0.197	SC	R2
1.181	1.969	0.236	TC	R2
1.181	1.969	0.276	SC	R2
1.181	1.969	0.276	TC	R2
1.181	1.969	0.315	SC	R2
1.181	1.969	0.315	SC	R2
1.181	1.969	0.315	TC	R2
1.181	1.969	0.394	DC	R2
1.181	1.969	0.394	SC	R2
1.181	1.969	0.394	TC	R2
1.181	1.969	0.433	SB2	G2
1.181	1.969	0.433	SC	R2
1.181	1.969	0.433	TB2	G2
1.181	1.969	0.433	TC	R2
1.181	1.969	0.433	TC	R2
1.181	1.969	0.472	SB2	G2
1.181	1.969	0.472	TC	R2
1.181	1.992	0.394	SC	R2
1.181	2.008	0.394	TC	R2
1.181	2.047	0.157	SC	R2
1.181	2.047	0.197	VC	R2
1.181	2.047	0.236	SC	R2
1.181	2.047	0.276	SB2	G2
1.181	2.047	0.276	SC	R2
1.181	2.047	0.276	TB2	G2
1.181	2.047	0.276	TC	R2
1.181	2.047	0.315	SB2	P2
1.181	2.047	0.315	SC	R2
1.181	2.047	0.315	TC	R2
1.181	2.047	0.354	SA2	G2
1.181	2.047	0.394	SC	R2
1.181	2.047	0.394	TB2	G2
1.181	2.047	0.394	TC	R2
1.181	2.047	0.433	TC	R2
1.181	2.047	0.472	TC	R2
1.181	2.126	0.236	TC	R2
1.181	2.126	0.354	TC	R2
1.181	2.165	0.276	SC	R2
1.181	2.165	0.276	TB2	G2
1.181	2.165	0.276	TC	R2
1.181	2.165	0.315	TB2	G2
1.181	2.165	0.315	TC	R2
1.181	2.165	0.394	SC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.181	2.165	0.394	TC	R2
1.181	2.165	0.433	TC	R2
1.181	2.165	0.472	SB2	G2
1.181	2.165	0.472	TC	R2
1.181	2.205	0.315	TC	R2
1.181	2.205	0.394	SC	R2
1.181	2.205	0.394	TC	R2
1.181	2.205	0.472	SC	R2
1.181	2.205	0.472	TC	R2
1.181	2.244	0.394	TC	R2
1.181	2.283	0.315	TC	R2
1.181	2.283	0.394	TC	R2
1.181	2.362	0.276	TC	R2
1.181	2.362	0.315	TB2	G2
1.181	2.362	0.315	TC	R2
1.181	2.362	0.394	SC	R2
1.181	2.362	0.394	TC	R2
1.181	2.362	0.472	TC	R2
1.181	2.441	0.157	TC	R2
1.181	2.441	0.197	TC	R2
1.181	2.441	0.236	TB2	G2
1.181	2.441	0.236	VC	R2
1.181	2.441	0.276	DC	R2
1.181	2.441	0.276	SC	R2
1.181	2.441	0.276	TC	R2
1.181	2.441	0.315	TC	R2
1.181	2.441	0.354	TC	R2
1.181	2.441	0.394	SB2	G2
1.181	2.441	0.394	SC	R2
1.181	2.441	0.394	TC	R2
1.181	2.441	0.433	TC	R2
1.181	2.441	0.472	SC	R2
1.181	2.441	0.472	TC	R2
1.181	2.559	0.394	TC	R2
1.181	2.677	0.236	TC	R2
1.181	2.677	0.394	TC	R2
1.181	2.677	0.472	TC	R2
1.181	2.756	0.394	TC	R2
1.181	2.835	0.236	SC	R2
1.181	2.835	0.276	TC	R2
1.181	2.835	0.315	TC	R2
1.181	2.835	0.354	TC	R2
1.181	2.835	0.394	SA2	G2
1.181	2.835	0.394	SC	R2
1.181	2.835	0.394	TC	R2
1.181	2.953	0.354	TC	R2
1.181	2.953	0.394	TC	R2
1.181	3.031	0.354	TC	R2
1.181	3.031	0.394	TC	R2
1.181	3.150	0.394	TC	R2
1.181	3.543	0.276	TC	R2
1.183	1.831	0.252	SB2	P2
1.187	1.563	0.189	WPB	G4
1.187	1.618	0.354	DB	C2

Shaft	Bore	Width	Lip Style	Material
1.187	1.665	0.303	SBR	C2
1.187	1.686	0.252	SBR	GPA
1.187	1.686	0.374	SB	P2
1.187	1.687	0.252	SB	P2
1.187	1.687	0.311	SB2	GV
1.187	1.687	0.311	SBR	C2
1.187	1.687	0.311	TBR	C2
1.187	1.687	0.374	SB	G2
1.187	1.687	0.374	SC	R2
1.187	1.687	0.374	TB	G2
1.187	1.690	0.311	TBR	C2
1.187	1.691	0.252	SB2	G2
1.187	1.700	0.252	TB	G2
1.187	1.713	0.500	TBR	C2
1.187	1.750	0.189	SC	R2
1.187	1.750	0.252	SC	R2
1.187	1.750	0.437	DC	R2
1.187	1.750	0.437	SC	R2
1.187	1.752	0.252	TB2	P2
1.187	1.828	0.374	TB2	P2
1.187	1.875	0.252	SB2	P2
1.187	1.875	0.252	SBR	GPA
1.187	1.983	0.252	TB2	C2
1.187	1.983	0.252	TC	R2
1.187	1.983	0.374	TB2	P2
1.187	2.000	0.252	SB2	P2
1.187	2.000	0.252	SC	R2
1.187	2.000	0.252	TB2	C2
1.187	2.000	0.437	TB2	C2
1.187	2.063	0.252	SB2	P2
1.187	2.063	0.252	TB2	P2
1.187	2.250	0.500	TA2	G2
1.187	2.437	0.465	TA2	P2
1.187	2.441	0.374	TB2	P2
1.187	2.441	0.374	TC	R2
1.188	1.627	0.252	WPB	G4
1.201	1.575	0.079	VC	R2
1.201	1.752	0.252	TB2	P2
1.201	2.047	0.315	TC	R2
1.218	1.969	0.469	VB2	G2
1.218	2.000	0.437	SC	R2
1.219	1.979	0.252	VB2	P2
1.219	1.979	0.406	KB2	G2
1.219	1.982	0.354	TB2	G2
1.219	1.983	0.437	SA2	P2
1.219	2.125	0.689	DA2	G2
1.220	1.457	0.118	VB	G2
1.220	1.654	0.315	SC	R2
1.220	1.654	0.315	TC	R2
1.220	1.693	0.220	SC	R2
1.220	1.740	0.315	SC	R2
1.220	1.756	0.236	SC	R2
1.220	1.772	0.236	SC	R2
1.220	1.772	0.276	SC	R2

Shaft	Bore	Width	Lip Style	Material
1.220	1.772	0.276	TC	R2
1.220	1.850	0.276	SC	R2
1.220	1.850	0.394	TC	R2
1.220	1.929	0.276	TC	R2
1.220	1.969	0.276	TC	R2
1.220	1.969	0.315	SC	R2
1.220	1.969	0.315	TC	R2
1.220	2.047	0.236	TC	R2
1.220	2.047	0.276	TC	R2
1.220	2.047	0.276	VB2	C2
1.220	2.283	0.315	DC	R2
1.220	2.461	0.169	SC	R2
1.247	1.688	0.311	SBR	C2
1.250	1.499	0.126	VB	G2
1.250	1.499	0.157	VC	R2
1.250	1.500	0.126	KB	P2
1.250	1.500	0.126	VB	C2
1.250	1.500	0.126	WPB	G4
1.250	1.500	0.157	WPB	G4
1.250	1.500	0.189	TC	R2
1.250	1.575	0.236	TC	R2
1.250	1.575	0.276	TC	R2
1.250	1.600	0.126	SC	R2
1.250	1.618	0.252	TC	R2
1.250	1.625	0.189	DC	R2
1.250	1.625	0.189	SB	P2
1.250	1.625	0.189	VB	P2
1.250	1.625	0.252	WPB	G4
1.250	1.686	0.189	VB2	P2
1.250	1.686	0.252	SC	R2
1.250	1.686	0.469	DC	R2
1.250	1.687	0.126	WPB	G4
1.250	1.687	0.189	WPB	G4
1.250	1.687	0.189	WPB	G4
1.250	1.687	0.252	SB	G2
1.250	1.687	0.252	TB	P2
1.250	1.687	0.252	TC	R2
1.250	1.687	0.311	SB	G2
1.250	1.687	0.311	TB2	C2
1.250	1.687	0.311	TC	R2
1.250	1.687	0.311	TC	R2
1.250	1.690	0.189	WPB	G4
1.250	1.690	0.224	KC	V3
1.250	1.693	0.252	TC	R2
1.250	1.700	0.252	SC	R2
1.250	1.700	0.252	WPC	R4
1.250	1.750	0.252	SB2	P2
1.250	1.750	0.252	SBR	C2
1.250	1.750	0.252	SC	R2
1.250	1.750	0.252	TC	R2
1.250	1.750	0.311	WPB	G4
1.250	1.750	0.374	DB	CH
1.250	1.750	0.374	SB	GV
1.250	1.750	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.250	1.752	0.252	SB2	P2
1.250	1.752	0.252	TB2	PV
1.250	1.752	0.252	TB2	P2
1.250	1.752	0.252	VB2	G2
1.250	1.752	0.252	VB2	C2
1.250	1.752	0.252	WPB	G4
1.250	1.752	0.311	TA2	GV
1.250	1.752	0.311	TB2	G2
1.250	1.752	0.437	SA2	PPA
1.250	1.772	0.276	WPC	R4
1.250	1.813	0.374	TC	R2
1.250	1.828	0.374	TC	R2
1.250	1.874	0.252	WPB	G4
1.250	1.875	0.252	SB2	P2
1.250	1.875	0.252	SC	R2
1.250	1.875	0.252	TB2	C2
1.250	1.875	0.252	TC	R2
1.250	1.875	0.311	SC	R2
1.250	1.875	0.437	TB2	G2
1.250	1.937	0.252	SB2	P2
1.250	1.937	0.437	SC	R2
1.250	1.941	0.441	TC	R2
1.250	1.979	0.252	KB2	C2
1.250	1.979	0.252	TB2	C2
1.250	1.979	0.252	VB2	G2
1.250	1.980	0.366	TB2	P2
1.250	1.983	0.252	TB2	C2
1.250	1.983	0.252	VA2	C2
1.250	1.983	0.438	TB2	P2
1.250	2.000	0.252	SB2	G2
1.250	2.000	0.252	TB2	C2
1.250	2.000	0.252	TC	R2
1.250	2.000	0.252	VB2	G2
1.250	2.000	0.311	SC	R2
1.250	2.000	0.311	TC	R2
1.250	2.000	0.374	SA2	G2
1.250	2.000	0.374	SA2	PS
1.250	2.000	0.374	SB2	C2
1.250	2.000	0.374	SC	R2
1.250	2.000	0.390	DC	R2
1.250	2.000	0.437	TA2	G2
1.250	2.000	0.437	TA2	P2
1.250	2.000	0.437	TB2	G2
1.250	2.000	0.437	TB2	GV
1.250	2.000	0.437	TC	R2
1.250	2.000	0.500	SC	R2
1.250	2.000	0.500	TC	R2
1.250	2.061	0.252	SB2	P2
1.250	2.061	0.252	SB2	P2
1.250	2.063	0.252	SC	R2
1.250	2.063	0.252	TB2	P2
1.250	2.063	0.252	TC	R2
1.250	2.063	0.374	SB2	P2
1.250	2.063	0.437	TA2	P2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.250	2.065	0.252	SB2	P2
1.250	2.125	0.252	SB2	P2
1.250	2.125	0.252	TB2	GV
1.250	2.125	0.374	SB2	P2
1.250	2.125	0.374	TB2	P2
1.250	2.240	0.252	TC	R2
1.250	2.250	0.252	SB2	P2
1.250	2.250	0.252	TB2	P2
1.250	2.250	0.252	VB	P2
1.250	2.250	0.252	VB2	P2
1.250	2.250	0.374	TC	R2
1.250	2.250	0.500	TC	R2
1.250	2.251	0.374	SB2	P2
1.250	2.252	0.374	TB2	P2
1.250	2.313	0.374	VC	R2
1.250	2.328	0.437	TB2	G2
1.250	2.328	0.437	TC	R2
1.250	2.328	0.469	TB2	P2
1.250	2.375	0.374	SC	R2
1.250	2.437	0.252	SA2	C2
1.250	2.437	0.252	SB2	G2
1.250	2.437	0.311	SC	R2
1.250	2.437	0.311	TB2	P2
1.250	2.437	0.350	SB2	G2
1.250	2.437	0.374	TB2	P2
1.250	2.437	0.374	TC	R2
1.250	2.440	0.311	TC	R2
1.250	2.441	0.252	TC	R2
1.250	2.441	0.276	TC	R2
1.250	2.441	0.374	TB2	G2
1.250	2.441	0.374	TC	R2
1.250	2.500	0.374	SC	R2
1.250	2.502	0.374	TB2	P2
1.250	2.502	0.500	TB2	PV
1.250	2.561	0.500	SA2	P2
1.250	2.686	0.374	SA2	P2
1.250	2.835	0.374	TC	R2
1.252	1.575	0.315	TC	R2
1.260	1.535	0.236	TB	G2
1.260	1.535	0.315	TB	G2
1.260	1.575	0.197	VC	R2
1.260	1.575	0.276	SC	R2
1.260	1.575	0.276	TC	R2
1.260	1.575	0.394	TC	R2
1.260	1.614	0.276	TC	R2
1.260	1.654	0.157	VB	G2
1.260	1.654	0.157	VC	R2
1.260	1.654	0.197	KC	R2
1.260	1.654	0.236	TC	R2
1.260	1.654	0.276	SC	R2
1.260	1.654	0.276	TB	G2
1.260	1.654	0.276	TC	R2
1.260	1.654	0.315	TC	R2
1.260	1.654	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.260	1.693	0.276	TC	R2
1.260	1.693	0.394	SB	G2
1.260	1.693	0.394	TC	R2
1.260	1.732	0.157	VC	R2
1.260	1.732	0.197	TC	R2
1.260	1.732	0.236	TC	R2
1.260	1.732	0.276	TC	R2
1.260	1.732	0.315	DC	R2
1.260	1.732	0.315	TC	R2
1.260	1.732	0.315	TC	R2
1.260	1.732	0.354	SB	G2
1.260	1.732	0.354	TC	R2
1.260	1.732	0.394	SC	R2
1.260	1.732	0.394	TC	R2
1.260	1.752	0.315	TC	R2
1.260	1.752	0.394	TC	R2
1.260	1.772	0.157	VB	G2
1.260	1.772	0.157	WPC	R4
1.260	1.772	0.197	SC	R2
1.260	1.772	0.197	VB2	G2
1.260	1.772	0.236	SC	R2
1.260	1.772	0.236	TC	R2
1.260	1.772	0.256	TC	R2
1.260	1.772	0.276	SC	R2
1.260	1.772	0.276	TB2	G2
1.260	1.772	0.276	TBR	G2
1.260	1.772	0.276	TC	R2
1.260	1.772	0.315	DC	R2
1.260	1.772	0.315	TC	R2
1.260	1.772	0.394	SC	R2
1.260	1.772	0.394	TC	R2
1.260	1.780	0.276	SC	R2
1.260	1.811	0.236	TC	R2
1.260	1.811	0.264	TBR	GV
1.260	1.811	0.276	SC	R2
1.260	1.811	0.276	TC	R2
1.260	1.811	0.315	SB2	G2
1.260	1.811	0.315	TBR	G2
1.260	1.811	0.315	TC	R2
1.260	1.850	0.236	TC	R2
1.260	1.850	0.276	SC	R2
1.260	1.850	0.276	TB2	G2
1.260	1.850	0.276	TC	R2
1.260	1.850	0.315	TC	R2
1.260	1.850	0.394	TB	G2
1.260	1.850	0.394	TC	R2
1.260	1.850	0.472	DC	RV
1.260	1.890	0.276	TC	R2
1.260	1.890	0.315	SB2	G2
1.260	1.890	0.315	SC	RV
1.260	1.890	0.315	TC	R2
1.260	1.890	0.394	TC	R2
1.260	1.969	0.276	TB2	G2
1.260	1.969	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.260	1.969	0.315	SB	G2
1.260	1.969	0.315	SC	R2
1.260	1.969	0.315	TC	R2
1.260	1.969	0.394	TC	R2
1.260	1.969	0.433	TC	R2
1.260	2.008	0.315	TB2	P3
1.260	2.047	0.197	SC	R2
1.260	2.047	0.197	TC	R2
1.260	2.047	0.197	VC	R2
1.260	2.047	0.276	DB2	G2
1.260	2.047	0.276	DC	R2
1.260	2.047	0.276	SC	R2
1.260	2.047	0.276	TB2	G2
1.260	2.047	0.276	TC	R2
1.260	2.047	0.315	TC	R2
1.260	2.047	0.354	TC	R2
1.260	2.047	0.374	KB2	G2
1.260	2.047	0.394	SC	R2
1.260	2.047	0.394	TB2	G2
1.260	2.047	0.394	TC	R2
1.260	2.047	0.433	TB2	G2
1.260	2.047	0.433	TC	R2
1.260	2.047	0.472	TC	R2
1.260	2.087	0.276	TC	R2
1.260	2.126	0.276	TC	R2
1.260	2.126	0.315	TC	R2
1.260	2.126	0.394	TC	R2
1.260	2.165	0.256	TC	R2
1.260	2.165	0.276	TC	R2
1.260	2.165	0.315	TC	R2
1.260	2.165	0.354	TC	R2
1.260	2.165	0.394	TC	R2
1.260	2.165	0.433	TC	R2
1.260	2.165	0.591	TC	R2
1.260	2.205	0.315	TC	R2
1.260	2.205	0.394	TB2	C2
1.260	2.205	0.394	TC	R2
1.260	2.205	0.472	TC	R2
1.260	2.244	0.276	TC	RV
1.260	2.283	0.315	TC	R2
1.260	2.283	0.394	TC	R2
1.260	2.283	0.472	TB2	G2
1.260	2.283	0.472	TC	R2
1.260	2.362	0.315	TC	R2
1.260	2.362	0.394	TA2	G2
1.260	2.362	0.394	TC	R2
1.260	2.441	0.236	SC	R2
1.260	2.441	0.276	TC	R2
1.260	2.441	0.315	TC	R2
1.260	2.441	0.394	TC	R2
1.260	2.441	0.472	TC	R2
1.260	2.559	0.295	TC	R2
1.260	2.559	0.315	TC	R2
1.260	2.559	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.260	2.559	0.472	TB2	G2
1.260	2.677	0.315	TC	R2
1.260	2.756	0.315	TC	R2
1.260	2.756	0.394	TC	R2
1.260	2.756	0.433	TC	R2
1.260	2.835	0.276	TB2	P2
1.260	2.835	0.315	TC	R2
1.260	2.835	0.394	SC	R2
1.260	2.835	0.394	TC	R2
1.260	2.874	0.394	TC	R3
1.260	3.150	0.472	TC	RV
1.280	1.693	0.276	TC	R2
1.281	1.827	0.374	SBR	G2
1.281	1.937	0.500	TC	R2
1.281	2.000	0.350	SB	G2
1.281	2.000	0.354	SB	G2
1.281	2.000	0.374	TB2	G2
1.281	2.000	0.374	TB2	P2
1.281	2.025	0.374	SB2	G2
1.287	2.000	0.343	SB	C2
1.299	1.535	0.157	KC	R2
1.299	1.654	0.276	KC	P2
1.299	1.693	0.276	TC	R2
1.299	1.732	0.276	TB	G2
1.299	1.732	0.276	TC	R2
1.299	1.732	0.315	TB	G2
1.299	1.732	0.315	TBR	C2
1.299	1.732	0.315	TC	R2
1.299	1.772	0.276	SC	R2
1.299	1.772	0.315	DC	R2
1.299	1.772	0.315	TC	R2
1.299	1.772	0.394	TC	R2
1.299	1.811	0.276	TC	R2
1.299	1.850	0.315	TC	R2
1.299	1.862	0.276	TC	R2
1.299	1.890	0.236	TC	R2
1.299	1.890	0.315	TC	R2
1.299	1.969	0.236	SC	R2
1.299	1.969	0.236	TC	R2
1.299	1.969	0.276	TC	R2
1.299	1.969	0.315	TB2	G2
1.299	1.969	0.394	SC	R2
1.299	1.969	0.394	TC	R2
1.299	2.047	0.197	TC	R2
1.299	2.047	0.236	SC	R2
1.299	2.047	0.315	SC	RPA
1.299	2.047	0.394	TC	R2
1.299	2.126	0.256	SC	R2
1.299	2.165	0.374	TB2	G2
1.299	2.165	0.394	TC	R2
1.299	2.205	0.394	TC	R2
1.299	2.205	0.472	TC	R2
1.299	2.441	0.276	TC	R2
1.299	2.441	0.472	TC	R2

# Tobar

oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.299	2.559	0.315	TC	R2
1.299	2.598	0.472	SC	R2
1.299	2.835	0.394	TC	R2
1.301	2.000	0.437	TB2	GPA
1.310	1.983	0.252	TB2	P2
1.311	1.562	0.126	VBR	CV
1.311	1.562	0.126	VBR	CV
1.311	1.812	0.161	WPC	R4
1.311	1.850	0.146	VB2	G2
1.313	1.563	0.126	WPB	G4
1.313	1.813	0.339	TC	R2
1.313	1.828	0.374	SBR	G2
1.313	1.837	0.189	SC	R2
1.313	1.850	0.500	TA2	PV
1.313	1.875	0.252	SC	R2
1.313	1.890	0.252	SB	C2
1.313	1.937	0.189	SC	R2
1.313	1.937	0.374	TC	R2
1.313	1.983	0.374	TB2	G2
1.313	2.000	0.311	TC	R2
1.313	2.000	0.374	SC	R2
1.313	2.063	0.252	VB	G2
1.313	2.063	0.252	VC	R2
1.313	2.063	0.311	TB2	P2
1.313	2.063	0.311	TB2	P2
1.313	2.125	0.374	SC	R2
1.313	2.171	0.374	TB2	G2
1.313	2.250	0.311	TB2	P2
1.313	2.250	0.374	SC	R2
1.313	2.374	0.311	TB2	P2
1.313	2.591	0.331	VBR	C2
1.313	2.734	0.311	SB2	G2
1.319	2.165	0.374	TB	G2
1.322	2.227	0.374	SB2	P2
1.326	2.061	0.374	SB2	P2
1.326	2.313	0.435	SB2	P2
1.339	1.535	0.118	VC	R2
1.339	1.575	0.197	VB	G2
1.339	1.614	0.157	KC	R2
1.339	1.614	0.157	TB	G2
1.339	1.614	0.157	VB	G2
1.339	1.614	0.157	VC	R2
1.339	1.614	0.276	TC	R2
1.339	1.654	0.197	KC	R2
1.339	1.654	0.197	TC	R2
1.339	1.732	0.197	VB	G2
1.339	1.732	0.276	TB	G2
1.339	1.732	0.276	TC	R2
1.339	1.732	0.315	TC	R2
1.339	1.772	0.236	TC	R2
1.339	1.772	0.315	TC	R2
1.339	1.811	0.315	SB2	G2
1.339	1.811	0.315	TC	R2
1.339	1.811	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.339	1.828	0.252	SC	R2
1.339	1.850	0.276	TC	R2
1.339	1.850	0.315	TC	R2
1.339	1.850	0.354	TC	R2
1.339	1.890	0.276	TC	R2
1.339	1.890	0.295	SC	RPA
1.339	1.890	0.315	SB2	P2
1.339	1.890	0.315	TB2	G2
1.339	1.890	0.315	TC	R2
1.339	1.969	0.276	TC	R2
1.339	1.969	0.315	TC	R2
1.339	1.969	0.394	TC	R2
1.339	1.969	0.472	TC	R2
1.339	2.047	0.236	TC	R2
1.339	2.047	0.276	TB2	G2
1.339	2.047	0.276	TC	R2
1.339	2.047	0.295	SC	R2
1.339	2.047	0.315	SC	R2
1.339	2.047	0.315	TC	R2
1.339	2.047	0.394	DB	G2
1.339	2.047	0.394	SB2	G2
1.339	2.047	0.394	TC	R2
1.339	2.047	0.433	TC	R2
1.339	2.087	0.315	TC	RPA
1.339	2.126	0.315	TC	R2
1.339	2.126	0.394	TC	R2
1.339	2.165	0.354	TC	R2
1.339	2.165	0.433	TC	R2
1.339	2.205	0.315	TC	R2
1.339	2.205	0.394	TC	R2
1.339	2.283	0.197	KC	R2
1.339	2.283	0.236	TC	RPA
1.339	2.283	0.394	TC	R2
1.339	2.362	0.472	TC	R2
1.339	2.441	0.236	TC	R2
1.339	2.441	0.276	TC	R2
1.339	2.441	0.315	TC	R2
1.339	2.441	0.394	SC	R2
1.339	2.441	0.394	TC	R2
1.339	2.441	0.551	TC	R2
1.339	2.559	0.354	TC	R2
1.339	2.559	0.472	TB2	C2
1.339	2.756	0.394	TC	R2
1.339	2.756	0.433	DC	R2
1.339	2.835	0.394	TC	R2
1.339	2.835	0.472	TC	R2
1.343	2.106	0.311	TA2	P2
1.358	1.654	0.157	VB2	G2
1.358	2.047	0.433	TC	R2
1.358	2.835	0.453	TC	R2
1.359	1.750	0.197	SC	RPA
1.362	2.191	0.252	SB2	P2
1.363	2.242	0.240	SC	R2
1.365	2.081	0.433	SB	P2

Shaft	Bore	Width	Lip Style	Material
1.365	2.374	0.433	SB2	P2
1.367	2.250	0.311	SB2	G2
1.373	2.165	0.591	TC	R2
1.375	1.625	0.126	WPB	G4
1.375	1.750	0.189	SB	G2
1.375	1.750	0.189	VB	C2
1.375	1.750	0.189	WPB	G4
1.375	1.750	0.193	SB	G2
1.375	1.750	0.220	TC	R2
1.375	1.750	0.252	SC	R2
1.375	1.750	0.252	WPB	G4
1.375	1.752	0.252	TC	RV
1.375	1.813	0.252	TC	RV
1.375	1.828	0.252	TB	G2
1.375	1.828	0.252	TC	R2
1.375	1.834	0.374	TB	GV
1.375	1.851	0.252	TC	R2
1.375	1.874	0.311	TB	G2
1.375	1.874	0.374	TB	G2
1.375	1.875	0.189	VB2	C2
1.375	1.875	0.189	VB2	C2
1.375	1.875	0.252	SC	R2
1.375	1.875	0.252	TB2	P2
1.375	1.875	0.252	WPB	G4
1.375	1.875	0.311	SB2	G2
1.375	1.875	0.311	SC	RPA
1.375	1.875	0.311	TC	R2
1.375	1.875	0.374	SB	P2
1.375	1.875	0.374	TC	R2
1.375	1.937	0.236	TBR	C2
1.375	1.947	0.500	TBR	G2
1.375	1.980	0.311	TC	R2
1.375	1.983	0.311	SB2	PPA
1.375	2.000	0.252	TC	R2
1.375	2.000	0.311	SB2	G2
1.375	2.000	0.311	SC	R2
1.375	2.000	0.311	TB2	G2
1.375	2.000	0.311	TB2	P2
1.375	2.000	0.311	TC	R2
1.375	2.000	0.311	WPB	G4
1.375	2.000	0.328	SA2	G2
1.375	2.000	0.374	SC	R2
1.375	2.000	0.374	TB2	G2
1.375	2.000	0.374	TB2	P2
1.375	2.000	0.374	TB2	P2
1.375	2.000	0.437	TC	R2
1.375	2.000	0.500	SC	R2
1.375	2.047	0.311	TB2	P2
1.375	2.063	0.311	TC	R2
1.375	2.063	0.374	SA2	G2
1.375	2.063	0.374	SB2	P2
1.375	2.063	0.374	SC	R2
1.375	2.104	0.374	SB2	P2
1.375	2.106	0.311	TB2	P2
1.375	2.125	0.311	TB2	P2

Shaft	Bore	Width	Lip Style	Material
1.375	2.125	0.311	TBR	C2
1.375	2.125	0.311	TC	R2
1.375	2.125	0.315	SB2	C2
1.375	2.125	0.315	SC	R2
1.375	2.125	0.315	TA2	P2
1.375	2.125	0.374	SB2	P2
1.375	2.125	0.374	SC	R2
1.375	2.125	0.437	SA2	G2
1.375	2.125	0.437	SB2	P2
1.375	2.125	0.437	SC	R2
1.375	2.125	0.437	TB2	P2
1.375	2.135	0.311	SC	R2
1.375	2.187	0.248	SC	R2
1.375	2.187	0.500	TC	R2
1.375	2.250	0.311	TB2	G2
1.375	2.250	0.311	TC	R2
1.375	2.250	0.500	TB2	G2
1.375	2.250	0.500	TC	R2
1.375	2.281	0.374	SC	R2
1.375	2.282	0.252	KBR	C2
1.375	2.313	0.437	SC	R2
1.375	2.375	0.311	TB2	P2
1.375	2.375	0.311	TC	R2
1.375	2.375	0.374	TC	RPA
1.375	2.375	0.500	SB2	P2
1.375	2.437	0.250	SB2	G2
1.375	2.437	0.469	SB2	G2
1.375	2.440	0.252	SC	RPA
1.375	2.441	0.311	TA2	P2
1.375	2.441	0.311	TB2	C2
1.375	2.441	0.374	TB2	P2
1.375	2.441	0.374	TC	R2
1.375	2.500	0.374	SC	RV
1.375	2.500	0.374	SC	R2
1.375	2.500	0.500	SA2	G2
1.375	2.502	0.374	TB2	P2
1.375	2.502	0.374	TBR	G2
1.375	2.561	0.374	TB2	P2
1.375	2.717	0.374	TC	R2
1.375	2.750	0.500	SC	R2
1.375	2.835	0.311	TB2	PPA
1.375	2.835	0.374	TB2	G2
1.375	2.835	0.374	TC	R2
1.375	2.835	0.469	TB2	C2
1.375	2.875	0.469	TB2	P2
1.375	3.000	0.500	TA2	G2
1.375	3.150	0.374	TC	R2
1.375	3.156	0.374	SC	R2
1.378	1.534	0.157	VB	C2
1.378	1.614	0.098	VB	G2
1.378	1.614	0.098	VB	G2
1.378	1.654	0.118	KC	R2
1.378	1.654	0.157	KB	G2
1.378	1.654	0.157	SC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.378	1.654	0.157	VB	G2
1.378	1.654	0.157	VB	G2
1.378	1.654	0.236	TC	R2
1.378	1.654	0.315	TC	R2
1.378	1.660	0.224	VB	C2
1.378	1.660	0.224	VB	C2
1.378	1.693	0.236	TC	R2
1.378	1.732	0.157	SC	R2
1.378	1.732	0.157	VB	G2
1.378	1.732	0.276	DC	R2
1.378	1.732	0.276	TB	G2
1.378	1.732	0.276	TC	R2
1.378	1.752	0.189	VC	R2
1.378	1.772	0.157	SC	R2
1.378	1.772	0.157	VB	G2
1.378	1.772	0.197	SC	R2
1.378	1.772	0.236	SC	R2
1.378	1.772	0.236	TC	R2
1.378	1.772	0.236	VB	G2
1.378	1.772	0.236	WPC	R4
1.378	1.772	0.276	SB	G2
1.378	1.772	0.276	SC	R2
1.378	1.772	0.276	TC	R2
1.378	1.772	0.315	TB	G2
1.378	1.772	0.315	TC	R2
1.378	1.772	0.394	TC	R2
1.378	1.772	0.472	TC	R2
1.378	1.780	0.276	SC	R2
1.378	1.811	0.276	SC	R2
1.378	1.811	0.394	TC	R2
1.378	1.831	0.315	TC	R2
1.378	1.850	0.197	SC	R2
1.378	1.850	0.197	TC	R2
1.378	1.850	0.197	VB2	G2
1.378	1.850	0.236	TB	G2
1.378	1.850	0.276	KC	R2
1.378	1.850	0.276	SB	G2
1.378	1.850	0.276	SC	RV
1.378	1.850	0.276	SC	R2
1.378	1.850	0.276	SC	R2
1.378	1.850	0.276	TC	R2
1.378	1.850	0.276	TC	R2
1.378	1.850	0.276	TC	R2
1.378	1.850	0.295	TC	RV
1.378	1.850	0.315	TB	GV
1.378	1.850	0.315	TBR	G2
1.378	1.850	0.315	TC	R2
1.378	1.850	0.354	SC	R2
1.378	1.850	0.394	SC	R2
1.378	1.850	0.394	TC	R2
1.378	1.850	0.472	TC	R2
1.378	1.875	0.157	VA2	C2
1.378	1.890	0.276	TB	G2
1.378	1.890	0.276	TC	R2
1.378	1.890	0.315	TC	RPA

Shaft	Bore	Width	Lip Style	Material
1.378	1.890	0.315	TC	R2
1.378	1.890	0.354	TC	R2
1.378	1.890	0.394	TC	R2
1.378	1.929	0.236	TC	R2
1.378	1.929	0.315	TC	R2
1.378	1.949	0.394	TC	R2
1.378	1.969	0.197	SC	R2
1.378	1.969	0.197	TC	R2
1.378	1.969	0.236	TC	R2
1.378	1.969	0.276	SC	R2
1.378	1.969	0.276	TC	R2
1.378	1.969	0.315	SC	R2
1.378	1.969	0.315	TC	R2
1.378	1.969	0.354	TC	R2
1.378	1.969	0.374	TB	G2
1.378	1.969	0.394	SB2	G2
1.378	1.969	0.394	SC	R2
1.378	1.969	0.394	TC	R2
1.378	1.969	0.433	DC	R2
1.378	1.969	0.433	TC	R2
1.378	1.969	0.472	SC	R2
1.378	2.008	0.276	TC	R2
1.378	2.008	0.315	TC	R2
1.378	2.008	0.354	TB2	G2
1.378	2.008	0.394	TC	R2
1.378	2.047	0.197	TC	R2
1.378	2.047	0.236	SB2	C2
1.378	2.047	0.236	SC	RPA
1.378	2.047	0.236	TC	R2
1.378	2.047	0.276	SB2	G2
1.378	2.047	0.276	SC	R2
1.378	2.047	0.276	TC	R2
1.378	2.047	0.315	SBR	C2
1.378	2.047	0.315	SC	R2
1.378	2.047	0.315	TC	R2
1.378	2.047	0.346	SB2	C2
1.378	2.047	0.354	TC	R2
1.378	2.047	0.394	SC	R2
1.378	2.047	0.394	TC	R2
1.378	2.047	0.433	TB2	G2
1.378	2.047	0.433	TC	R2
1.378	2.047	0.472	DC	R2
1.378	2.047	0.472	TC	R2
1.378	2.059	0.374	TC	R2
1.378	2.087	0.276	SC	R2
1.378	2.087	0.276	TC	R2
1.378	2.126	0.236	TC	R2
1.378	2.126	0.315	TB2	G2
1.378	2.126	0.315	TC	R2
1.378	2.126	0.394	TC	R2
1.378	2.126	0.472	TC	R2
1.378	2.165	0.197	TB2	G2
1.378	2.165	0.197	VC	R2
1.378	2.165	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.378	2.165	0.315	SC	R2
1.378	2.165	0.315	TB2	G2
1.378	2.165	0.315	TC	R2
1.378	2.165	0.354	TC	R2
1.378	2.165	0.394	SC	R2
1.378	2.165	0.394	TB2	G2
1.378	2.165	0.394	TC	R2
1.378	2.165	0.433	TB2	G2
1.378	2.165	0.433	TB2	PS
1.378	2.165	0.433	TC	R2
1.378	2.165	0.472	SB2	G2
1.378	2.165	0.472	TC	R2
1.378	2.205	0.228	TC	R2
1.378	2.205	0.315	SB2	PV
1.378	2.205	0.315	SC	R2
1.378	2.205	0.315	TC	R2
1.378	2.205	0.394	SC	R2
1.378	2.205	0.394	TB2	G2
1.378	2.205	0.394	TC	R2
1.378	2.205	0.472	SB2	G2
1.378	2.205	0.472	SC	R2
1.378	2.205	0.472	TC	R2
1.378	2.244	0.236	SC	R2
1.378	2.244	0.354	TB2	G2
1.378	2.244	0.354	TC	R2
1.378	2.244	0.394	TC	R2
1.378	2.283	0.236	TC	R2
1.378	2.283	0.315	TB2	P2
1.378	2.283	0.354	SC	R2
1.378	2.283	0.354	TB2	G2
1.378	2.283	0.354	TC	R2
1.378	2.283	0.394	SA2	G2
1.378	2.283	0.394	SC	R2
1.378	2.283	0.394	TB2	G2
1.378	2.283	0.394	TC	R2
1.378	2.283	0.472	TC	R2
1.378	2.283	0.512	TC	R2
1.378	2.283	0.709	TC	R2
1.378	2.323	0.472	TC	R2
1.378	2.362	0.276	TC	R2
1.378	2.362	0.315	SC	R2
1.378	2.362	0.315	TC	R2
1.378	2.362	0.394	DC	R2
1.378	2.362	0.394	SC	R2
1.378	2.362	0.394	TC	R2
1.378	2.362	0.394	TC	R2
1.378	2.362	0.433	TC	R2
1.378	2.362	0.472	TC	R2
1.378	2.441	0.197	VC	R2
1.378	2.441	0.236	TC	R2
1.378	2.441	0.236	TC	R2
1.378	2.441	0.276	SC	RPA
1.378	2.441	0.276	SC	RS
1.378	2.441	0.276	SC	R2
1.378	2.441	0.276	TB2	G2

Shaft	Bore	Width	Lip Style	Material
1.378	2.441	0.276	TC	R2
1.378	2.441	0.315	DC	R2
1.378	2.441	0.315	SC	R2
1.378	2.441	0.315	TC	RPA
1.378	2.441	0.315	TC	R2
1.378	2.441	0.374	TC	R2
1.378	2.441	0.394	SB2	G2
1.378	2.441	0.394	SC	R2
1.378	2.441	0.394	TC	R2
1.378	2.441	0.394	TC	R2
1.378	2.441	0.433	TC	R2
1.378	2.441	0.472	TB2	G2
1.378	2.441	0.472	TC	R2
1.378	2.500	0.311	SC	R2
1.378	2.500	0.472	TC	RPA
1.378	2.520	0.315	TB2	P2
1.378	2.520	0.394	TC	R2
1.378	2.520	0.472	TC	R2
1.378	2.520	0.512	TB	G2
1.378	2.520	0.512	TC	R2
1.378	2.559	0.276	TC	R2
1.378	2.559	0.394	SC	R2
1.378	2.559	0.394	TC	R2
1.378	2.559	0.472	TB2	G2
1.378	2.559	0.472	TC	R2
1.378	2.638	0.472	TC	RPA
1.378	2.677	0.236	SC	R2
1.378	2.677	0.236	TC	R2
1.378	2.677	0.315	SC	R2
1.378	2.677	0.315	TC	R2
1.378	2.677	0.394	SC	R2
1.378	2.677	0.394	TC	R2
1.378	2.677	0.472	SC	R2
1.378	2.756	0.394	TC	R2
1.378	2.756	0.472	TC	R2
1.378	2.835	0.276	SC	R2
1.378	2.835	0.276	TC	R2
1.378	2.835	0.315	TC	R2
1.378	2.835	0.374	TB2	G2
1.378	2.835	0.394	SA2	G2
1.378	2.835	0.394	SC	R2
1.378	2.835	0.394	TB2	G2
1.378	2.835	0.394	TC	R2
1.378	2.835	0.433	TC	R2
1.378	2.835	0.472	SA2	G2
1.378	2.835	0.472	SC	R2
1.378	2.835	0.472	TC	R2
1.378	2.953	0.276	TC	RV
1.378	2.953	0.315	TC	R2
1.378	2.953	0.394	TC	R2
1.378	2.953	0.472	TC	R2
1.378	3.071	0.315	TC	R2
1.378	3.150	0.236	TC	R2
1.378	3.150	0.315	SB2	G2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.378	3.150	0.315	SC	R2
1.378	3.150	0.315	TC	R2
1.378	3.150	0.394	SC	R2
1.378	3.150	0.394	TC	R2
1.378	3.150	0.472	SC	R2
1.378	3.150	0.472	TC	R2
1.378	3.150	0.512	SA2	G2
1.378	3.150	0.512	SC	R2
1.378	3.150	0.512	TC	R2
1.378	3.189	0.394	TB2	C2
1.378	3.228	0.236	SC	R2
1.378	3.228	0.276	TC	R2
1.378	3.228	0.394	TC	R2
1.378	3.346	0.394	SB2	C2
1.378	3.543	0.512	TC	R2
1.387	2.328	0.311	TB2	G2
1.399	2.250	0.252	TB2	P2
1.399	2.292	0.500	SB2	C2
1.400	2.292	0.500	TBR	C2
1.409	2.677	0.394	TB2	G2
1.410	1.560	0.118	VB	C2
1.415	2.063	0.311	TC	R2
1.417	1.693	0.315	KBR	C2
1.417	1.732	0.197	TC	R2
1.417	1.772	0.276	TC	R2
1.417	1.811	0.236	TC	R2
1.417	1.811	0.276	TC	R2
1.417	1.811	0.354	SB	G2
1.417	1.811	0.354	SBR	G2
1.417	1.811	0.354	TB	G2
1.417	1.811	0.354	TC	R2
1.417	1.850	0.276	SC	R2
1.417	1.850	0.276	TC	R2
1.417	1.850	0.315	TC	R2
1.417	1.890	0.236	TC	R2
1.417	1.890	0.276	TC	R2
1.417	1.890	0.315	TC	R2
1.417	1.890	0.394	TC	R2
1.417	1.890	0.433	DC	R2
1.417	1.929	0.276	TC	R2
1.417	1.929	0.394	TC	R2
1.417	1.969	0.197	TC	R2
1.417	1.969	0.276	SC	R2
1.417	1.969	0.276	TA2	G2
1.417	1.969	0.276	TBR	G2
1.417	1.969	0.276	TC	R2
1.417	1.969	0.394	TC	R2
1.417	1.988	0.276	TC	R2
1.417	2.008	0.276	TC	R2
1.417	2.008	0.315	TC	R2
1.417	2.047	0.248	SC	R2
1.417	2.047	0.276	SC	R2
1.417	2.047	0.276	TC	R2
1.417	2.047	0.315	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.417	2.047	0.394	TC	R2
1.417	2.126	0.276	SC	R2
1.417	2.126	0.276	TB2	G3
1.417	2.126	0.276	TC	R2
1.417	2.126	0.295	SC	R2
1.417	2.126	0.295	TC	R2
1.417	2.126	0.315	SC	R2
1.417	2.126	0.315	TC	R2
1.417	2.126	0.394	TC	R2
1.417	2.126	0.433	TB2	G2
1.417	2.165	0.256	TB2	G2
1.417	2.165	0.394	TC	R2
1.417	2.165	0.472	TC	R2
1.417	2.205	0.315	TC	R2
1.417	2.205	0.394	SC	R2
1.417	2.205	0.394	TC	R2
1.417	2.205	0.472	TC	R2
1.417	2.283	0.315	TB2	P2
1.417	2.283	0.315	TC	R2
1.417	2.283	0.394	SC	R2
1.417	2.283	0.472	TC	R2
1.417	2.362	0.236	TC	R2
1.417	2.362	0.276	TC	R2
1.417	2.362	0.394	TC	R2
1.417	2.362	0.472	TC	R2
1.417	2.441	0.276	SC	R2
1.417	2.441	0.276	TC	R2
1.417	2.441	0.394	TC	R2
1.417	2.500	0.512	TC	R2
1.417	2.677	0.315	SB2	G2
1.417	2.677	0.394	SC	R2
1.417	2.677	0.472	TB2	G2
1.417	2.835	0.276	TC	R2
1.417	3.268	0.472	SC	R2
1.437	1.693	0.315	KB	G2
1.437	1.713	0.315	KB	G2
1.437	1.732	0.197	VC	R2
1.437	1.750	0.193	SBR	C2
1.437	1.850	0.197	TC	R2
1.437	1.937	0.252	SB	G2
1.437	2.000	0.311	TB2	C2
1.437	2.000	0.311	TC	R2
1.437	2.062	0.311	TC	RPA
1.437	2.063	0.311	TB2	P2
1.437	2.125	0.311	TB2	C2
1.437	2.187	0.437	TC	R2
1.437	2.250	0.311	SB2	P2
1.437	2.250	0.311	TB2	P2
1.437	2.250	0.374	TC	R2
1.437	2.328	0.252	SC	R2
1.437	2.328	0.252	TC	R2
1.437	2.329	0.374	TB2	C2
1.437	2.374	0.311	TB2	P2
1.437	2.441	0.276	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.437	2.500	0.500	SC	R2
1.437	2.502	0.311	TB2	G2
1.437	2.502	0.500	SB2	G2
1.437	2.686	0.311	SB2	P2
1.437	2.686	0.374	TB2	P2
1.437	2.835	0.276	TC	R2
1.437	3.500	0.437	TC	R2
1.438	1.560	0.118	VB	C2
1.447	2.441	0.157	KC	R2
1.450	2.000	0.311	SB	G2
1.457	1.772	0.276	TC	R2
1.457	1.850	0.157	VB	G2
1.457	1.850	0.394	TC	R2
1.457	1.969	0.236	TB	G2
1.457	1.969	0.276	SC	R2
1.457	1.969	0.394	TC	R2
1.457	2.047	0.276	SC	RPA
1.457	2.047	0.315	SC	R2
1.457	2.047	0.315	TC	R2
1.457	2.087	0.276	TC	R2
1.457	2.165	0.315	TC	R2
1.457	2.205	0.354	SC	RPA
1.457	2.205	0.354	TB2	G2
1.457	2.244	0.394	TC	R2
1.457	2.283	0.276	TC	R2
1.457	2.283	0.394	TC	R2
1.457	2.283	0.512	TC	R2
1.457	2.441	0.315	SC	R2
1.457	2.441	0.315	TC	R2
1.457	2.441	0.394	SC	R2
1.457	2.441	0.394	TC	R2
1.457	2.520	0.512	TC	R2
1.457	2.835	0.276	TC	R2
1.457	2.913	0.433	TC	R2
1.457	3.150	0.394	SC	R2
1.457	3.150	0.472	SC	R2
1.457	3.150	0.512	SC	R2
1.469	1.875	0.189	VC	R2
1.469	2.063	0.500	SB	GPA
1.469	2.125	0.252	SB	G2
1.469	2.375	0.374	TB2	C2
1.476	1.772	0.157	VB2	G2
1.476	1.850	0.276	KC	P2
1.488	2.442	0.185	WPB	G4
1.489	3.147	0.378	TC	RV
1.491	2.191	0.252	SA2	G2
1.494	1.995	0.252	VB	C2
1.496	1.654	0.252	VC	R2
1.496	1.693	0.118	VB	G2
1.496	1.772	0.157	VB	G2
1.496	1.772	0.315	KB	G2
1.496	1.850	0.276	TBR	G2
1.496	1.850	0.276	TC	R2
1.496	1.850	0.394	SB	G2

Shaft	Bore	Width	Lip Style	Material
1.496	1.850	0.394	SBR	G2
1.496	1.850	0.394	SC	R2
1.496	1.850	0.394	TC	R2
1.496	1.870	0.197	TB	G3
1.496	1.890	0.157	VB	G2
1.496	1.890	0.236	TC	R2
1.496	1.890	0.276	TC	R2
1.496	1.890	0.394	TC	R2
1.496	1.929	0.315	TC	R2
1.496	1.937	0.354	TB	G2
1.496	1.969	0.276	KC	R2
1.496	1.969	0.276	SB2	GV
1.496	1.969	0.276	SC	R2
1.496	1.969	0.276	TB	G2
1.496	1.969	0.276	TC	R2
1.496	1.969	0.315	SC	R2
1.496	1.969	0.315	TC	R2
1.496	1.969	0.394	TC	R2
1.496	1.980	0.394	KB	G2
1.496	1.980	0.394	KB2	C2
1.496	2.008	0.276	TB	G2
1.496	2.008	0.276	TC	R2
1.496	2.047	0.236	KB2	G2
1.496	2.047	0.236	KC	R2
1.496	2.047	0.236	TB2	G2
1.496	2.047	0.236	TC	R2
1.496	2.047	0.276	SB	G2
1.496	2.047	0.276	SC	R2
1.496	2.047	0.276	TA2	G2
1.496	2.047	0.276	TB2	G2
1.496	2.047	0.276	TC	R2
1.496	2.047	0.315	SC	R2
1.496	2.047	0.315	TC	R2
1.496	2.047	0.335	TC	R2
1.496	2.047	0.354	TC	R2
1.496	2.047	0.374	KC	R2
1.496	2.047	0.394	SB2	C2
1.496	2.047	0.394	SC	R2
1.496	2.047	0.394	TC	R2
1.496	2.071	0.236	TC	R2
1.496	2.087	0.315	TC	RPA
1.496	2.126	0.276	SB	PPA
1.496	2.126	0.276	TC	R2
1.496	2.126	0.394	SC	R2
1.496	2.126	0.394	TC	R2
1.496	2.126	0.433	TB2	G2
1.496	2.165	0.236	SC	R2
1.496	2.165	0.236	TC	R2
1.496	2.165	0.276	SC	R2
1.496	2.165	0.276	TC	R2
1.496	2.165	0.315	TBR	GS
1.496	2.165	0.315	TC	R2
1.496	2.165	0.354	TB	G2
1.496	2.165	0.354	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.496	2.165	0.394	SC	R2
1.496	2.165	0.394	TC	R2
1.496	2.177	0.315	KBR	C2
1.496	2.205	0.276	TC	R2
1.496	2.205	0.315	TC	R2
1.496	2.205	0.354	TB2	G2
1.496	2.205	0.394	SC	R2
1.496	2.205	0.394	TC	R3
1.496	2.205	0.472	TC	R2
1.496	2.244	0.394	TC	R2
1.496	2.283	0.276	TC	R2
1.496	2.283	0.315	TA2	G2
1.496	2.283	0.315	TB2	P2
1.496	2.283	0.315	TC	R2
1.496	2.283	0.335	TB2	GS
1.496	2.283	0.394	TC	R2
1.496	2.283	0.413	TB2	P2
1.496	2.283	0.433	TB2	GPA
1.496	2.283	0.433	TC	R2
1.496	2.283	0.472	TC	R2
1.496	2.362	0.315	TB2	G2
1.496	2.362	0.315	TC	R2
1.496	2.362	0.354	TC	R2
1.496	2.362	0.394	TC	R2
1.496	2.382	0.472	TC	R3
1.496	2.441	0.276	SC	R2
1.496	2.441	0.276	TC	R2
1.496	2.441	0.315	SC	R2
1.496	2.441	0.315	TC	R2
1.496	2.441	0.354	TC	R2
1.496	2.441	0.394	SC	R2
1.496	2.441	0.394	TC	R2
1.496	2.441	0.433	SC	R2
1.496	2.441	0.433	TB2	G2
1.496	2.441	0.472	TC	R2
1.496	2.500	0.394	TB2	G2
1.496	2.500	0.394	TC	R2
1.496	2.500	0.472	TC	R3
1.496	2.520	0.433	DC	R2
1.496	2.520	0.472	TC	R2
1.496	2.559	0.315	SC	R2
1.496	2.559	0.315	TC	R2
1.496	2.559	0.354	TB2	GPA
1.496	2.559	0.354	TC	R2
1.496	2.559	0.394	TC	R2
1.496	2.559	0.433	TC	R2
1.496	2.559	0.472	TC	R2
1.496	2.559	0.512	TC	R2
1.496	2.677	0.315	TC	R2
1.496	2.677	0.472	TC	R2
1.496	2.756	0.394	TB2	G2
1.496	2.756	0.394	TC	R2
1.496	2.835	0.394	TC	R2
1.496	2.835	0.472	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.496	2.913	0.394	SC	R2
1.496	2.913	0.433	TB2	GPA
1.496	2.913	0.433	TC	R2
1.496	3.150	0.315	TC	R2
1.496	3.150	0.394	TC	R2
1.496	3.543	0.315	SB2	G2
1.499	1.630	0.126	VB	C2
1.499	2.310	0.500	SC	RV
1.500	1.750	0.157	VB	G2
1.500	1.750	0.157	VB	G2
1.500	1.750	0.374	WPB	G4
1.500	1.772	0.189	WPB	G4
1.500	1.875	0.126	WPB	G4
1.500	1.875	0.189	SB	G2
1.500	1.875	0.189	SB	P2
1.500	1.875	0.189	TB	P2
1.500	1.875	0.189	VB	C2
1.500	1.875	0.189	WPB	G4
1.500	1.875	0.252	SB	G2
1.500	1.875	0.252	TB	P2
1.500	1.875	0.252	WPB	G4
1.500	1.917	0.252	SB	GV
1.500	1.921	0.252	SB2	GV
1.500	1.937	0.252	SBR	C2
1.500	1.937	0.252	SC	R2
1.500	1.938	0.189	TB	C2
1.500	1.939	0.248	TC	RV
1.500	1.983	0.189	TB2	C2
1.500	1.983	0.252	TB2	G2
1.500	1.983	0.252	TC	R2
1.500	1.983	0.252	VB2	G2
1.500	1.983	0.437	SA2	G2
1.500	1.984	0.189	VB2	C2
1.500	1.987	0.189	TB	G2
1.500	1.987	0.311	SB2	P2
1.500	1.988	0.252	TB2	C2
1.500	1.989	0.252	KB	C2
1.500	1.989	0.252	VA2	G2
1.500	2.000	0.189	SC	R2
1.500	2.000	0.189	VB2	C2
1.500	2.000	0.224	VB	C2
1.500	2.000	0.252	KC	P2
1.500	2.000	0.252	SC	RPA
1.500	2.000	0.252	SC	R2
1.500	2.000	0.252	WPB	G4
1.500	2.000	0.252	WPB	G4
1.500	2.000	0.311	SB	P2
1.500	2.000	0.311	TB	P2
1.500	2.000	0.311	TC	R2
1.500	2.000	0.311	TC	R2
1.500	2.000	0.311	TC	R2
1.500	2.000	0.311	WPB	G4
1.500	2.000	0.374	SC	R2
1.500	2.000	0.374	TB2	P2
1.500	2.062	0.209	VB2	P2

Shaft	Bore	Width	Lip Style	Material
1.500	2.062	0.209	VC	R2
1.500	2.062	0.209	VC	R2
1.500	2.063	0.252	SC	R2
1.500	2.063	0.252	TB2	P2
1.500	2.063	0.272	SB	P2
1.500	2.063	0.311	SC	R2
1.500	2.063	0.437	TB2	C2
1.500	2.125	0.311	SB	P2
1.500	2.125	0.311	TC	R2
1.500	2.125	0.315	TB2	G2
1.500	2.125	0.315	TB2	P2
1.500	2.125	0.374	TB2	P2
1.500	2.125	0.437	SC	R2
1.500	2.125	0.437	TB2	PS
1.500	2.187	0.252	SBR	C2
1.500	2.188	0.272	SBR	C2
1.500	2.250	0.311	SC	R2
1.500	2.250	0.311	TB2	G2
1.500	2.250	0.311	TC	R2
1.500	2.250	0.374	SBR	GV
1.500	2.250	0.374	SC	R2
1.500	2.250	0.374	TC	R2
1.500	2.250	0.500	SC	R2
1.500	2.250	0.500	TB2	G2
1.500	2.254	0.252	VB2	P2
1.500	2.254	0.311	SA2	P2
1.500	2.260	0.406	SB2	P2
1.500	2.327	0.406	VB2	G2
1.500	2.328	0.374	TC	R2
1.500	2.328	0.375	TB2	G2
1.500	2.375	0.252	KC	P2
1.500	2.375	0.311	TB2	P2
1.500	2.375	0.311	TC	R2
1.500	2.375	0.500	SB2	P2
1.500	2.375	0.500	TB2	G2
1.500	2.375	0.500	TB2	PPA
1.500	2.430	0.374	SC	R2
1.500	2.437	0.252	WPB	G4
1.500	2.441	0.311	TB2	P2
1.500	2.500	0.252	SC	R2
1.500	2.500	0.311	SC	R2
1.500	2.500	0.311	TC	R2
1.500	2.500	0.374	SC	R2
1.500	2.500	0.500	SA2	C2
1.500	2.500	0.500	SC	R2
1.500	2.500	0.500	TB2	P2
1.500	2.502	0.311	SB2	G2
1.500	2.502	0.311	TB2	C2
1.500	2.502	0.374	SB2	P2
1.500	2.502	0.433	SB2	P2
1.500	2.623	0.311	TC	R2
1.500	2.686	0.500	SB2	C2
1.500	2.687	0.374	VC	R2
1.500	2.721	0.374	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.500	2.750	0.311	SB2	C2
1.500	2.750	0.311	TB2	P2
1.500	2.750	0.374	SC	R2
1.500	2.758	0.500	SB2	G2
1.500	2.758	0.500	TC	R2
1.500	2.835	0.311	SB2	P2
1.500	2.835	0.311	TB2	P2
1.500	2.874	0.469	SB2	C2
1.500	2.875	0.437	TC	R2
1.500	3.000	0.374	TB2	P2
1.500	3.125	0.374	SB2	G2
1.500	3.125	0.375	TB2	C2
1.500	3.150	0.276	TC	R2
1.512	1.987	0.189	VB2	G2
1.524	2.374	0.374	SA2	P2
1.535	1.929	0.335	TB	G2
1.535	1.984	0.280	TB	G2
1.535	1.984	0.335	TBR	C2
1.535	1.984	0.354	TBR	C2
1.535	1.988	0.335	TBR	G2
1.535	2.008	0.295	SC	R2
1.535	2.008	0.295	TC	R2
1.535	2.047	0.236	KB	G2
1.535	2.087	0.374	TC	R2
1.535	2.126	0.236	KB2	G2
1.535	2.165	0.354	TC	R2
1.535	2.185	0.394	TA2	G2
1.535	2.205	0.276	TC	R2
1.535	2.323	0.315	TC	RS
1.535	2.362	0.354	TB2	C2
1.535	2.362	0.394	TB2	G2
1.535	2.441	0.236	TC	RV
1.535	2.559	0.315	TC	R2
1.535	2.559	0.354	SC	R2
1.535	2.756	0.433	DC	R2
1.552	2.686	0.500	SBR	C2
1.555	2.362	0.394	TB2	G2
1.559	2.047	0.433	TC	R2
1.562	2.250	0.374	SA2	C2
1.562	2.441	0.500	TC	R2
1.562	2.500	0.500	SB2	C2
1.562	2.502	0.500	SA2	P2
1.562	2.623	0.311	TC	R2
1.562	2.686	0.374	TB2	P2
1.562	3.150	0.311	TC	R2
1.563	2.000	0.173	SC	R4
1.563	2.062	0.205	WPB	G4
1.563	2.063	0.209	VB2	P2
1.563	2.063	0.252	SB	CPA
1.563	2.063	0.252	SBR	P2
1.563	2.125	0.311	SB2	CPA
1.563	2.125	0.315	TA2	P2
1.563	2.125	0.315	TB2	CPA
1.563	2.125	0.315	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.563	2.125	0.374	TB2	P2
1.563	2.125	0.437	TA2	G2
1.563	2.125	0.437	TA2	P2
1.563	2.187	0.350	SC	RPA
1.563	2.250	0.252	SBR	G2
1.563	2.250	0.311	TB2	P2
1.563	2.250	0.311	TC	R2
1.563	2.374	0.311	SB2	C2
1.563	2.374	0.311	TA2	C2
1.563	2.374	0.311	TB2	C2
1.563	2.375	0.252	VA2	P2
1.563	2.375	0.374	TC	R2
1.563	2.375	0.469	TB2	C2
1.563	2.406	0.500	SA2	G2
1.563	2.437	0.374	TB2	P2
1.563	2.437	0.437	TC	R2
1.563	2.441	0.374	TB2	P2
1.563	2.465	0.370	TB2	PV
1.563	2.500	0.374	SC	R2
1.563	2.500	0.500	SA2	P2
1.563	2.500	0.500	TC	R2
1.563	2.502	0.311	TB2	P2
1.563	2.561	0.500	SA2	P2
1.563	2.563	0.437	TC	R2
1.563	2.623	0.311	TB2	P2
1.563	2.687	0.374	TC	R2
1.563	2.875	0.311	SB2	P2
1.563	2.875	0.374	TB2	G2
1.563	3.150	0.311	TB2	P2
1.574	2.502	0.598	DC	R2
1.575	1.772	0.079	VC	R2
1.575	1.850	0.157	TB2	C2
1.575	1.850	0.157	VB	G2
1.575	1.850	0.157	VC	R2
1.575	1.890	0.157	VC	R2
1.575	1.929	0.217	TB	G2
1.575	1.953	0.287	SC	R2
1.575	1.969	0.157	VB	G2
1.575	1.969	0.157	VC	R2
1.575	1.969	0.197	TC	R2
1.575	1.969	0.256	TC	R2
1.575	1.969	0.276	SC	R2
1.575	1.969	0.276	TC	R2
1.575	1.969	0.315	SC	R2
1.575	1.969	0.315	TC	R2
1.575	1.969	0.394	SC	R2
1.575	1.969	0.394	TC	R2
1.575	2.008	0.276	TB	G2
1.575	2.047	0.157	KC	R2
1.575	2.047	0.197	VB2	G2
1.575	2.047	0.197	VC	R2
1.575	2.047	0.236	TC	R2
1.575	2.047	0.236	VC	R2
1.575	2.047	0.256	SC	R2

Shaft	Bore	Width	Lip Style	Material
1.575	2.047	0.276	KC	R2
1.575	2.047	0.276	SB	G2
1.575	2.047	0.276	SC	RV
1.575	2.047	0.276	SC	R2
1.575	2.047	0.276	SC	R2
1.575	2.047	0.276	TA2	G2
1.575	2.047	0.276	TB	G2
1.575	2.047	0.276	TC	R2
1.575	2.047	0.315	TB2	P2
1.575	2.047	0.315	TC	R2
1.575	2.047	0.354	TC	R2
1.575	2.047	0.394	TC	R2
1.575	2.063	0.228	TB	P2
1.575	2.067	0.236	TC	R3
1.575	2.087	0.276	TB	G2
1.575	2.087	0.315	TC	R2
1.575	2.087	0.335	TC	R2
1.575	2.126	0.197	TB	G2
1.575	2.126	0.197	VB	G2
1.575	2.126	0.236	TBR	C2
1.575	2.126	0.276	TB2	G2
1.575	2.126	0.276	TC	R2
1.575	2.126	0.276	VC	R2
1.575	2.126	0.295	TB2	G2
1.575	2.126	0.315	SB2	G2
1.575	2.126	0.315	TBR	G2
1.575	2.126	0.315	TC	R2
1.575	2.126	0.394	TC	R2
1.575	2.165	0.197	KC	R2
1.575	2.165	0.236	SC	RV
1.575	2.165	0.236	TC	R2
1.575	2.165	0.256	KB2	C2
1.575	2.165	0.256	TB2	G2
1.575	2.165	0.276	DC	R2
1.575	2.165	0.276	SC	RV
1.575	2.165	0.276	SC	R2
1.575	2.165	0.276	TC	R2
1.575	2.165	0.315	KB2	G2
1.575	2.165	0.315	SC	R2
1.575	2.165	0.315	TB2	P2
1.575	2.165	0.315	TC	RV
1.575	2.165	0.315	TC	R2
1.575	2.165	0.354	SA2	G2
1.575	2.165	0.354	TB2	G2
1.575	2.165	0.394	SC	R2
1.575	2.165	0.394	TC	R2
1.575	2.165	0.472	TC	R2
1.575	2.191	0.252	SA2	P2
1.575	2.205	0.276	SC	R2
1.575	2.205	0.276	TB2	G2
1.575	2.205	0.276	TC	R2
1.575	2.205	0.315	SC	R2
1.575	2.205	0.315	TB2	G2
1.575	2.205	0.315	TC	RPA

Shaft	Bore	Width	Lip Style	Material
1.575	2.205	0.315	TC	R2
1.575	2.205	0.315	TC	R2
1.575	2.205	0.394	TB2	G2
1.575	2.205	0.394	TC	R2
1.575	2.205	0.472	SC	R2
1.575	2.205	0.472	TC	R2
1.575	2.244	0.276	TC	R2
1.575	2.244	0.315	TBR	C2
1.575	2.244	0.394	TC	R2
1.575	2.250	0.394	SB2	C2
1.575	2.250	0.394	TB2	C2
1.575	2.250	0.394	TC	R2
1.575	2.283	0.236	SC	RPA
1.575	2.283	0.236	TC	R2
1.575	2.283	0.256	TC	R2
1.575	2.283	0.315	SC	R2
1.575	2.283	0.315	TC	R2
1.575	2.283	0.354	SC	R2
1.575	2.283	0.394	SC	R2
1.575	2.283	0.394	TC	R2
1.575	2.283	0.472	SC	R2
1.575	2.283	0.472	TC	R2
1.575	2.323	0.394	TC	R2
1.575	2.358	0.217	TC	R2
1.575	2.362	0.197	VC	R2
1.575	2.362	0.236	TC	R2
1.575	2.362	0.276	SC	R2
1.575	2.362	0.276	TC	R2
1.575	2.362	0.315	SC	R2
1.575	2.362	0.315	TC	R2
1.575	2.362	0.394	DC	R2
1.575	2.362	0.394	SC	R2
1.575	2.362	0.394	TB2	G2
1.575	2.362	0.394	TC	R2
1.575	2.362	0.472	SC	R2
1.575	2.362	0.472	TB2	G2
1.575	2.362	0.472	TC	R2
1.575	2.441	0.197	VC	R2
1.575	2.441	0.256	KC	R2
1.575	2.441	0.276	SC	R2
1.575	2.441	0.276	TC	R2
1.575	2.441	0.315	SC	R2
1.575	2.441	0.315	TC	R2
1.575	2.441	0.354	TB2	G2
1.575	2.441	0.354	TC	R2
1.575	2.441	0.394	DC	R2
1.575	2.441	0.394	SC	R2
1.575	2.441	0.394	TB2	G2
1.575	2.441	0.394	TC	R2
1.575	2.441	0.433	TB2	G2
1.575	2.441	0.433	TC	R2
1.575	2.441	0.453	SC	R2
1.575	2.441	0.453	TC	R2
1.575	2.441	0.472	SC	R2

Shaft	Bore	Width	Lip Style	Material
1.575	2.441	0.472	TB2	G2
1.575	2.441	0.472	TC	R2
1.575	2.441	0.512	TB2	C2
1.575	2.461	0.433	TC	RPA
1.575	2.480	0.276	TC	R2
1.575	2.500	0.394	TB2	G2
1.575	2.500	0.394	TC	R2
1.575	2.520	0.157	TC	R2
1.575	2.520	0.394	TC	R2
1.575	2.520	0.472	TC	R2
1.575	2.559	0.276	TC	R2
1.575	2.559	0.315	TC	R2
1.575	2.559	0.354	SB2	C2
1.575	2.559	0.394	SA2	G2
1.575	2.559	0.394	SC	R2
1.575	2.559	0.394	TC	R2
1.575	2.559	0.472	TB2	G2
1.575	2.559	0.472	TC	R2
1.575	2.598	0.236	SB2	P2
1.575	2.638	0.472	TC	R2
1.575	2.677	0.197	TC	R2
1.575	2.677	0.276	SC	R2
1.575	2.677	0.276	TC	R2
1.575	2.677	0.315	SB2	P2
1.575	2.677	0.315	SC	RV
1.575	2.677	0.315	TC	R2
1.575	2.677	0.394	SC	R2
1.575	2.677	0.394	TB2	G2
1.575	2.677	0.394	TBR	G2
1.575	2.677	0.394	TC	R2
1.575	2.677	0.433	TB2	G2
1.575	2.677	0.472	SC	R2
1.575	2.677	0.472	TC	R2
1.575	2.756	0.315	TC	R2
1.575	2.756	0.394	SC	R2
1.575	2.756	0.394	TA2	G2
1.575	2.756	0.394	TC	R2
1.575	2.756	0.472	SA2	G2
1.575	2.756	0.472	TC	R2
1.575	2.835	0.276	SC	R2
1.575	2.835	0.276	TC	R2
1.575	2.835	0.315	TC	R2
1.575	2.835	0.394	SBR	G2
1.575	2.835	0.394	SC	R2
1.575	2.835	0.394	TC	R2
1.575	2.835	0.472	TB2	G2
1.575	2.835	0.472	TC	R2
1.575	2.913	0.394	TC	R2
1.575	2.953	0.276	SC	R2
1.575	2.953	0.315	SB2	G2
1.575	2.953	0.394	TC	R2
1.575	2.953	0.472	TC	R2
1.575	2.953	0.512	TC	R2
1.575	2.992	0.315	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.575	3.071	0.276	TC	R2
1.575	3.150	0.276	SC	R2
1.575	3.150	0.276	TC	R2
1.575	3.150	0.315	SC	R2
1.575	3.150	0.315	TC	R2
1.575	3.150	0.394	SC	R2
1.575	3.150	0.394	TB2	G2
1.575	3.150	0.394	TC	R2
1.575	3.150	0.472	TC	R2
1.575	3.150	0.512	SC	R2
1.575	3.169	0.394	TC	R2
1.575	3.346	0.394	SC	R2
1.575	3.346	0.394	TC	R2
1.575	3.346	0.433	TB2	G2
1.575	3.346	0.472	TC	R2
1.575	3.386	0.394	TB2	C2
1.575	3.465	0.236	SC	R2
1.575	3.543	0.315	SB2	P2
1.575	3.543	0.315	SC	R2
1.575	3.543	0.315	TC	R2
1.575	3.543	0.394	SC	R2
1.575	3.543	0.394	TC	R2
1.575	3.543	0.472	SC	R2
1.575	3.543	0.472	TC	R2
1.575	4.331	0.394	TC	R2
1.578	2.408	0.500	SA2	P2
1.593	2.502	0.252	SB2	P2
1.594	2.283	0.315	TC	R2
1.594	2.437	0.469	SA2	P2
1.610	2.000	0.217	SC	RPA
1.614	1.941	0.244	TB	GS
1.614	2.008	0.197	KC	R2
1.614	2.008	0.197	TC	R2
1.614	2.087	0.276	TA2	G2
1.614	2.087	0.276	TBR	G2
1.614	2.087	0.276	TC	R2
1.614	2.087	0.315	TB	G2
1.614	2.126	0.276	TC	R2
1.614	2.165	0.276	TB	G2
1.614	2.165	0.276	TC	R2
1.614	2.165	0.354	TB	G2
1.614	2.193	0.354	TC	R2
1.614	2.205	0.276	SC	R2
1.614	2.205	0.276	TBR	G2
1.614	2.205	0.276	TC	R2
1.614	2.402	0.354	TB2	G2
1.614	2.441	0.315	TC	R2
1.614	2.520	0.394	TC	R2
1.614	2.559	0.354	SB2	G2
1.614	2.559	0.394	TB2	G2
1.617	1.998	0.299	TB2	C2
1.619	2.445	0.193	SBR	C2
1.619	2.532	0.260	TB2	C2
1.619	2.532	0.260	TB2	C2

Shaft	Bore	Width	Lip Style	Material
1.619	2.532	0.260	VB	C2
1.620	1.997	0.252	SB	C2
1.620	2.000	0.252	SB	C2
1.625	1.750	0.126	VB	C2
1.625	1.875	0.157	WPB	G4
1.625	1.937	0.252	TB	GS
1.625	1.938	0.252	TB	GPA
1.625	2.000	0.142	TB	CS
1.625	2.000	0.189	VC	R2
1.625	2.000	0.189	WPB	G4
1.625	2.000	0.220	SC	RV
1.625	2.000	0.252	SB	G2
1.625	2.000	0.252	TC	R2
1.625	2.116	0.311	TB	P2
1.625	2.125	0.252	SB2	PPA
1.625	2.125	0.252	SC	R2
1.625	2.125	0.252	VB2	G2
1.625	2.125	0.252	WPB	G4
1.625	2.125	0.283	SB2	CV
1.625	2.160	0.276	SB2	P2
1.625	2.187	0.374	TC	R2
1.625	2.207	0.276	SB2	P2
1.625	2.207	0.276	SB2	P2
1.625	2.250	0.311	TB2	P2
1.625	2.282	0.311	SB2	P2
1.625	2.374	0.252	TB2	P2
1.625	2.374	0.311	SB2	C2
1.625	2.374	0.311	TB2	P2
1.625	2.374	0.500	SA2	C2
1.625	2.375	0.374	TC	R2
1.625	2.375	0.437	SA2	P2
1.625	2.437	0.311	SB2	P2
1.625	2.437	0.311	TB2	GV
1.625	2.437	0.374	SB2	C2
1.625	2.437	0.374	TB2	G2
1.625	2.437	0.469	TA2	G2
1.625	2.437	0.500	SB2	C2
1.625	2.441	0.374	TB2	P2
1.625	2.441	0.374	TC	R2
1.625	2.441	0.472	DC	R2
1.625	2.500	0.252	SB	GV
1.625	2.500	0.252	TB2	CS
1.625	2.500	0.311	SC	R2
1.625	2.502	0.311	TB2	P2
1.625	2.502	0.311	TC	R2
1.625	2.502	0.374	TB2	P2
1.625	2.502	0.469	SC	R2
1.625	2.562	0.311	TB2	PPA
1.625	2.563	0.374	VB2	C2
1.625	2.575	0.500	SA2	C2
1.625	2.625	0.250	TB2	P2
1.625	2.625	0.311	TB2	G2
1.625	2.625	0.374	TC	R2
1.625	2.750	0.311	SA2	P2

Shaft	Bore	Width	Lip Style	Material
1.625	2.750	0.311	TB2	P2
1.625	2.750	0.374	TB2	G2
1.625	3.000	0.311	SA2	G2
1.625	3.000	0.500	SA2	P2
1.626	1.874	0.126	VB	CV
1.626	1.874	0.126	VB	CV
1.642	2.165	0.276	TC	R2
1.642	2.165	0.394	TC	R2
1.646	2.656	0.406	TB2	PPA
1.652	2.125	0.248	TC	RV
1.654	1.969	0.236	TC	R2
1.654	1.969	0.276	TC	R2
1.654	1.969	0.394	TC	R2
1.654	2.008	0.276	TC	R2
1.654	2.047	0.157	TC	R2
1.654	2.047	0.157	VB	C2
1.654	2.047	0.157	VC	R2
1.654	2.047	0.236	TC	R2
1.654	2.047	0.276	SC	R2
1.654	2.047	0.276	TC	R2
1.654	2.047	0.315	TC	R2
1.654	2.047	0.394	SC	R2
1.654	2.047	0.472	TC	R2
1.654	2.087	0.276	TBR	G2
1.654	2.087	0.315	TB	G2
1.654	2.126	0.276	TC	R2
1.654	2.126	0.295	SBR	C2
1.654	2.126	0.295	TB	G2
1.654	2.165	0.236	TB2	C2
1.654	2.165	0.236	TC	R2
1.654	2.165	0.276	KC	R2
1.654	2.165	0.276	SA2	GV
1.654	2.165	0.276	SC	R2
1.654	2.165	0.276	TB	G2
1.654	2.165	0.276	TB2	G2
1.654	2.165	0.276	TBR	G2
1.654	2.165	0.276	TC	R2
1.654	2.165	0.315	SC	R2
1.654	2.165	0.315	TB2	G2
1.654	2.165	0.315	TC	R2
1.654	2.165	0.354	SB2	CV
1.654	2.165	0.354	SBR	G2
1.654	2.165	0.354	TB2	G2
1.654	2.165	0.354	TC	R2
1.654	2.165	0.394	TC	R2
1.654	2.205	0.236	TC	R2
1.654	2.205	0.276	KC	R2
1.654	2.205	0.276	SC	R2
1.654	2.205	0.276	TB2	G2
1.654	2.205	0.276	TB2	C2
1.654	2.205	0.276	TC	R2
1.654	2.205	0.354	TB	G2
1.654	2.205	0.394	TC	R2
1.654	2.213	0.276	KC	R2

Shaft	Bore	Width	Lip Style	Material
1.654	2.244	0.276	TC	R2
1.654	2.250	0.394	TB2	G2
1.654	2.283	0.276	KBR	G2
1.654	2.283	0.276	SB	G2
1.654	2.283	0.276	TC	R2
1.654	2.283	0.315	TB2	G2
1.654	2.283	0.315	TC	R2
1.654	2.283	0.394	SC	R2
1.654	2.283	0.394	TC	R2
1.654	2.283	0.472	DC	R2
1.654	2.283	0.472	TC	R2
1.654	2.362	0.236	TC	R2
1.654	2.362	0.276	TC	R2
1.654	2.362	0.315	TC	R2
1.654	2.362	0.354	SB2	CPA
1.654	2.362	0.354	TB2	GPA
1.654	2.362	0.354	TC	R2
1.654	2.362	0.394	SC	R2
1.654	2.362	0.394	TC	R2
1.654	2.362	0.472	SBR	G2
1.654	2.362	0.472	SC	R2
1.654	2.362	0.472	TC	R2
1.654	2.441	0.236	SC	R2
1.654	2.441	0.256	SB2	PS
1.654	2.441	0.276	SC	R2
1.654	2.441	0.276	TB2	G2
1.654	2.441	0.276	TC	R2
1.654	2.441	0.315	SB2	C2
1.654	2.441	0.315	SC	R2
1.654	2.441	0.315	TC	RPA
1.654	2.441	0.315	TC	R2
1.654	2.441	0.354	TC	R2
1.654	2.441	0.394	SC	R2
1.654	2.441	0.394	TC	R2
1.654	2.441	0.433	DC	RP
1.654	2.441	0.472	TA2	G2
1.654	2.441	0.472	TC	R2
1.654	2.480	0.276	TC	R2
1.654	2.500	0.512	TA2	P2
1.654	2.520	0.236	KC	R2
1.654	2.520	0.276	SC	R2
1.654	2.520	0.315	TC	R2
1.654	2.520	0.394	TB2	G2
1.654	2.520	0.394	TC	R2
1.654	2.520	0.472	DC	RP
1.654	2.559	0.295	TC	R2
1.654	2.559	0.315	SC	R2
1.654	2.559	0.315	TC	R2
1.654	2.559	0.354	TC	R2
1.654	2.559	0.394	SC	R2
1.654	2.559	0.394	TC	R2
1.654	2.559	0.433	DC	RP
1.654	2.559	0.472	SB2	G2
1.654	2.559	0.472	TA2	G3



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.654	2.559	0.472	TB2	G2
1.654	2.559	0.472	TC	R2
1.654	2.638	0.394	TC	R3
1.654	2.677	0.315	TC	R2
1.654	2.677	0.394	TC	R2
1.654	2.756	0.315	TC	R2
1.654	2.756	0.394	TC	R2
1.654	2.756	0.472	TC	R2
1.654	2.835	0.315	SC	R2
1.654	2.835	0.315	TC	R2
1.654	2.835	0.394	SB2	C2
1.654	2.835	0.394	SBR	C2
1.654	2.835	0.394	SC	R2
1.654	2.835	0.394	TC	R2
1.654	2.835	0.472	TB2	G2
1.654	2.835	0.472	TC	R2
1.654	2.953	0.394	TC	R2
1.654	2.953	0.472	TC	R2
1.654	2.992	0.315	TC	R2
1.654	2.992	0.472	TC	R2
1.654	3.071	0.394	TC	R2
1.654	3.150	0.394	TC	R2
1.654	3.346	0.315	SC	R2
1.654	3.346	0.315	TC	R2
1.656	2.623	0.382	TC	RPA
1.656	2.625	0.374	TB2	G2
1.656	2.686	0.500	SA2	P2
1.656	2.686	0.500	SB2	C2
1.656	2.937	0.374	TB2	P2
1.683	2.441	0.157	KC	R2
1.686	2.686	0.500	SB2	C2
1.687	2.125	0.189	SB	G2
1.687	2.187	0.189	SC	R2
1.687	2.328	0.217	VB2	G2
1.687	2.328	0.311	TB2	P2
1.687	2.374	0.311	TB2	P2
1.687	2.375	0.252	VB	P2
1.687	2.437	0.469	SBR	GS
1.687	2.437	0.469	SBR	CS
1.687	2.500	0.374	SC	R2
1.687	2.500	0.374	TB2	G2
1.687	2.502	0.311	TB2	G2
1.687	2.502	0.311	TB2	P2
1.687	2.502	0.311	TC	R2
1.687	2.561	0.500	TB2	P2
1.687	2.605	0.252	VBR	C2
1.687	2.623	0.374	VB2	G2
1.687	2.623	0.500	SB2	G2
1.687	2.625	0.252	SBR	CPA
1.687	2.625	0.374	TC	R2
1.687	2.625	0.469	TC	R2
1.687	2.686	0.311	TB2	C2
1.687	2.750	0.311	TB2	G2
1.687	2.875	0.311	TB2	G2

Shaft	Bore	Width	Lip Style	Material
1.687	2.875	0.374	TB2	P2
1.687	2.875	0.469	TA2	C2
1.688	2.250	0.312	SC	R2
1.688	2.437	0.315	TB2	P2
1.689	2.441	0.315	TC	R2
1.693	1.969	0.276	TC	R2
1.693	1.969	0.315	TB	G2
1.693	1.969	0.354	KB	G2
1.693	2.047	0.256	TB	G2
1.693	2.047	0.394	SB	G2
1.693	2.087	0.157	VB	G2
1.693	2.087	0.197	SC	RV
1.693	2.126	0.236	TA2	G2
1.693	2.126	0.295	KB	G2
1.693	2.126	0.295	SC	R2
1.693	2.126	0.295	TB	G2
1.693	2.165	0.236	TC	R2
1.693	2.165	0.276	SC	R2
1.693	2.165	0.295	TB	G2
1.693	2.165	0.295	TB	P2
1.693	2.165	0.315	KC	R2
1.693	2.165	0.315	SC	R2
1.693	2.165	0.315	TC	R2
1.693	2.165	0.354	TC	R2
1.693	2.205	0.276	SB	C2
1.693	2.283	0.276	TC	R2
1.693	2.283	0.315	TC	R2
1.693	2.323	0.276	TB2	G2
1.693	2.362	0.315	SB2	G2
1.693	2.362	0.394	SC	R2
1.693	2.441	0.315	SC	R2
1.693	2.441	0.315	TC	R2
1.693	2.441	0.472	TC	R2
1.693	2.480	0.276	TB2	G2
1.693	2.500	0.276	SC	R2
1.693	2.559	0.276	SA2	G2
1.693	2.559	0.276	TBR	C2
1.693	2.559	0.276	TC	R2
1.693	2.559	0.354	TC	RS
1.693	2.559	0.394	TC	R2
1.693	2.561	0.374	TB2	G2
1.693	2.598	0.394	TC	R2
1.693	2.953	0.394	SC	R2
1.703	2.329	0.374	TB2	C2
1.705	2.559	0.472	TC	RS
1.713	2.283	0.276	SB2	CPA
1.713	2.402	0.354	SBR	G2
1.713	2.441	0.256	TC	R2
1.718	2.559	0.508	KB2	P2
1.718	2.561	0.500	VB2	P2
1.718	2.875	0.469	SA2	C2
1.719	2.375	0.374	TC	R2
1.719	2.500	0.311	SB2	C2
1.719	2.500	0.311	TB2	PPA

Shaft	Bore	Width	Lip Style	Material
1.719	2.561	0.315	TB2	P2
1.719	2.561	0.500	TC	R2
1.719	2.561	0.500	VA2	C2
1.719	2.563	0.500	TB2	C2
1.719	2.625	0.374	TA2	G2
1.732	2.047	0.394	TC	R2
1.732	2.126	0.177	TB	C2
1.732	2.126	0.197	SC	R2
1.732	2.126	0.217	SB	G2
1.732	2.126	0.276	TC	R2
1.732	2.126	0.295	TB	G2
1.732	2.165	0.197	VC	R2
1.732	2.165	0.276	TC	R2
1.732	2.205	0.276	SB2	G2
1.732	2.283	0.276	SB2	G2
1.732	2.283	0.315	TC	R2
1.732	2.362	0.276	TC	R2
1.732	2.362	0.315	SC	R2
1.732	2.362	0.354	TC	R2
1.732	2.362	0.394	SC	R2
1.732	2.441	0.276	TC	R2
1.732	2.441	0.315	TB	G2
1.732	2.441	0.315	TC	R2
1.732	2.441	0.354	TC	R2
1.732	2.441	0.394	SC	R2
1.732	2.441	0.394	TC	R2
1.732	2.559	0.315	SB2	G2
1.732	2.559	0.315	TC	RV
1.732	2.559	0.394	SC	RV
1.732	2.559	0.394	TC	R2
1.732	2.559	0.433	TC	RPA
1.732	2.756	0.472	TC	R2
1.732	2.835	0.315	SC	R2
1.732	2.835	0.315	TB2	G2
1.732	2.835	0.315	TC	R2
1.732	2.835	0.394	SC	R2
1.732	2.953	0.276	TC	R2
1.732	3.150	0.472	SB2	G2
1.732	3.622	0.394	TC	R2
1.734	2.125	0.189	VBR	C2
1.734	2.336	0.252	VA2	G2
1.734	2.336	0.469	TB2	G2
1.745	1.880	0.126	VB	C2
1.749	1.999	0.110	VB	CV
1.749	1.999	0.110	VB	CV
1.750	2.063	0.134	WPB	G4
1.750	2.125	0.189	VBR	G2
1.750	2.125	0.189	WPB	G4
1.750	2.125	0.197	SB	C2
1.750	2.125	0.201	VB	C2
1.750	2.250	0.189	VB2	C2
1.750	2.250	0.189	WPB	G4
1.750	2.250	0.252	WPB	G4
1.750	2.250	0.252	WPB	G4

Shaft	Bore	Width	Lip Style	Material
1.750	2.250	0.311	SB	G2
1.750	2.250	0.311	SB2	PV
1.750	2.250	0.311	SC	R2
1.750	2.250	0.311	WPB	G4
1.750	2.250	0.374	SC	R2
1.750	2.250	0.374	TB	C2
1.750	2.313	0.252	SB	G2
1.750	2.328	0.252	TC	R2
1.750	2.328	0.374	TC	R2
1.750	2.328	0.437	SB2	G2
1.750	2.329	0.374	TB2	C2
1.750	2.356	0.500	TC	R2
1.750	2.374	0.252	WPB	G4
1.750	2.374	0.374	TB2	P2
1.750	2.374	0.484	DBR	CP
1.750	2.375	0.252	SC	R2
1.750	2.375	0.311	TB2	P2
1.750	2.375	0.311	TC	R2
1.750	2.375	0.374	SC	R2
1.750	2.375	0.374	TC	R2
1.750	2.406	0.374	TB2	G2
1.750	2.411	0.378	TB2	PPA
1.750	2.437	0.311	TB2	P2
1.750	2.437	0.311	TC	R2
1.750	2.437	0.374	TB2	G2
1.750	2.437	0.374	WPB	G4
1.750	2.437	0.469	SA2	C2
1.750	2.437	0.469	TB2	P2
1.750	2.441	0.374	TB2	PS
1.750	2.500	0.252	SB	GV
1.750	2.500	0.252	SC	RS
1.750	2.500	0.311	SB2	P2
1.750	2.500	0.311	SC	R2
1.750	2.500	0.311	TB2	C2
1.750	2.500	0.374	SB2	G2
1.750	2.500	0.374	SB2	G2
1.750	2.500	0.374	SC	R2
1.750	2.500	0.484	DC	RP
1.750	2.500	0.500	TA2	P2
1.750	2.500	0.500	TB2	G2
1.750	2.500	0.500	TC	R2
1.750	2.502	0.252	WPC	R4
1.750	2.502	0.311	SB2	G2
1.750	2.502	0.311	TB2	P2
1.750	2.502	0.311	TB2	P2
1.750	2.502	0.311	TB2	PV
1.750	2.502	0.374	SA2	GV
1.750	2.502	0.500	TB2	P2
1.750	2.537	0.189	SC	R2
1.750	2.559	0.394	TB2	G2
1.750	2.561	0.500	TB2	P2
1.750	2.563	0.311	SC	R2
1.750	2.565	0.311	TB2	P2
1.750	2.623	0.252	WPB	G4

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.750	2.623	0.311	TB2	G2
1.750	2.623	0.500	TB2	P2
1.750	2.625	0.311	TC	R2
1.750	2.625	0.500	TC	R2
1.750	2.681	0.437	TC	R2
1.750	2.686	0.311	SB2	P2
1.750	2.686	0.374	SB2	G2
1.750	2.686	0.500	SB	P2
1.750	2.687	0.374	SC	R2
1.750	2.687	0.437	SB2	C2
1.750	2.687	0.500	SB2	G2
1.750	2.687	0.500	TB2	C2
1.750	2.688	0.437	SC	R2
1.750	2.715	0.437	TC	R2
1.750	2.717	0.437	TB2	P2
1.750	2.750	0.311	SB2	P2
1.750	2.750	0.311	TB2	P2
1.750	2.750	0.311	TC	R2
1.750	2.750	0.374	SC	R2
1.750	2.750	0.374	TB2	G2
1.750	2.750	0.374	TC	R2
1.750	2.750	0.437	TC	R2
1.750	2.750	0.500	SA2	G2
1.750	2.750	0.500	SC	R2
1.750	2.750	0.500	TB	GPA
1.750	2.750	0.500	TB2	G2
1.750	2.875	0.311	SB2	P2
1.750	2.875	0.374	TC	R2
1.750	2.875	0.469	SA2	G2
1.750	2.875	0.500	SB2	C2
1.750	3.000	0.311	TB2	P2
1.750	3.000	0.374	SB2	PPA
1.750	3.000	0.374	TB2	P2
1.750	3.000	0.374	TC	R2
1.750	3.000	0.500	SB2	C2
1.750	3.000	0.500	SC	R2
1.750	3.063	0.488	DBR	C2
1.750	3.125	0.374	TB2	G2
1.750	3.153	0.311	SB2	P2
1.750	3.187	0.500	SC	R2
1.750	3.188	0.311	TC	R2
1.750	3.189	0.311	TB2	G2
1.750	3.189	0.374	TC	R2
1.750	3.189	0.437	TB2	P2
1.750	3.264	0.500	TB2	G2
1.750	3.624	0.500	TB2	G2
1.750	3.937	0.311	TB2	C2
1.752	2.441	0.394	SC	R2
1.752	2.441	0.394	TC	R2
1.752	2.625	0.374	SB2	C2
1.752	2.756	0.374	SC	R2
1.761	2.349	0.252	SB	C2
1.765	2.421	0.374	SC	R2
1.766	2.406	0.469	SB2	G2

Shaft	Bore	Width	Lip Style	Material
1.766	2.953	0.311	TC	R2
1.772	1.969	0.079	VC	R2
1.772	1.969	0.118	VB	G2
1.772	1.969	0.315	VC	R2
1.772	2.047	0.157	TB	G3
1.772	2.047	0.157	TC	R2
1.772	2.047	0.157	VB	G2
1.772	2.047	0.315	TC	R2
1.772	2.087	0.276	TB	G2
1.772	2.126	0.118	VB	C2
1.772	2.126	0.177	TC	R2
1.772	2.165	0.157	KB	C2
1.772	2.165	0.157	SC	R2
1.772	2.165	0.157	VC	R2
1.772	2.165	0.197	TC	R2
1.772	2.165	0.236	TC	R2
1.772	2.165	0.276	SB2	G2
1.772	2.165	0.276	SC	R2
1.772	2.165	0.276	TC	R2
1.772	2.165	0.295	TB	G2
1.772	2.165	0.315	TC	R2
1.772	2.165	0.394	TC	R2
1.772	2.165	0.472	TC	R2
1.772	2.205	0.236	SC	R2
1.772	2.205	0.236	TC	R2
1.772	2.205	0.315	TC	R2
1.772	2.205	0.394	TC	R2
1.772	2.244	0.217	TC	R2
1.772	2.244	0.315	TC	R2
1.772	2.244	0.354	TC	R2
1.772	2.283	0.276	TC	R2
1.772	2.283	0.315	SC	R2
1.772	2.283	0.315	TC	R2
1.772	2.283	0.354	TB2	G2
1.772	2.283	0.394	TC	R2
1.772	2.323	0.276	TC	R2
1.772	2.323	0.394	TB2	C2
1.772	2.323	0.394	TC	R2
1.772	2.328	0.394	TB2	C2
1.772	2.362	0.276	SC	R2
1.772	2.362	0.276	TC	R2
1.772	2.362	0.276	TC	R2
1.772	2.362	0.315	KC	R2
1.772	2.362	0.315	SB2	G2
1.772	2.362	0.315	SC	RV
1.772	2.362	0.315	SC	R2
1.772	2.362	0.315	TC	R2
1.772	2.362	0.354	SBR	G2
1.772	2.362	0.354	TB2	P2
1.772	2.362	0.354	TC	R2
1.772	2.362	0.394	SC	R2
1.772	2.362	0.394	TC	R2
1.772	2.362	0.472	TC	R2
1.772	2.402	0.394	TBR	G2

Shaft	Bore	Width	Lip Style	Material
1.772	2.441	0.197	SA2	G2
1.772	2.441	0.197	VC	R2
1.772	2.441	0.236	KB2	G2
1.772	2.441	0.236	SC	R2
1.772	2.441	0.276	SC	R2
1.772	2.441	0.276	TB2	G2
1.772	2.441	0.276	TC	R2
1.772	2.441	0.276	VC	R2
1.772	2.441	0.315	DC	R2
1.772	2.441	0.315	SC	R2
1.772	2.441	0.315	TC	R2
1.772	2.441	0.354	TB2	G2
1.772	2.441	0.354	TC	R2
1.772	2.441	0.394	SC	R2
1.772	2.441	0.394	TB	G2
1.772	2.441	0.394	TC	R2
1.772	2.441	0.433	DC	R2
1.772	2.441	0.472	TC	R2
1.772	2.480	0.276	TB2	G2
1.772	2.480	0.276	TC	R2
1.772	2.500	0.394	TB2	G2
1.772	2.500	0.394	TC	R2
1.772	2.520	0.276	TC	R2
1.772	2.520	0.394	TC	R2
1.772	2.520	0.472	SB2	G2
1.772	2.559	0.197	TB2	G2
1.772	2.559	0.197	VB2	G2
1.772	2.559	0.276	SC	R2
1.772	2.559	0.276	TC	R2
1.772	2.559	0.315	DC	R2
1.772	2.559	0.315	SC	R2
1.772	2.559	0.315	TB2	G2
1.772	2.559	0.315	TC	R2
1.772	2.559	0.315	VC	R2
1.772	2.559	0.354	SB2	G2
1.772	2.559	0.354	TC	R2
1.772	2.559	0.394	SC	R2
1.772	2.559	0.394	TA2	G3
1.772	2.559	0.394	TB2	G3
1.772	2.559	0.394	TC	R2
1.772	2.559	0.472	TB2	G2
1.772	2.559	0.472	TC	R2
1.772	2.566	0.382	TC	R2
1.772	2.598	0.394	TC	R2
1.772	2.677	0.236	VC	R2
1.772	2.677	0.276	TC	RPA
1.772	2.677	0.315	SC	R2
1.772	2.677	0.315	TC	R2
1.772	2.677	0.354	TC	R2
1.772	2.677	0.394	SC	R2
1.772	2.677	0.394	TC	R2
1.772	2.677	0.433	TB2	G2
1.772	2.677	0.472	SB2	G2
1.772	2.677	0.472	TB2	G2

Shaft	Bore	Width	Lip Style	Material
1.772	2.677	0.472	TC	R2
1.772	2.677	0.591	TC	R2
1.772	2.689	0.276	TC	RPA
1.772	2.756	0.197	VC	R2
1.772	2.756	0.276	SC	R2
1.772	2.756	0.315	TC	R2
1.772	2.756	0.394	SC	R2
1.772	2.756	0.394	TC	R2
1.772	2.756	0.472	TC	R2
1.772	2.756	0.512	TA2	P2
1.772	2.756	0.591	DBR	GP
1.772	2.835	0.315	SC	R2
1.772	2.835	0.315	TC	R2
1.772	2.835	0.394	SC	R2
1.772	2.835	0.394	TB2	G2
1.772	2.835	0.394	TC	R2
1.772	2.835	0.433	DB2	G2
1.772	2.835	0.472	SC	R2
1.772	2.835	0.472	TB2	G2
1.772	2.835	0.472	TC	R2
1.772	2.843	0.295	KC	R2
1.772	2.894	0.472	TB2	G2
1.772	2.933	0.472	TC	RPA
1.772	2.953	0.276	TC	RV
1.772	2.953	0.315	SC	R2
1.772	2.953	0.315	TC	R2
1.772	2.953	0.394	SC	R2
1.772	2.953	0.394	TC	R2
1.772	2.953	0.472	TB2	G2
1.772	2.953	0.472	TC	R2
1.772	3.071	0.472	TB2	G2
1.772	3.071	0.472	TC	R2
1.772	3.150	0.276	TC	RV
1.772	3.150	0.315	TC	R2
1.772	3.150	0.394	SC	R2
1.772	3.150	0.394	TC	R2
1.772	3.150	0.472	TC	R2
1.772	3.150	0.512	SC	R2
1.772	3.228	0.472	TC	R2
1.772	3.346	0.315	SB2	G2
1.772	3.346	0.315	TC	R2
1.772	3.346	0.394	SC	R2
1.772	3.346	0.394	TC	R2
1.772	3.346	0.472	TC	R2
1.772	3.543	0.394	SC	R2
1.772	3.543	0.394	TC	R2
1.772	3.661	0.236	SC	R2
1.772	3.937	0.394	SC	R2
1.772	3.937	0.394	TC	R2
1.781	2.125	0.252	VB	G2
1.781	2.251	0.374	TC	RPA
1.781	2.502	0.311	SA2	P2
1.781	2.686	0.374	SB2	P2
1.781	2.750	0.311	SB2	C2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.793	2.228	0.252	VB	C2
1.794	1.920	0.118	VB	C2
1.803	2.965	0.252	VBR	C2
1.811	1.937	0.126	VB	C2
1.811	2.126	0.354	TC	R2
1.811	2.165	0.217	SB	G2
1.811	2.165	0.413	VB	G2
1.811	2.283	0.197	VB	C2
1.811	2.283	0.276	TC	R2
1.811	2.323	0.354	KB	G2
1.811	2.327	0.472	KC	R2
1.811	2.327	0.472	TB	G2
1.811	2.327	0.472	TC	R2
1.811	2.362	0.276	TC	R2
1.811	2.362	0.394	TC	R2
1.811	2.441	0.276	KB2	G2
1.811	2.441	0.276	TB	G2
1.811	2.441	0.315	TC	R2
1.811	2.559	0.354	TC	R2
1.811	2.559	0.394	SC	R2
1.811	2.579	0.276	TC	R2
1.811	2.677	0.315	TC	R2
1.811	2.756	0.315	TC	R2
1.811	2.835	0.394	SC	R2
1.813	2.327	0.437	VB2	P2
1.813	2.623	0.374	TB2	P2
1.813	2.623	0.500	SB2	P2
1.813	2.750	0.374	TB2	P2
1.813	2.750	0.500	SA2	G2
1.813	2.875	0.374	TB2	P2
1.813	3.000	0.374	SC	R2
1.813	3.000	0.374	TB2	C2
1.821	2.623	0.252	VB	G2
1.831	2.362	0.354	SC	R2
1.837	2.671	0.374	TB2	PPA
1.843	2.750	0.374	TB2	P2
1.843	2.750	0.500	TB2	PPA
1.844	2.376	0.374	SB	G2
1.844	2.623	0.374	TB2	P2
1.850	2.205	0.276	SC	R2
1.850	2.205	0.276	TB	G2
1.850	2.244	0.276	TC	R2
1.850	2.283	0.197	TC	R2
1.850	2.362	0.276	TC	R2
1.850	2.362	0.472	TC	R2
1.850	2.409	0.217	SC	R2
1.850	2.409	0.217	TC	R2
1.850	2.441	0.236	TC	R2
1.850	2.441	0.276	TC	R2
1.850	2.441	0.315	SC	R2
1.850	2.441	0.315	TC	R2
1.850	2.441	0.354	SB2	G2
1.850	2.559	0.315	SC	R2
1.850	2.559	0.315	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.850	2.559	0.394	TC	R2
1.850	2.559	0.472	TA2	G2
1.850	2.677	0.394	TC	R2
1.850	2.756	0.394	TC	R2
1.850	3.307	0.394	TC	R2
1.850	3.465	0.472	TC	R2
1.859	2.500	0.252	TC	R2
1.870	2.323	0.472	KC	R2
1.870	2.781	0.354	TC	R2
1.870	3.744	0.437	SA2	GPA
1.872	2.057	0.126	VBR	C2
1.873	2.060	0.187	VB	C2
1.875	2.125	0.126	VC	R2
1.875	2.250	0.189	SB	G2
1.875	2.250	0.189	WPB	G4
1.875	2.315	0.205	TBR	C2
1.875	2.375	0.252	SC	R2
1.875	2.394	0.252	SC	R2
1.875	2.398	0.252	TC	R2
1.875	2.400	0.240	VA2	G2
1.875	2.402	0.252	SB2	P2
1.875	2.402	0.276	VC	R2
1.875	2.437	0.311	SC	R2
1.875	2.471	0.311	TC	R2
1.875	2.471	0.437	TB2	C2
1.875	2.500	0.252	WPB	G4
1.875	2.500	0.311	SB2	PPA
1.875	2.500	0.374	SC	R2
1.875	2.500	0.437	SA2	CPA
1.875	2.500	0.437	SB2	P2
1.875	2.502	0.311	TB2	P2
1.875	2.502	0.315	SC	R2
1.875	2.502	0.374	SB2	PPA
1.875	2.535	0.283	SB	CV
1.875	2.553	0.283	SBR	C2
1.875	2.563	0.311	SC	R2
1.875	2.563	0.374	TB2	P2
1.875	2.623	0.311	TB2	P2
1.875	2.623	0.311	TC	R2
1.875	2.623	0.374	SB2	PS
1.875	2.623	0.500	TA2	P2
1.875	2.625	0.374	TC	R2
1.875	2.625	0.437	TC	RS
1.875	2.625	0.450	SB	GPA
1.875	2.686	0.374	TB2	G2
1.875	2.687	0.311	SB2	P2
1.875	2.721	0.268	VB	G2
1.875	2.750	0.311	TB2	G2
1.875	2.750	0.311	TB2	C2
1.875	2.750	0.311	TC	R2
1.875	2.750	0.374	SC	R2
1.875	2.750	0.488	DBR	C2
1.875	2.758	0.469	DB	PPA
1.875	2.782	0.252	VBR	C2

Shaft	Bore	Width	Lip Style	Material
1.875	2.782	0.500	TA2	P2
1.875	2.835	0.374	TB2	P2
1.875	2.835	0.469	TB2	C2
1.875	2.875	0.311	TB2	G2
1.875	2.875	0.374	SC	R2
1.875	2.875	0.374	TC	R2
1.875	2.875	0.469	SA2	P2
1.875	2.965	0.232	VB	C2
1.875	2.996	0.500	SA2	P2
1.875	3.000	0.311	TB2	G2
1.875	3.000	0.374	SB2	PS
1.875	3.000	0.374	TB2	P2
1.875	3.000	0.500	SC	R2
1.875	3.000	0.500	TC	R2
1.875	3.061	0.313	TB2	P2
1.875	3.125	0.500	TB2	G2
1.875	3.125	0.500	TC	R2
1.875	3.251	0.500	SA2	P2
1.875	3.543	0.315	TC	R2
1.880	2.398	0.252	SBR	C2
1.890	2.283	0.157	TC	R2
1.890	2.283	0.157	VC	R2
1.890	2.283	0.276	TC	R2
1.890	2.283	0.394	TB	G2
1.890	2.323	0.236	TC	R2
1.890	2.362	0.276	TC	R2
1.890	2.362	0.315	TB	G2
1.890	2.362	0.315	TC	R2
1.890	2.362	0.394	TB	G2
1.890	2.362	0.394	TC	R2
1.890	2.441	0.236	KC	R2
1.890	2.441	0.276	TA2	G2
1.890	2.441	0.276	TB2	G2
1.890	2.441	0.276	TC	R2
1.890	2.441	0.315	SB2	G2
1.890	2.441	0.315	SC	RS
1.890	2.441	0.315	SC	R2
1.890	2.441	0.315	TA2	G2
1.890	2.441	0.315	TB2	G2
1.890	2.441	0.315	TC	R2
1.890	2.441	0.354	SB	G2
1.890	2.441	0.354	TB2	G2
1.890	2.441	0.354	TC	R2
1.890	2.441	0.394	TC	R2
1.890	2.441	0.472	TC	R2
1.890	2.480	0.354	TB2	G2
1.890	2.500	0.394	TB2	P2
1.890	2.500	0.394	TC	R3
1.890	2.520	0.276	SC	R2
1.890	2.520	0.472	TB2	CH
1.890	2.559	0.276	SC	R2
1.890	2.559	0.276	TC	R2
1.890	2.559	0.315	TBR	C2
1.890	2.559	0.315	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.890	2.559	0.354	TB	G2
1.890	2.559	0.354	TB2	G2
1.890	2.559	0.354	TC	R2
1.890	2.559	0.394	SC	R2
1.890	2.559	0.394	TC	R2
1.890	2.559	0.472	TA2	G2
1.890	2.559	0.472	TC	R2
1.890	2.638	0.433	TC	R2
1.890	2.677	0.315	TC	R2
1.890	2.677	0.394	SC	R2
1.890	2.677	0.394	TC	R2
1.890	2.677	0.472	TC	R2
1.890	2.677	0.551	TC	R2
1.890	2.717	0.394	TB2	G2
1.890	2.756	0.276	TC	R2
1.890	2.756	0.354	TC	R2
1.890	2.756	0.374	TB2	G2
1.890	2.756	0.394	TC	R2
1.890	2.756	0.472	SB2	GPA
1.890	2.756	0.472	TB2	G2
1.890	2.756	0.472	TC	R2
1.890	2.756	0.512	TB2	P2
1.890	2.776	0.394	TC	R2
1.890	2.835	0.276	SC	R2
1.890	2.835	0.276	TB2	P2
1.890	2.835	0.276	TC	R2
1.890	2.835	0.315	SC	R2
1.890	2.835	0.315	TC	R2
1.890	2.835	0.354	TC	R2
1.890	2.835	0.394	DC	RP
1.890	2.835	0.394	SC	R2
1.890	2.835	0.394	SC	R2
1.890	2.835	0.394	TC	R2
1.890	2.835	0.433	DC	RP
1.890	2.835	0.472	TC	R2
1.890	2.835	0.591	DC	R2
1.890	2.854	0.394	TC	R2
1.890	2.874	0.276	TB2	G2
1.890	2.874	0.315	TC	R2
1.890	2.913	0.394	TC	R2
1.890	2.913	0.433	TB2	G2
1.890	2.913	0.472	TC	R2
1.890	2.953	0.394	TC	R2
1.890	2.953	0.472	TC	R2
1.890	2.992	0.394	TC	R2
1.890	2.992	0.472	TC	R2
1.890	3.150	0.394	SC	R2
1.890	3.150	0.394	TC	R2
1.890	3.228	0.315	SB2	G2
1.890	3.228	0.394	TC	R2
1.890	3.346	0.394	SC	R2
1.890	3.346	0.394	TC	R2
1.890	3.543	0.315	SB2	G2
1.890	3.543	0.512	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.890	3.740	0.315	TC	RH
1.893	2.434	0.252	SBR	G2
1.900	2.479	0.350	TB2	P2
1.906	2.500	0.374	TC	R2
1.906	3.000	0.500	SB2	G2
1.906	3.000	0.500	SC	R2
1.921	2.046	0.126	VB	C2
1.929	2.205	0.354	KB	G2
1.929	2.362	0.276	TC	R2
1.929	2.441	0.236	TC	R2
1.929	2.520	0.315	TC	R2
1.929	2.559	0.354	SC	RPA
1.929	2.559	0.394	TC	R2
1.929	2.677	0.394	TC	RPA
1.929	2.835	0.339	TBR	GV
1.929	2.992	0.591	TC	R2
1.929	3.228	0.472	TC	RS
1.929	3.622	0.394	TC	R2
1.933	2.687	0.500	SB	G2
1.937	2.250	0.500	TB	G2
1.937	2.437	0.252	SB2	G2
1.937	2.437	0.252	TB2	P2
1.937	2.470	0.315	TB	GV
1.937	2.500	0.374	SA2	P2
1.937	2.500	0.374	SC	R2
1.937	2.500	0.374	TC	R2
1.937	2.502	0.374	SB	P2
1.937	2.502	0.374	TB2	P2
1.937	2.502	0.374	TC	R2
1.937	2.563	0.327	TC	R2
1.937	2.623	0.311	TB2	G2
1.937	2.623	0.311	TC	R2
1.937	2.686	0.303	SB2	PPA
1.937	2.686	0.311	TB2	GV
1.937	2.687	0.500	SBR	CS
1.937	2.750	0.311	SB2	PV
1.937	2.750	0.311	TB2	G2
1.937	2.750	0.374	DC	R2
1.937	2.750	0.374	SC	R2
1.937	2.750	0.374	TB2	C2
1.937	2.750	0.374	TC	R2
1.937	2.813	0.374	TC	R2
1.937	2.875	0.311	SA2	G2
1.937	2.884	0.311	TB2	PPA
1.937	3.000	0.311	TB2	C2
1.937	3.000	0.311	TB2	P2
1.937	3.000	0.500	SBR	C2
1.937	3.061	0.374	TB2	C2
1.937	3.063	0.500	TBR	CPA
1.937	3.187	0.437	TC	R2
1.937	3.750	0.500	SA2	P2
1.938	2.502	0.280	VA2	G2
1.938	2.563	0.311	SB2	P2
1.938	2.687	0.500	SA2	P2

Shaft	Bore	Width	Lip Style	Material
1.938	2.688	0.374	SB2	GS
1.938	2.748	0.311	TC	R2
1.938	2.997	0.500	SA2	P2
1.938	3.062	0.311	SB2	P2
1.938	3.125	0.500	SB2	P2
1.938	3.189	0.433	SA2	P2
1.969	2.165	0.157	VB	C2
1.969	2.283	0.157	KB	G2
1.969	2.283	0.157	TC	R2
1.969	2.283	0.157	VB	G2
1.969	2.323	0.157	KC	R2
1.969	2.362	0.157	TC	R2
1.969	2.362	0.197	VB2	G2
1.969	2.362	0.236	KC	R2
1.969	2.362	0.276	TC	R2
1.969	2.362	0.315	SC	R2
1.969	2.362	0.315	TC	R2
1.969	2.362	0.394	TC	R2
1.969	2.362	0.472	TC	R2
1.969	2.382	0.197	TC	R2
1.969	2.441	0.197	WPC	R4
1.969	2.441	0.276	SB	G2
1.969	2.441	0.276	SC	R2
1.969	2.441	0.276	TC	R2
1.969	2.441	0.315	SC	R2
1.969	2.441	0.315	TB	G2
1.969	2.441	0.354	TB	G2
1.969	2.441	0.354	TC	R2
1.969	2.441	0.394	TB	G2
1.969	2.441	0.394	TC	R2
1.969	2.441	0.472	TC	R2
1.969	2.480	0.236	TB	G2
1.969	2.480	0.315	TB	G2
1.969	2.480	0.315	TC	R2
1.969	2.520	0.256	TC	R2
1.969	2.520	0.315	TC	R2
1.969	2.520	0.354	TC	R2
1.969	2.520	0.394	TC	R2
1.969	2.559	0.315	DC	RV
1.969	2.559	0.315	KC	R2
1.969	2.559	0.315	SB	G2
1.969	2.559	0.315	SC	RV
1.969	2.559	0.315	SC	RPA
1.969	2.559	0.315	SC	R2
1.969	2.559	0.315	SC	R2
1.969	2.559	0.315	TA2	P3
1.969	2.559	0.315	TB	G2
1.969	2.559	0.315	TC	R2
1.969	2.559	0.315	TC	R2
1.969	2.559	0.354	TB	G2
1.969	2.559	0.354	TC	R2
1.969	2.559	0.394	SA2	G2
1.969	2.559	0.394	SC	R2
1.969	2.559	0.394	TB	G2

Shaft	Bore	Width	Lip Style	Material
1.969	2.559	0.394	TC	R2
1.969	2.559	0.472	TC	R2
1.969	2.598	0.236	TC	R2
1.969	2.598	0.315	SC	R2
1.969	2.618	0.374	TB2	P2
1.969	2.623	0.311	TB2	P2
1.969	2.638	0.354	TB	G2
1.969	2.638	0.354	TC	R2
1.969	2.638	0.394	TC	R2
1.969	2.638	0.433	TC	R2
1.969	2.677	0.276	TB2	G2
1.969	2.677	0.276	TC	R2
1.969	2.677	0.276	VC	R2
1.969	2.677	0.315	DC	R2
1.969	2.677	0.315	SC	R2
1.969	2.677	0.315	TA2	G2
1.969	2.677	0.315	TC	R2
1.969	2.677	0.354	TA2	G2
1.969	2.677	0.354	TB2	G2
1.969	2.677	0.354	TC	R2
1.969	2.677	0.394	SC	R2
1.969	2.677	0.394	TC	R2
1.969	2.677	0.472	TC	R2
1.969	2.717	0.394	TB2	C2
1.969	2.756	0.276	TA2	G2
1.969	2.756	0.276	TB2	G2
1.969	2.756	0.276	TC	R2
1.969	2.756	0.315	SA2	G2
1.969	2.756	0.315	SC	RV
1.969	2.756	0.315	SC	R2
1.969	2.756	0.315	TC	R2
1.969	2.756	0.354	TB2	G2
1.969	2.756	0.354	TBR	G2
1.969	2.756	0.354	TC	R2
1.969	2.756	0.394	SC	R2
1.969	2.756	0.394	TB2	G2
1.969	2.756	0.394	TC	R2
1.969	2.756	0.472	SC	R2
1.969	2.756	0.472	TB2	G2
1.969	2.756	0.472	TC	R2
1.969	2.756	0.512	TB	G3
1.969	2.756	0.512	TC	R2
1.969	2.756	0.531	TB	G2
1.969	2.835	0.197	VC	R2
1.969	2.835	0.276	TC	R2
1.969	2.835	0.315	SC	R2
1.969	2.835	0.315	TA2	P2
1.969	2.835	0.315	TB2	C2
1.969	2.835	0.315	TC	R2
1.969	2.835	0.354	SB2	GPA
1.969	2.835	0.354	TC	R2
1.969	2.835	0.394	SC	R2
1.969	2.835	0.394	TB2	G2
1.969	2.835	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
1.969	2.835	0.472	DC	RP
1.969	2.835	0.472	SB2	G2
1.969	2.835	0.472	SC	R2
1.969	2.835	0.472	TB2	G2
1.969	2.835	0.472	TC	R2
1.969	2.835	0.551	TC	R2
1.969	2.874	0.354	TA2	G2
1.969	2.874	0.354	TC	R2
1.969	2.875	0.469	SA2	C2
1.969	2.953	0.315	TC	R2
1.969	2.953	0.354	TA2	G2
1.969	2.953	0.354	TB	G2
1.969	2.953	0.394	SC	R2
1.969	2.953	0.394	TC	R2
1.969	2.953	0.472	TC	R2
1.969	2.992	0.394	TC	R2
1.969	2.992	0.472	TC	R2
1.969	2.992	0.512	TA2	P2
1.969	3.071	0.315	TC	R2
1.969	3.071	0.472	TC	R2
1.969	3.150	0.315	SB2	G2
1.969	3.150	0.315	SC	R2
1.969	3.150	0.315	TC	R2
1.969	3.150	0.394	SB2	G2
1.969	3.150	0.394	SC	R2
1.969	3.150	0.394	TB2	G2
1.969	3.150	0.394	TC	R2
1.969	3.150	0.472	TC	R2
1.969	3.150	0.512	SA2	G2
1.969	3.150	0.512	TB2	G2
1.969	3.150	0.512	TC	R2
1.969	3.189	0.472	TC	R2
1.969	3.189	0.512	TB2	G2
1.969	3.228	0.472	TC	R2
1.969	3.346	0.315	TC	R2
1.969	3.346	0.394	SC	R2
1.969	3.346	0.394	TC	R2
1.969	3.346	0.472	TC	R2
1.969	3.425	0.512	TC	R2
1.969	3.543	0.315	TC	R2
1.969	3.543	0.394	SC	R2
1.969	3.543	0.394	TB2	G2
1.969	3.543	0.394	TC	RV
1.969	3.543	0.394	TC	R2
1.969	3.543	0.472	TC	R2
1.969	3.543	0.512	TA2	G2
1.969	3.543	0.512	TC	R2
1.969	3.622	0.394	TC	R2
1.969	3.858	0.236	SC	R2
1.969	3.937	0.394	TC	R2
1.969	3.937	0.512	TC	R3
1.969	4.134	0.394	TC	R2
1.969	4.331	0.394	SC	R2
1.969	4.331	0.394	TC	RV



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
1.969	4.921	0.394	TC	R2
1.969	5.118	0.591	TC	R2
1.983	2.686	0.311	SB2	P2
1.988	2.303	0.177	VB	G2
1.988	2.441	0.354	TC	R2
1.991	4.387	0.189	VC	R2
1.996	3.345	0.374	TBR	G2
1.999	2.125	0.126	VB	C2
2.000	2.371	0.252	TB	P2
2.000	2.375	0.189	VB	G2
2.000	2.375	0.189	WPB	G4
2.000	2.375	0.252	SC	R2
2.000	2.375	0.252	TB	P2
2.000	2.478	0.563	TBR	P2
2.000	2.478	0.563	TBR	P2
2.000	2.500	0.252	SB2	P2
2.000	2.500	0.252	SC	R2
2.000	2.500	0.252	WPB	G4
2.000	2.500	0.311	TC	R2
2.000	2.500	0.469	SA2	PS
2.000	2.500	0.500	SA2	C2
2.000	2.502	0.252	TB2	P2
2.000	2.502	0.311	SB2	PPA
2.000	2.562	0.500	VB	G2
2.000	2.563	0.228	VB2	C2
2.000	2.563	0.528	SBR	GPA
2.000	2.569	0.374	KB2	G2
2.000	2.623	0.252	WPB	G4
2.000	2.623	0.311	SA2	P2
2.000	2.623	0.311	SB2	P2
2.000	2.623	0.311	TB2	P2
2.000	2.623	0.311	TC	R2
2.000	2.625	0.252	KB2	G2
2.000	2.625	0.252	VB2	C2
2.000	2.625	0.252	WPB	G4
2.000	2.625	0.252	WPB	G4
2.000	2.625	0.311	TB2	C2
2.000	2.686	0.252	WPB	G4
2.000	2.686	0.374	TB2	P2
2.000	2.686	0.437	TB2	P2
2.000	2.686	0.500	SA2	C2
2.000	2.686	0.500	TA2	G2
2.000	2.686	0.500	TB2	P2
2.000	2.687	0.307	SB2	PS
2.000	2.700	0.260	VC	R2
2.000	2.717	0.563	TC	R2
2.000	2.750	0.311	TB2	P2
2.000	2.750	0.311	TC	R2
2.000	2.750	0.374	DC	R2
2.000	2.750	0.374	SBR	CS
2.000	2.750	0.374	SC	RV
2.000	2.750	0.374	SC	R2
2.000	2.750	0.500	SA2	G2
2.000	2.750	0.500	SC	R2

Shaft	Bore	Width	Lip Style	Material
2.000	2.750	0.500	TC	R2
2.000	2.752	0.189	VB2	P2
2.000	2.833	0.469	SA2	P2
2.000	2.875	0.311	TB2	P2
2.000	2.875	0.374	SC	R2
2.000	2.875	0.469	SA2	G2
2.000	2.875	0.469	TA2	P2
2.000	2.875	0.500	SC	R2
2.000	2.880	0.374	TB2	P2
2.000	2.890	0.563	TB2	P2
2.000	2.906	0.311	SC	R2
2.000	2.996	0.500	TA2	PPA
2.000	2.997	0.374	SA2	P2
2.000	2.997	0.374	TC	R2
2.000	2.997	0.437	TB2	P2
2.000	3.000	0.311	TB2	P2
2.000	3.000	0.311	TC	R2
2.000	3.000	0.374	TC	R2
2.000	3.000	0.500	SC	R2
2.000	3.000	0.500	TB2	C2
2.000	3.000	0.500	TC	R2
2.000	3.061	0.374	TB2	P2
2.000	3.125	0.374	SC	R2
2.000	3.148	0.252	VBR	C2
2.000	3.150	0.374	SB2	P2
2.000	3.189	0.374	TB2	P2
2.000	3.250	0.374	SC	R2
2.000	3.260	0.625	VC	R2
2.000	3.265	0.441	TB2	P2
2.000	3.375	0.437	TC	R2
2.000	3.500	0.500	SC	R2
2.000	3.543	0.437	SA2	C2
2.000	3.750	0.441	TB2	P2
2.000	4.000	0.437	TB2	C2
2.000	4.003	0.437	SA2	P2
2.008	2.441	0.276	SB	G2
2.008	2.441	0.276	SC	R2
2.008	2.480	0.236	KB	G2
2.008	2.480	0.236	KBR	G2
2.008	2.480	0.315	TB2	C2
2.008	2.480	0.335	KBR	C2
2.008	2.559	0.276	TBR	G2
2.008	2.559	0.512	TC	R2
2.008	2.598	0.256	SC	RPA
2.008	2.618	0.394	TC	R2
2.008	2.835	0.394	TB2	G2
2.010	2.650	0.362	KB2	C2
2.031	2.650	0.185	SC	R2
2.031	2.888	0.563	TC	R2
2.046	2.171	0.126	VB	C2
2.047	2.362	0.276	TC	R2
2.047	2.441	0.276	TC	R2
2.047	2.441	0.315	SC	R2
2.047	2.441	0.315	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.047	2.441	0.354	TB2	G2
2.047	2.441	0.354	TC	R2
2.047	2.441	0.394	TC	R2
2.047	2.480	0.236	TC	R2
2.047	2.480	0.315	TB2	C2
2.047	2.480	0.315	TC	R2
2.047	2.480	0.354	TBR	G2
2.047	2.520	0.354	TBR	G2
2.047	2.520	0.354	TC	R2
2.047	2.559	0.315	SC	R2
2.047	2.559	0.315	TC	R2
2.047	2.559	0.354	TB	G2
2.047	2.559	0.354	TC	R2
2.047	2.559	0.394	TC	R2
2.047	2.598	0.236	SC	RPA
2.047	2.598	0.354	SC	RPA
2.047	2.677	0.236	VB2	C2
2.047	2.677	0.276	TC	R2
2.047	2.677	0.315	SC	R2
2.047	2.677	0.315	TB2	G2
2.047	2.677	0.315	TC	R2
2.047	2.677	0.394	SC	R2
2.047	2.677	0.394	TC	R2
2.047	2.677	0.531	TB2	C2
2.047	2.717	0.394	SC	R2
2.047	2.756	0.354	SB2	G2
2.047	2.756	0.354	TB2	G2
2.047	2.756	0.354	TBR	C2
2.047	2.756	0.354	TC	R2
2.047	2.756	0.394	TB2	G2
2.047	2.756	0.394	TBR	G2
2.047	2.756	0.394	TC	R2
2.047	2.756	0.512	TC	R2
2.047	2.795	0.315	TC	R2
2.047	2.835	0.276	TB2	G2
2.047	2.835	0.315	SC	R2
2.047	2.835	0.315	TB2	G2
2.047	2.835	0.315	TC	R2
2.047	2.835	0.354	TC	R2
2.047	2.835	0.394	TB2	G2
2.047	2.835	0.394	TC	R2
2.047	2.835	0.472	SA2	G2
2.047	2.835	0.472	TB2	G2
2.047	2.835	0.472	TC	R2
2.047	2.874	0.394	TB2	G2
2.047	2.874	0.394	TC	R2
2.047	2.874	0.394	TC	R2
2.047	2.953	0.315	SC	R2
2.047	2.953	0.315	TC	R2
2.047	2.953	0.394	TC	R2
2.047	2.953	0.472	DC	R2
2.047	2.953	0.472	SB2	G2
2.047	2.953	0.472	SC	R2
2.047	2.953	0.472	TB2	G2
2.047	2.953	0.472	TC	R2
2.047	2.992	0.354	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.047	3.071	0.354	SC	RPA
2.047	3.071	0.394	TC	R2
2.047	3.150	0.315	SC	R2
2.047	3.150	0.315	TC	R2
2.047	3.150	0.394	SC	R2
2.047	3.150	0.394	TC	R2
2.047	3.150	0.472	TC	R2
2.047	3.150	0.512	TC	R2
2.047	3.228	0.315	TB2	G2
2.047	3.346	0.354	TC	R2
2.047	3.346	0.394	SC	R2
2.047	3.346	0.394	TC	R2
2.047	3.346	0.512	SC	R2
2.047	3.346	0.512	TC	R2
2.047	3.543	0.315	KC	R2
2.047	3.543	0.394	TC	R2
2.063	2.750	0.500	SA2	G2
2.063	2.842	0.449	SA2	P2
2.063	3.000	0.311	SB2	G2
2.063	3.000	0.311	VB2	C2
2.063	3.000	0.374	SC	R2
2.063	3.000	0.374	TB2	P2
2.063	3.187	0.453	SC	R2
2.063	3.189	0.437	SA2	P2
2.063	3.251	0.500	SA2	P2
2.063	3.251	0.500	SA2	P2
2.063	3.371	0.469	SA2	P2
2.087	2.559	0.512	TB	G2
2.087	2.606	0.276	KC	R2
2.087	2.638	0.354	TC	R2
2.087	2.677	0.394	TC	R2
2.087	2.685	0.276	KC	R2
2.087	2.685	0.276	TC	R2
2.087	2.795	0.354	SC	R2
2.087	2.835	0.394	TC	R2
2.087	2.874	0.394	TC	R2
2.087	2.953	0.472	SA2	G2
2.087	3.150	0.512	TC	R2
2.087	3.346	0.315	SC	R2
2.106	3.114	0.157	VBR	C2
2.106	3.114	0.276	SBR	C2
2.106	3.543	0.236	SC	R2
2.106	3.543	0.236	VC	R2
2.125	2.500	0.189	WPB	G4
2.125	2.561	0.492	TB	P2
2.125	2.750	0.311	SC	R2
2.125	2.750	0.311	TB2	P2
2.125	2.750	0.311	TC	R2
2.125	2.750	0.374	TB2	P2
2.125	2.750	0.437	TB2	P2
2.125	2.750	0.500	TB2	P2
2.125	2.758	0.437	TB	P2
2.125	2.763	0.252	SB2	P2
2.125	2.815	0.283	SBR	C2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.125	2.871	0.358	TC	R2
2.125	2.875	0.252	VB	G2
2.125	2.875	0.374	SB2	G2
2.125	2.875	0.374	SBR	CS
2.125	2.875	0.374	SC	R2
2.125	2.875	0.374	TB2	P2
2.125	2.875	0.374	TC	R2
2.125	2.875	0.437	SA2	G2
2.125	2.875	0.437	SB2	G2
2.125	2.875	0.437	TA2	CPA
2.125	2.875	0.437	TB2	G2
2.125	2.891	0.252	VB2	C2
2.125	2.891	0.252	VC	R2
2.125	2.996	0.437	SA2	G2
2.125	2.997	0.500	TA2	P2
2.125	3.000	0.311	KB2	P2
2.125	3.000	0.374	SB	P2
2.125	3.000	0.374	SB2	PV
2.125	3.000	0.374	SC	R2
2.125	3.000	0.374	TB2	P2
2.125	3.000	0.374	TC	R2
2.125	3.000	0.437	TA2	P2
2.125	3.000	0.500	SB	G2
2.125	3.000	0.500	SC	R2
2.125	3.000	0.500	TC	R2
2.125	3.061	0.374	TB2	P2
2.125	3.061	0.500	SA2	P2
2.125	3.061	0.500	TA2	G2
2.125	3.061	0.500	TB2	PPA
2.125	3.063	0.500	SB2	G2
2.125	3.063	0.500	TA2	P2
2.125	3.063	0.500	TC	R2
2.125	3.125	0.311	SBR	CS
2.125	3.125	0.311	TC	R2
2.125	3.125	0.374	SC	R2
2.125	3.125	0.374	TA2	PPA
2.125	3.125	0.469	TA2	P2
2.125	3.125	0.469	TC	R2
2.125	3.125	0.500	SA2	C2
2.125	3.146	0.500	VBR	C2
2.125	3.149	0.374	TB2	C2
2.125	3.187	0.374	SC	R2
2.125	3.189	0.437	SA2	P2
2.125	3.189	0.469	TB2	G2
2.125	3.350	0.437	SA2	P2
2.125	3.371	0.311	VB2	P2
2.125	3.371	0.374	TA2	P2
2.125	3.371	0.374	TB2	C2
2.125	3.371	0.469	TA2	P2
2.125	3.372	0.437	TB2	G2
2.125	3.372	0.437	TC	R2
2.125	3.375	0.311	TB2	G2
2.125	3.375	0.375	TC	R2
2.125	3.543	0.500	TA2	P2

Shaft	Bore	Width	Lip Style	Material
2.125	3.623	0.469	TB2	PPA
2.125	3.625	0.374	TC	R2
2.125	4.000	0.500	TB2	G2
2.126	2.500	0.197	TB	G3
2.126	2.520	0.354	TBR	G2
2.126	2.520	0.354	TC	R2
2.126	2.559	0.315	SB2	P2
2.126	2.559	0.354	TC	R2
2.126	2.559	0.394	TC	R2
2.126	2.559	0.512	TB	G2
2.126	2.559	0.512	TBR	G2
2.126	2.559	0.512	TC	R2
2.126	2.598	0.276	TC	R2
2.126	2.677	0.354	TC	R2
2.126	2.677	0.394	TC	R2
2.126	2.756	0.354	TC	R2
2.126	2.756	0.374	TB2	P2
2.126	2.756	0.394	TC	R2
2.126	2.795	0.315	TC	R2
2.126	2.835	0.394	TC	R2
2.126	2.854	0.354	TB2	C2
2.126	2.854	0.354	TC	R2
2.126	2.874	0.315	TC	R2
2.126	2.874	0.394	TB2	G2
2.126	2.874	0.394	TC	R2
2.126	2.874	0.484	SC	RV
2.126	2.886	0.394	TB	G2
2.126	2.913	0.394	TC	R2
2.126	2.953	0.394	TC	R2
2.126	2.992	0.315	TC	R2
2.126	2.992	0.472	SC	R2
2.126	2.992	0.472	TC	R2
2.126	2.992	0.551	DC	R2
2.126	3.071	0.472	TC	R2
2.126	3.150	0.394	TC	R2
2.126	3.189	0.394	TB2	C2
2.126	3.189	0.394	TC	R2
2.126	3.189	0.433	SC	R2
2.126	3.228	0.433	TC	R2
2.126	3.346	0.315	SC	R2
2.126	3.346	0.315	TC	R2
2.126	3.346	0.394	TC	R2
2.126	3.543	0.315	TC	R2
2.126	3.622	0.512	SA2	PPA
2.146	2.756	0.315	TC	R2
2.156	2.750	0.217	KC	R2
2.156	2.875	0.374	SC	R2
2.165	2.480	0.197	SC	R2
2.165	2.559	0.315	TC	R2
2.165	2.559	0.394	TC	R2
2.165	2.638	0.197	TB	G2
2.165	2.677	0.236	TC	R2
2.165	2.677	0.236	VB2	G2
2.165	2.677	0.315	SC	R2

Shaft	Bore	Width	Lip Style	Material
2.165	2.677	0.315	TC	R2
2.165	2.677	0.394	TC	R2
2.165	2.677	0.472	DC	R2
2.165	2.677	0.472	TC	R2
2.165	2.756	0.315	SC	R2
2.165	2.756	0.315	TB2	C2
2.165	2.756	0.315	TC	R2
2.165	2.756	0.354	TB	G2
2.165	2.756	0.354	TC	R2
2.165	2.756	0.394	SC	R2
2.165	2.756	0.394	TC	R2
2.165	2.756	0.472	TC	R2
2.165	2.756	0.591	DC	R2
2.165	2.835	0.276	SC	R2
2.165	2.835	0.315	SC	R2
2.165	2.835	0.315	TC	R2
2.165	2.835	0.354	TB	G2
2.165	2.835	0.354	TC	R2
2.165	2.835	0.394	SC	R2
2.165	2.835	0.394	TB	G2
2.165	2.835	0.394	TC	R2
2.165	2.835	0.472	TB2	G2
2.165	2.835	0.472	TC	R2
2.165	2.874	0.236	TC	R2
2.165	2.874	0.394	TC	R2
2.165	2.880	0.394	TB	G2
2.165	2.953	0.276	SC	RV
2.165	2.953	0.315	TC	R2
2.165	2.953	0.354	TC	R2
2.165	2.953	0.394	SC	R2
2.165	2.953	0.394	TB2	G3
2.165	2.953	0.394	TC	R2
2.165	2.953	0.472	TC	R2
2.165	2.992	0.394	TC	R3
2.165	2.992	0.472	SB2	G2
2.165	2.992	0.472	TC	R2
2.165	3.031	0.315	TC	R2
2.165	3.031	0.354	TB2	G2
2.165	3.071	0.276	TC	R2
2.165	3.071	0.354	TC	R2
2.165	3.071	0.472	DC	RV
2.165	3.071	0.472	SA2	P3
2.165	3.071	0.472	SB2	G2
2.165	3.071	0.472	SC	R2
2.165	3.071	0.472	TB2	G2
2.165	3.071	0.472	TC	R2
2.165	3.071	0.709	DB	GP
2.165	3.075	0.256	TC	R2
2.165	3.150	0.315	SC	R2
2.165	3.150	0.315	TB2	GV
2.165	3.150	0.315	TC	R2
2.165	3.150	0.394	DC	R2
2.165	3.150	0.394	SB2	C2
2.165	3.150	0.394	SC	R2

Shaft	Bore	Width	Lip Style	Material
2.165	3.150	0.394	TA2	G2
2.165	3.150	0.394	TB2	CPA
2.165	3.150	0.394	TC	R2
2.165	3.150	0.472	SA2	C2
2.165	3.150	0.472	SC	R2
2.165	3.150	0.472	TC	R2
2.165	3.150	0.512	SC	R2
2.165	3.150	0.748	DBR	C2
2.165	3.228	0.354	TC	R2
2.165	3.228	0.394	TB2	G2
2.165	3.228	0.394	TC	R3
2.165	3.228	0.394	VB2	G2
2.165	3.228	0.472	TC	R2
2.165	3.250	0.374	TC	R2
2.165	3.346	0.315	SC	R2
2.165	3.346	0.315	TC	R2
2.165	3.346	0.394	SC	R2
2.165	3.346	0.394	TC	R2
2.165	3.346	0.472	TC	R2
2.165	3.346	0.512	SC	R2
2.165	3.346	0.551	TC	R2
2.165	3.378	0.512	SC	R2
2.165	3.465	0.394	TC	R2
2.165	3.543	0.315	TC	R2
2.165	3.543	0.394	DC	R2
2.165	3.543	0.394	SB2	G2
2.165	3.543	0.394	SC	R2
2.165	3.543	0.394	TC	R2
2.165	3.543	0.472	SC	R2
2.165	3.543	0.512	TC	R2
2.165	3.622	0.354	SC	R2
2.165	3.622	0.354	TC	R2
2.165	3.740	0.394	TC	R3
2.165	3.937	0.315	SB2	G2
2.165	3.937	0.315	TC	R2
2.165	3.937	0.394	TC	R2
2.165	3.937	0.472	SC	R2
2.165	3.937	0.472	TC	R2
2.165	3.937	0.492	SC	R2
2.165	4.724	0.472	TC	R2
2.180	3.000	0.250	KB	G2
2.180	3.000	0.496	TB2	C2
2.187	2.750	0.374	TC	R2
2.187	2.808	0.354	SB2	CPA
2.187	2.874	0.315	DC	RV
2.187	2.875	0.374	TA2	PPA
2.187	2.875	0.500	SC	R2
2.187	2.996	0.437	TA2	C2
2.187	3.000	0.374	TB2	P2
2.187	3.000	0.374	TC	R2
2.187	3.000	0.500	TC	R2
2.187	3.063	0.374	TB2	P2
2.187	3.091	0.453	SC	R2
2.187	3.187	0.437	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.187	3.313	0.374	TB2	PV
2.187	3.375	0.500	SC	R2
2.187	3.623	0.469	TB2	PPA
2.205	2.677	0.236	TC	R2
2.205	2.756	0.315	SC	R2
2.205	2.756	0.354	TC	R2
2.205	2.835	0.315	SC	R2
2.205	2.835	0.315	TC	R2
2.205	2.835	0.354	TC	R2
2.205	2.835	0.394	TC	R2
2.205	2.874	0.236	TB2	G2
2.205	2.874	0.394	TC	R2
2.205	2.880	0.394	TB2	G2
2.205	2.953	0.315	SB2	G2
2.205	2.953	0.315	TC	R2
2.205	2.992	0.315	TC	R2
2.205	3.150	0.315	SC	R2
2.205	3.150	0.394	TC	R2
2.205	3.150	0.512	TC	R2
2.205	3.189	0.315	TB2	G2
2.205	3.346	0.315	SC	R2
2.205	3.346	0.315	TC	R2
2.205	3.346	0.394	TC	R2
2.205	3.543	0.394	SC	R2
2.205	3.543	0.394	TC	R2
2.205	3.937	0.394	SC	R2
2.244	2.638	0.236	TBR	C2
2.244	2.638	0.236	TC	R2
2.244	2.835	0.331	TBR	C2
2.244	2.953	0.472	TC	R2
2.244	3.150	0.472	TC	R2
2.244	3.248	0.394	TC	R2
2.244	3.248	0.472	TB2	G3
2.244	3.307	0.315	TB2	G2
2.244	3.346	0.394	TC	R2
2.244	3.346	0.472	TC	R2
2.244	3.346	0.591	TC	R2
2.244	3.543	0.512	SC	R2
2.250	2.500	0.189	WPB	G4
2.250	2.625	0.189	VB2	C2
2.250	2.625	0.189	VC	R2
2.250	2.625	0.189	WPB	G4
2.250	2.625	0.252	WPB	G4
2.250	2.675	0.539	TA2	P2
2.250	2.750	0.252	TC	R2
2.250	2.750	0.252	WPB	G4
2.250	2.875	0.252	VBR	C4
2.250	2.875	0.252	WPB	G4
2.250	2.875	0.311	TB	G2
2.250	2.875	0.374	TC	R2
2.250	2.890	0.563	TB2	P2
2.250	2.996	0.437	SB2	P2
2.250	2.996	0.437	TB2	GPA
2.250	2.996	0.437	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.250	2.997	0.437	TA2	P2
2.250	3.000	0.374	DC	R2
2.250	3.000	0.374	SB	P2
2.250	3.000	0.374	SB2	CV
2.250	3.000	0.374	SC	R2
2.250	3.000	0.374	TB2	C2
2.250	3.000	0.374	TB2	GV
2.250	3.000	0.374	TC	R2
2.250	3.000	0.437	SA2	P2
2.250	3.000	0.437	TB	G2
2.250	3.000	0.500	SA2	P2
2.250	3.000	0.500	SC	R2
2.250	3.000	0.500	TA2	P2
2.250	3.000	0.500	TB2	G2
2.250	3.000	0.500	TC	R2
2.250	3.061	0.374	SB2	C2
2.250	3.061	0.437	TA2	P2
2.250	3.062	0.374	TB2	P2
2.250	3.063	0.374	TC	R2
2.250	3.063	0.437	TB2	G2
2.250	3.066	0.374	TC	R2
2.250	3.125	0.374	SC	R2
2.250	3.125	0.374	TA2	P2
2.250	3.125	0.374	TB2	PPA
2.250	3.185	0.437	TA2	P2
2.250	3.187	0.500	SC	R2
2.250	3.189	0.437	TB2	PPA
2.250	3.250	0.374	TB2	G2
2.250	3.250	0.500	SC	R2
2.250	3.250	0.750	TC	RPA
2.250	3.251	0.437	SA2	C2
2.250	3.251	0.500	SA2	P2
2.250	3.350	0.311	SA2	PPA
2.250	3.350	0.469	SB2	C2
2.250	3.371	0.374	TA2	P2
2.250	3.371	0.374	VB	P2
2.250	3.371	0.374	VB2	G2
2.250	3.371	0.437	TA2	C2
2.250	3.375	0.252	TC	R2
2.250	3.375	0.311	SC	R2
2.250	3.375	0.375	TC	R2
2.250	3.375	0.437	TB2	G2
2.250	3.375	0.441	SA2	P2
2.250	3.375	0.500	TC	R2
2.250	3.500	0.437	TA2	G2
2.250	3.500	0.500	TA2	G2
2.250	3.500	0.500	TB2	G2
2.250	3.500	0.500	TB2	P2
2.250	3.500	0.500	TC	R2
2.250	3.543	0.500	TA2	P2
2.250	3.623	0.469	TA2	P2
2.250	3.623	0.469	TB2	PPA
2.250	3.625	0.500	TC	R2
2.250	3.750	0.500	TB2	G2

Shaft	Bore	Width	Lip Style	Material
2.250	3.750	0.626	VB2	C2
2.250	3.751	0.500	TA2	P2
2.250	3.875	0.437	SA2	C2
2.252	3.622	0.709	TA2	G2
2.252	4.331	0.394	TC	R2
2.254	2.756	0.340	SB2	PV
2.281	3.250	0.500	TA2	G2
2.283	2.677	0.236	TB2	G2
2.283	2.677	0.354	TB	G2
2.283	2.677	0.354	TC	R2
2.283	2.756	0.276	TC	R2
2.283	2.756	0.354	TB	GPA
2.283	2.756	0.354	TC	R2
2.283	2.756	0.433	TC	R2
2.283	2.835	0.315	SC	R2
2.283	2.835	0.315	TC	R2
2.283	2.835	0.354	TC	R2
2.283	2.835	0.394	TC	R2
2.283	2.880	0.394	TB	G2
2.283	2.913	0.394	TC	R2
2.283	2.953	0.315	TC	R2
2.283	2.953	0.354	TB	G2
2.283	2.953	0.354	TBR	G2
2.283	2.953	0.354	TC	R2
2.283	2.953	0.394	TC	R2
2.283	2.953	0.433	TC	R2
2.283	2.953	0.472	TA2	G2
2.283	2.953	0.472	TC	R2
2.283	2.953	0.591	TB	G2
2.283	3.071	0.354	TC	R2
2.283	3.071	0.472	TC	R2
2.283	3.150	0.315	SC	R2
2.283	3.150	0.315	TC	R2
2.283	3.150	0.354	TC	R2
2.283	3.150	0.394	SC	R2
2.283	3.150	0.394	TC	R2
2.283	3.150	0.433	SC	R2
2.283	3.150	0.472	SB2	G2
2.283	3.150	0.472	TB2	G2
2.283	3.150	0.472	TC	R2
2.283	3.150	0.512	TC	R2
2.283	3.155	0.374	KB	P2
2.283	3.228	0.394	TC	R2
2.283	3.228	0.472	TC	R2
2.283	3.346	0.315	TB2	P2
2.283	3.346	0.315	TC	R2
2.283	3.346	0.394	TC	R2
2.283	3.346	0.472	SC	R2
2.283	3.346	0.472	TC	R2
2.283	3.386	0.472	TC	R3
2.283	3.543	0.394	SC	R2
2.283	3.543	0.394	TC	R2
2.283	3.543	0.433	SC	R2
2.283	3.543	0.512	TC	RV

Shaft	Bore	Width	Lip Style	Material
2.283	3.622	0.315	TC	R2
2.283	4.016	0.394	TB2	G2
2.283	4.016	0.472	TB2	G2
2.287	3.000	0.374	SC	R2
2.312	3.000	0.500	TA2	GV
2.313	3.000	0.252	VB2	P2
2.313	3.000	0.390	SB2	P2
2.313	3.125	0.374	TB2	P2
2.313	3.250	0.500	SA2	G2
2.313	3.313	0.374	TC	R2
2.313	3.350	0.311	SB2	G2
2.313	3.350	0.311	SC	R2
2.313	3.500	0.374	TA2	P2
2.313	3.500	0.500	SA2	C2
2.321	3.000	0.311	KB	C2
2.323	2.835	0.354	TB	G2
2.323	2.835	0.472	TB	G2
2.323	2.835	0.472	TC	R2
2.323	2.953	0.394	TB2	G2
2.328	2.878	0.311	TC	R2
2.328	2.997	0.311	KB2	P2
2.343	3.150	0.394	TC	RV
2.362	2.756	0.197	VB	G2
2.362	2.756	0.276	SC	R2
2.362	2.756	0.276	TB	G2
2.362	2.756	0.315	SC	R2
2.362	2.756	0.315	TC	R2
2.362	2.756	0.394	TC	R2
2.362	2.756	0.472	TC	R2
2.362	2.756	0.472	TC	R2
2.362	2.835	0.236	VC	R2
2.362	2.835	0.295	TB	G2
2.362	2.835	0.315	SB	C2
2.362	2.835	0.315	SC	R2
2.362	2.835	0.354	TC	R2
2.362	2.835	0.394	TC	R2
2.362	2.835	0.472	TC	R2
2.362	2.835	0.709	SB	G2
2.362	2.913	0.295	TB	G2
2.362	2.913	0.394	SC	R2
2.362	2.913	0.394	TA2	G2
2.362	2.913	0.394	TC	R2
2.362	2.953	0.157	VB	G2
2.362	2.953	0.236	VC	R2
2.362	2.953	0.315	SC	RV
2.362	2.953	0.315	SC	R2
2.362	2.953	0.315	TB	G2
2.362	2.953	0.315	TC	R2
2.362	2.953	0.354	SC	R2
2.362	2.953	0.354	TC	R2
2.362	2.953	0.394	TC	R2
2.362	2.953	0.472	TC	R2
2.362	2.984	0.157	VBR	C2
2.362	2.992	0.354	TC	R2
2.362	3.031	0.354	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.362	3.031	0.472	TB2	G2
2.362	3.031	0.472	TC	R2
2.362	3.063	0.315	DC	R2
2.362	3.071	0.252	DC	R2
2.362	3.071	0.276	VB2	G2
2.362	3.071	0.354	SC	R2
2.362	3.071	0.354	TB2	G2
2.362	3.071	0.354	TC	R2
2.362	3.071	0.394	TC	R2
2.362	3.130	0.394	TC	R2
2.362	3.150	0.197	VB2	C2
2.362	3.150	0.276	TC	R2
2.362	3.150	0.315	SC	R2
2.362	3.150	0.315	TB2	G2
2.362	3.150	0.315	TC	R2
2.362	3.150	0.354	TC	R2
2.362	3.150	0.394	DC	RV
2.362	3.150	0.394	SC	RV
2.362	3.150	0.394	SC	R2
2.362	3.150	0.394	TA2	G3
2.362	3.150	0.394	TB2	GV
2.362	3.150	0.394	TC	R2
2.362	3.150	0.472	SC	R2
2.362	3.150	0.472	TB2	G2
2.362	3.150	0.472	TC	R2
2.362	3.150	0.512	SC	R2
2.362	3.150	0.512	TC	R2
2.362	3.228	0.276	KC	R2
2.362	3.228	0.276	TC	R2
2.362	3.228	0.315	TC	R2
2.362	3.228	0.354	TB2	GPA
2.362	3.228	0.354	TC	R2
2.362	3.228	0.472	SB2	G2
2.362	3.228	0.472	SC	R2
2.362	3.228	0.472	TB2	G2
2.362	3.228	0.472	TC	R2
2.362	3.228	0.709	DB2	GP
2.362	3.307	0.394	TC	R2
2.362	3.346	0.236	TC	R2
2.362	3.346	0.276	TC	R2
2.362	3.346	0.315	SC	R2
2.362	3.346	0.315	TC	R2
2.362	3.346	0.394	SC	R2
2.362	3.346	0.394	TC	R2
2.362	3.346	0.472	SC	R2
2.362	3.346	0.472	TC	R2
2.362	3.346	0.512	SC	R2
2.362	3.346	0.512	TC	R2
2.362	3.346	0.630	TA2	G3
2.362	3.366	0.472	SA2	G2
2.362	3.366	0.472	TC	R2
2.362	3.366	0.630	TC	R2
2.362	3.386	0.248	DB2	C2
2.362	3.386	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.362	3.543	0.315	SC	R2
2.362	3.543	0.315	TC	R2
2.362	3.543	0.394	SB2	C2
2.362	3.543	0.394	SC	R2
2.362	3.543	0.394	TC	R2
2.362	3.543	0.433	TC	R2
2.362	3.543	0.472	TC	R2
2.362	3.543	0.512	TC	R2
2.362	3.622	0.472	TC	R2
2.362	3.740	0.315	TC	R2
2.362	3.740	0.394	SC	R2
2.362	3.740	0.394	TC	R2
2.362	3.740	0.433	TC	R2
2.362	3.740	0.472	TC	R2
2.362	3.740	0.512	TC	R2
2.362	3.937	0.394	SA2	C2
2.362	3.937	0.394	SC	R2
2.362	3.937	0.394	TC	R2
2.362	3.937	0.472	TC	R2
2.362	3.937	0.512	TC	R2
2.362	4.094	0.472	TC	R2
2.362	4.331	0.394	SC	R2
2.362	4.331	0.394	TC	R2
2.362	4.331	0.472	SC	R2
2.362	4.331	0.472	TC	R2
2.362	4.331	0.512	TA2	C2
2.362	4.724	0.512	TC	R2
2.362	5.118	0.394	TC	R2
2.375	2.844	0.295	KBR	C2
2.375	2.875	0.252	WPB	G4
2.375	2.875	0.311	SC	R2
2.375	3.000	0.311	SC	R2
2.375	3.000	0.374	SC	R2
2.375	3.063	0.374	TB2	P2
2.375	3.063	0.500	SB	PS
2.375	3.063	0.500	TC	R2
2.375	3.125	0.374	SB	P2
2.375	3.125	0.374	SC	R2
2.375	3.125	0.374	TA2	C2
2.375	3.125	0.374	TB2	P2
2.375	3.125	0.374	TC	R2
2.375	3.125	0.374	VB	G2
2.375	3.125	0.437	TA2	P2
2.375	3.125	0.500	SA2	P2
2.375	3.125	0.500	TA2	CPA
2.375	3.250	0.374	TB2	G2
2.375	3.250	0.437	TA2	PPA
2.375	3.250	0.469	TC	R2
2.375	3.250	0.500	SC	R2
2.375	3.251	0.374	TA2	P2
2.375	3.251	0.375	TC	R2
2.375	3.251	0.500	TB2	PPA
2.375	3.344	0.252	SB2	G2
2.375	3.344	0.500	SC	R2

Shaft	Bore	Width	Lip Style	Material
2.375	3.350	0.374	SB2	PS
2.375	3.350	0.374	TA2	P2
2.375	3.350	0.437	TA2	P2
2.375	3.350	0.469	TA2	CPA
2.375	3.350	0.673	TB2	P2
2.375	3.371	0.469	SA2	C2
2.375	3.375	0.500	SC	R2
2.375	3.375	0.500	TC	R2
2.375	3.480	0.689	TA2	G2
2.375	3.481	0.402	SA2	G2
2.375	3.481	0.437	TA2	P2
2.375	3.483	0.500	TA2	PPA
2.375	3.500	0.374	SC	R2
2.375	3.500	0.374	TA2	P2
2.375	3.500	0.374	TC	R2
2.375	3.500	0.500	TB2	P2
2.375	3.500	0.625	TC	RPA
2.375	3.543	0.311	TA2	G2
2.375	3.543	0.437	SA2	C2
2.375	3.543	0.500	TA2	PPA
2.375	3.601	0.437	TA2	P2
2.375	3.603	0.469	TA2	G2
2.375	3.623	0.437	SA2	G2
2.375	3.623	0.437	TA2	GPA
2.375	3.623	0.437	TB2	P2
2.375	3.623	0.500	SA2	G2
2.375	3.623	0.500	TA2	P2
2.375	3.750	0.500	SC	R2
2.375	3.750	0.500	TB2	G2
2.375	3.750	0.500	TC	R2
2.375	3.875	0.437	SA2	P2
2.375	4.331	0.500	TA2	C2
2.382	3.071	0.394	TC	R2
2.402	3.153	0.307	TB	G2
2.421	3.350	0.374	TB2	PV
2.437	3.125	0.374	TB2	G2
2.437	3.250	0.374	TC	R2
2.437	3.250	0.437	TC	R2
2.437	3.251	0.437	TA2	P2
2.437	3.350	0.374	SB2	P2
2.437	3.375	0.374	TA2	G2
2.437	3.500	0.375	TA2	P2
2.437	3.500	0.437	TA2	P2
2.437	3.500	0.500	SBR	G2
2.437	3.624	0.374	KB2	P2
2.437	3.625	0.374	TC	R2
2.438	3.350	0.469	TA2	P2
2.441	2.756	0.472	TC	R2
2.441	2.953	0.394	TC	R2
2.441	2.953	0.472	TC	R2
2.441	2.992	0.374	TB	G2
2.441	3.071	0.394	TC	R2
2.441	3.071	0.472	TC	R2
2.441	3.150	0.354	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.441	3.150	0.394	SC	R2
2.441	3.150	0.394	TA2	G2
2.441	3.150	0.394	TB2	G2
2.441	3.150	0.394	TC	R2
2.441	3.150	0.472	TC	R2
2.441	3.189	0.394	TC	R2
2.441	3.228	0.394	TC	R2
2.441	3.228	0.433	TB2	C3
2.441	3.228	0.472	TC	R2
2.441	3.346	0.315	TB2	G2
2.441	3.346	0.315	TC	R2
2.441	3.346	0.354	TB2	G2
2.441	3.346	0.394	SC	R2
2.441	3.346	0.394	TB2	G2
2.441	3.346	0.394	TC	R2
2.441	3.346	0.472	DB2	CV
2.441	3.346	0.472	SB2	G2
2.441	3.346	0.472	TB2	G2
2.441	3.346	0.472	TC	R2
2.441	3.346	0.512	TC	R2
2.441	3.346	0.709	DB	GP
2.441	3.465	0.472	TC	R2
2.441	3.504	0.472	TC	R2
2.441	3.543	0.394	SC	R2
2.441	3.543	0.394	TC	R2
2.441	3.543	0.472	TA2	G2
2.441	3.543	0.472	TC	R2
2.441	3.543	0.512	SA2	G2
2.441	3.543	0.512	TC	R2
2.441	3.661	0.472	TC	R2
2.441	3.740	0.394	SC	R2
2.441	3.740	0.394	TC	R2
2.441	3.740	0.472	TC	R2
2.441	3.937	0.394	TC	R2
2.441	3.937	0.472	SC	R2
2.441	3.937	0.472	TB2	C2
2.441	3.937	0.472	TC	R2
2.441	4.331	0.512	TC	R2
2.469	3.063	0.437	SC	R2
2.480	3.012	0.236	WPB	G4
2.480	3.150	0.303	TB2	G2
2.480	3.150	0.354	TC	R2
2.480	3.150	0.394	TC	R2
2.480	3.150	0.472	TB2	C2
2.480	3.150	0.472	TC	R2
2.480	3.248	0.394	TC	R2
2.480	3.268	0.315	SC	R2
2.480	3.346	0.472	TC	R2
2.480	3.465	0.394	TC	R2
2.480	3.465	0.472	TC	R2
2.480	3.543	0.394	SC	R2
2.480	3.543	0.394	TC	R2
2.480	3.543	0.472	TC	R2
2.480	3.543	0.512	TC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.480	3.937	0.394	SC	R2
2.480	3.937	0.394	TC	R2
2.480	3.937	0.512	TC	R2
2.500	3.000	0.252	VB	C2
2.500	3.000	0.252	WPB	G4
2.500	3.000	0.374	SC	R2
2.500	3.062	0.252	SBR	C2
2.500	3.125	0.252	WPB	G4
2.500	3.250	0.374	SC	R2
2.500	3.250	0.500	TC	R2
2.500	3.251	0.311	VB2	P2
2.500	3.251	0.374	TB2	P2
2.500	3.251	0.500	SA2	P2
2.500	3.251	0.500	SB2	P2
2.500	3.251	0.500	TA2	P2
2.500	3.264	0.626	TB2	P2
2.500	3.281	0.374	TC	R2
2.500	3.346	0.472	TC	R2
2.500	3.370	0.500	SA2	PS
2.500	3.371	0.374	TB2	G2
2.500	3.375	0.500	SC	R2
2.500	3.428	0.374	TB2	PPA
2.500	3.499	0.500	SB2	CV
2.500	3.500	0.374	TA2	P2
2.500	3.500	0.374	TB2	G2
2.500	3.500	0.500	SA2	G2
2.500	3.500	0.500	SA2	P2
2.500	3.500	0.500	SC	R2
2.500	3.500	0.500	TA2	P2
2.500	3.500	0.500	TB2	G2
2.500	3.500	0.500	TC	R2
2.500	3.500	0.626	SB2	G2
2.500	3.543	0.437	SA2	P2
2.500	3.543	0.437	TC	R2
2.500	3.543	0.500	TA2	P2
2.500	3.547	0.469	SA2	G2
2.500	3.563	0.437	SC	R2
2.500	3.623	0.374	TA2	P2
2.500	3.623	0.437	TB2	PPA
2.500	3.625	0.500	SC	R2
2.500	3.740	0.394	SC	R2
2.500	3.750	0.437	SBR	P2
2.500	3.750	0.500	TC	R2
2.500	3.751	0.437	SA2	P2
2.500	3.751	0.437	TB2	G2
2.500	3.751	0.500	SB2	P2
2.500	3.751	0.500	TA2	P2
2.500	3.875	0.437	SA2	C2
2.500	3.876	0.469	TA2	PPA
2.500	3.876	0.469	TB2	C2
2.500	4.000	0.374	TA2	G2
2.500	4.000	0.469	SC	R2
2.500	4.000	0.500	SC	R2
2.500	4.000	0.500	TA2	G2

Shaft	Bore	Width	Lip Style	Material
2.500	4.331	0.512	SA2	G2
2.500	4.938	0.500	TB2	CPA
2.520	3.031	0.472	TB	G2
2.520	3.150	0.315	TC	R2
2.520	3.150	0.394	TC	R2
2.520	3.150	0.472	TC	R2
2.520	3.150	0.512	TC	R2
2.520	3.228	0.276	KB2	G2
2.520	3.346	0.394	TC	R2
2.520	3.346	0.472	TC	R2
2.520	3.346	0.630	TC	R2
2.520	3.504	0.472	TB	G2
2.520	3.740	0.394	TC	R3
2.520	4.724	0.472	TC	R2
2.531	3.625	0.500	TB2	PPA
2.559	2.953	0.197	SC	R2
2.559	2.953	0.197	TC	R2
2.559	2.953	0.315	TC	R2
2.559	2.953	0.394	TC	R2
2.559	2.953	0.472	TC	R2
2.559	3.031	0.295	TB2	G3
2.559	3.071	0.472	TC	R2
2.559	3.150	0.236	SC	R2
2.559	3.150	0.276	TC	R2
2.559	3.150	0.315	DC	R2
2.559	3.150	0.315	SC	R2
2.559	3.150	0.315	TC	R2
2.559	3.150	0.315	VB2	G2
2.559	3.150	0.394	SC	R2
2.559	3.150	0.394	TC	R2
2.559	3.150	0.472	TC	R2
2.559	3.228	0.354	TC	R2
2.559	3.228	0.394	SC	R2
2.559	3.228	0.394	TC	R2
2.559	3.228	0.472	TC	R2
2.559	3.268	0.335	TC	R2
2.559	3.346	0.315	SC	R2
2.559	3.346	0.315	TC	R2
2.559	3.346	0.394	SC	R2
2.559	3.346	0.394	TB2	G2
2.559	3.346	0.394	TC	R2
2.559	3.346	0.472	TC	R2
2.559	3.346	0.512	SC	R2
2.559	3.346	0.512	TB2	G2
2.559	3.346	0.512	TC	R2
2.559	3.465	0.315	TC	R2
2.559	3.465	0.394	TC	R2
2.559	3.465	0.472	TA2	G2
2.559	3.465	0.472	TB2	G2
2.559	3.465	0.472	TB2	PS
2.559	3.465	0.472	TC	R2
2.559	3.465	0.512	TB2	G2
2.559	3.465	0.512	TC	R2
2.559	3.504	0.472	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.559	3.543	0.236	VB2	G2
2.559	3.543	0.276	TC	R2
2.559	3.543	0.315	TC	R2
2.559	3.543	0.394	SB2	C2
2.559	3.543	0.394	SC	R2
2.559	3.543	0.394	TC	R2
2.559	3.543	0.472	SC	R2
2.559	3.543	0.472	TC	R2
2.559	3.543	0.512	SB2	G2
2.559	3.543	0.512	SC	R2
2.559	3.543	0.512	TA2	G2
2.559	3.543	0.512	TB2	G2
2.559	3.543	0.512	TC	R2
2.559	3.543	0.787	DB	GP
2.559	3.622	0.394	TC	R2
2.559	3.622	0.472	TB2	P2
2.559	3.622	0.512	TB2	G2
2.559	3.740	0.394	SC	R2
2.559	3.740	0.394	TC	R2
2.559	3.740	0.472	TC	R2
2.559	3.740	0.512	TC	R2
2.559	3.740	0.551	TB2	G2
2.559	3.740	0.551	TC	R2
2.559	3.937	0.315	TC	R2
2.559	3.937	0.374	TC	R2
2.559	3.937	0.394	SC	R2
2.559	3.937	0.394	TC	R2
2.559	3.937	0.472	SC	R2
2.559	3.937	0.472	TB2	G2
2.559	3.937	0.472	TC	R2
2.559	3.937	0.512	TC	R2
2.559	4.016	0.512	TC	R2
2.559	4.134	0.472	TC	R2
2.559	4.331	0.394	TB2	G2
2.559	4.331	0.394	TC	R2
2.559	4.331	0.472	TC	R2
2.559	4.331	0.512	TC	R2
2.559	4.528	0.472	TC	R2
2.559	4.528	0.512	TC	R2
2.559	4.724	0.394	SC	R2
2.559	4.724	0.394	TC	R2
2.559	4.724	0.472	TC	R2
2.559	4.724	0.512	TC	R2
2.559	4.724	0.591	TC	R2
2.559	5.512	0.551	TC	R2
2.562	3.623	0.469	TB2	PPA
2.563	3.172	0.189	SBR	G2
2.563	3.481	0.374	TA2	P2
2.563	3.484	0.500	SB2	G2
2.563	3.500	0.500	TB2	G2
2.563	3.623	0.374	TA2	P2
2.563	3.625	0.437	TC	R2
2.563	3.625	0.500	SA2	P2
2.563	3.750	0.374	TA2	P2

Shaft	Bore	Width	Lip Style	Material
2.563	3.750	0.500	TC	RV
2.563	3.873	0.438	TB2	P2
2.593	3.250	0.500	TC	R2
2.598	3.346	0.315	TA2	G2
2.598	3.346	0.394	SC	R2
2.598	3.481	0.500	TA2	PPA
2.598	3.999	0.780	TB2	P2
2.625	3.125	0.252	WPB	G4
2.625	3.250	0.437	SA2	P2
2.625	3.251	0.437	TA2	PPA
2.625	3.350	0.374	SC	R2
2.625	3.371	0.437	TA2	C2
2.625	3.375	0.252	VB2	P2
2.625	3.375	0.374	TC	R2
2.625	3.480	0.500	SA2	P2
2.625	3.500	0.374	SC	R2
2.625	3.500	0.374	TA2	P2
2.625	3.500	0.374	TB2	P2
2.625	3.500	0.437	TA2	P2
2.625	3.500	0.437	TB2	CPA
2.625	3.543	0.311	SB2	P2
2.625	3.547	0.469	SC	R2
2.625	3.623	0.374	SB2	P2
2.625	3.623	0.374	TA2	G2
2.625	3.623	0.469	TB2	PPA
2.625	3.623	0.500	SA2	P2
2.625	3.623	0.750	TA2	G2
2.625	3.625	0.374	TC	R2
2.625	3.625	0.437	TB2	P2
2.625	3.625	0.500	SA2	G2
2.625	3.625	0.500	TC	R2
2.625	3.628	0.438	TA2	P2
2.625	3.628	0.469	SA2	G2
2.625	3.750	0.374	SB	P2
2.625	3.750	0.374	TC	R2
2.625	3.750	0.500	SC	R2
2.625	3.750	0.500	TA2	G2
2.625	3.750	0.626	TC	R2
2.625	3.751	0.374	TB2	C2
2.625	3.751	0.437	TA2	P2
2.625	3.751	0.500	TB2	PPA
2.625	3.875	0.374	TC	R2
2.625	3.876	0.437	SA2	P2
2.625	3.876	0.469	TA2	C2
2.625	4.003	0.374	TA2	P2
2.625	4.375	0.437	TA2	P2
2.625	4.437	0.437	SA2	C2
2.626	3.750	0.500	TC	R2
2.629	3.813	0.500	SB2	G2
2.638	3.228	0.276	TC	R2
2.638	3.307	0.354	DC	R2
2.638	3.346	0.394	TC	R2
2.638	3.937	0.394	DC	R2
2.648	3.812	0.500	SB2	P2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.667	3.751	0.500	VBR	C2
2.677	3.150	0.315	TC	R2
2.677	3.150	0.394	SC	R2
2.677	3.150	0.394	TC	R2
2.677	3.228	0.276	SC	R2
2.677	3.228	0.276	TC	R2
2.677	3.228	0.394	TC	R2
2.677	3.254	0.295	TC	R2
2.677	3.346	0.315	TB2	G2
2.677	3.346	0.394	SB2	G2
2.677	3.346	0.394	SC	R2
2.677	3.346	0.394	TC	R2
2.677	3.465	0.374	TA2	G2
2.677	3.465	0.394	TB2	G2
2.677	3.465	0.394	TC	R2
2.677	3.543	0.315	TC	R2
2.677	3.543	0.331	SB2	P2
2.677	3.543	0.394	SB2	C2
2.677	3.543	0.394	SC	R2
2.677	3.543	0.394	TA2	G2
2.677	3.543	0.394	TB2	G2
2.677	3.543	0.394	TC	R2
2.677	3.543	0.472	TB2	G2
2.677	3.543	0.472	TC	R2
2.677	3.543	0.512	DC	RV
2.677	3.543	0.512	SB2	G2
2.677	3.543	0.512	TC	R2
2.677	3.543	0.551	TB2	G2
2.677	3.622	0.394	TA2	G2
2.677	3.622	0.472	TB2	G2
2.677	3.622	0.472	TC	R2
2.677	3.740	0.315	TC	R2
2.677	3.740	0.394	SC	R2
2.677	3.740	0.512	SB2	G2
2.677	3.740	0.512	SB2	PV
2.677	3.740	0.512	TB2	G2
2.677	3.740	0.512	TC	R2
2.677	3.858	0.394	TC	R2
2.677	3.937	0.394	SC	R2
2.677	3.937	0.394	TC	R2
2.677	3.937	0.472	TC	R2
2.677	3.937	0.512	SC	R2
2.677	3.937	0.512	TC	R2
2.677	4.331	0.512	SC	R2
2.677	4.528	0.512	SC	R2
2.677	4.528	0.512	SC	R2
2.687	3.750	0.500	SC	R2
2.687	3.875	0.374	TC	R2
2.687	4.000	0.500	TC	R2
2.688	4.003	0.469	SA2	C2
2.717	3.346	0.394	TB2	C2
2.717	3.504	0.512	TC	R2
2.717	3.622	0.472	TC	R2
2.717	4.331	0.394	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.719	3.891	0.390	TA2	C2
2.750	3.125	0.189	WPB	G4
2.750	3.250	0.252	WPB	G4
2.750	3.500	0.157	VC	R2
2.750	3.500	0.252	VB2	P2
2.750	3.500	0.374	DC	RV
2.750	3.500	0.374	SB2	P2
2.750	3.500	0.374	SC	RV
2.750	3.500	0.374	SC	R2
2.750	3.500	0.374	TA2	P2
2.750	3.500	0.374	TB2	GV
2.750	3.500	0.374	TC	R2
2.750	3.500	0.437	SA2	P2
2.750	3.500	0.500	SC	R2
2.750	3.540	0.500	SA2	P2
2.750	3.543	0.437	TA2	C2
2.750	3.543	0.500	TA2	CPA
2.750	3.543	0.500	TB2	PPA
2.750	3.547	0.500	SC	R2
2.750	3.625	0.374	TC	R2
2.750	3.625	0.437	SA2	G2
2.750	3.750	0.374	TA2	GV
2.750	3.750	0.437	SC	R2
2.750	3.750	0.500	SA2	G2
2.750	3.750	0.500	SC	R2
2.750	3.750	0.626	TA2	C2
2.750	3.750	0.626	TB2	C2
2.750	3.751	0.437	TA2	G2
2.750	3.751	0.437	TB2	PPA
2.750	3.751	0.500	SA2	P2
2.750	3.751	0.500	TA2	G2
2.750	3.751	0.500	TA2	P2
2.750	3.765	0.469	SA2	G2
2.750	3.875	0.374	TA2	P2
2.750	3.875	0.500	SA2	P2
2.750	3.875	0.500	TC	R2
2.750	3.876	0.437	TB2	C2
2.750	3.876	0.469	TA2	PPA
2.750	3.876	0.469	TB2	PPA
2.750	3.937	0.307	TB2	P2
2.750	4.000	0.500	SC	R2
2.750	4.002	0.374	TA2	P2
2.750	4.003	0.469	TA2	PPA
2.750	4.125	0.437	SB2	PPA
2.750	4.250	0.469	TA2	P2
2.750	4.331	0.500	TA2	CPA
2.750	4.374	0.752	TA2	G2
2.756	3.150	0.236	TC	R2
2.756	3.150	0.315	TC	R2
2.756	3.150	0.394	TC	R2
2.756	3.150	0.472	TC	R2
2.756	3.209	0.236	SC	R3
2.756	3.209	0.236	TC	R3
2.756	3.209	0.236	VC	R2

Shaft	Bore	Width	Lip Style	Material
2.756	3.228	0.335	TC	R2
2.756	3.268	0.394	TC	R2
2.756	3.346	0.276	SC	R2
2.756	3.346	0.315	SC	R2
2.756	3.346	0.315	TB2	G2
2.756	3.346	0.315	TC	R2
2.756	3.346	0.354	TC	R2
2.756	3.346	0.394	TC	R2
2.756	3.346	0.472	TC	R2
2.756	3.386	0.472	SC	R2
2.756	3.425	0.394	TC	R2
2.756	3.465	0.315	TC	R2
2.756	3.465	0.394	TC	R2
2.756	3.465	0.472	TB	G2
2.756	3.465	0.472	TC	R2
2.756	3.543	0.276	TC	R2
2.756	3.543	0.315	TC	R2
2.756	3.543	0.394	DC	R2
2.756	3.543	0.394	SB2	G2
2.756	3.543	0.394	SC	RV
2.756	3.543	0.394	SC	R2
2.756	3.543	0.394	TA2	G2
2.756	3.543	0.394	TB2	G2
2.756	3.543	0.394	TC	R2
2.756	3.543	0.472	SC	R2
2.756	3.543	0.472	TA2	G2
2.756	3.543	0.472	TC	R2
2.756	3.543	0.512	SA2	G2
2.756	3.543	0.512	TC	R2
2.756	3.543	0.531	TB2	G2
2.756	3.547	0.413	TC	R2
2.756	3.622	0.276	VC	R2
2.756	3.622	0.354	TC	R2
2.756	3.622	0.394	TC	R2
2.756	3.622	0.472	TBR	G2
2.756	3.622	0.472	TC	R2
2.756	3.740	0.394	DC	R2
2.756	3.740	0.394	SC	R2
2.756	3.740	0.394	TC	R2
2.756	3.740	0.472	TC	R2
2.756	3.740	0.512	SB2	G2
2.756	3.740	0.512	SC	R2
2.756	3.740	0.512	TB2	G2
2.756	3.740	0.512	TC	R2
2.756	3.937	0.394	SC	R2
2.756	3.937	0.394	TC	R2
2.756	3.937	0.472	SC	R2
2.756	3.937	0.472	TB2	G2
2.756	3.937	0.472	TC	R2
2.756	3.937	0.512	SB2	G2
2.756	3.937	0.512	TB2	G2
2.756	3.937	0.512	TC	R2
2.756	3.937	0.551	TB2	G2
2.756	3.937	0.551	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.756	4.016	0.472	TC	R2
2.756	4.016	0.512	TC	R2
2.756	4.134	0.394	SB2	G2
2.756	4.134	0.394	TC	R3
2.756	4.134	0.472	TC	R2
2.756	4.134	0.512	SC	R2
2.756	4.134	0.512	TC	R2
2.756	4.331	0.315	SC	R2
2.756	4.331	0.394	SC	R2
2.756	4.331	0.394	TC	R2
2.756	4.331	0.472	SC	R2
2.756	4.331	0.472	TC	R2
2.756	4.331	0.512	SC	R2
2.756	4.331	0.512	TA2	G2
2.756	4.331	0.512	TC	R2
2.756	4.409	0.512	TC	R2
2.756	4.528	0.472	TC	R2
2.756	4.528	0.512	TC	R2
2.756	4.528	0.591	TC	R2
2.756	4.724	0.472	TC	R2
2.756	4.724	0.512	SC	R2
2.756	4.724	0.512	TC	R2
2.756	4.921	0.472	TC	R2
2.756	4.921	0.512	TC	R2
2.764	3.882	0.189	VB	C2
2.795	3.465	0.315	SC	R2
2.795	3.465	0.315	TC	R2
2.812	3.876	0.189	VBR	C2
2.812	3.876	0.437	TA2	P2
2.812	4.249	0.469	TA2	P2
2.813	3.875	0.484	SA2	C2
2.813	3.876	0.437	SA2	P2
2.835	3.386	0.295	TC	R2
2.835	3.386	0.354	TC	R2
2.835	3.465	0.315	SB2	G2
2.835	3.543	0.315	TB2	C2
2.835	3.543	0.315	TC	R2
2.835	3.543	0.394	SC	R2
2.835	3.543	0.394	TC	R2
2.835	3.622	0.374	SC	RS
2.835	3.622	0.374	TC	R2
2.835	3.622	0.472	TC	R2
2.835	3.701	0.315	TB2	G2
2.835	3.701	0.394	TB2	G2
2.835	3.701	0.472	TC	R2
2.835	3.740	0.394	SC	R2
2.835	3.740	0.394	TC	R2
2.835	3.740	0.472	SC	R2
2.835	3.740	0.472	TC	R2
2.835	3.740	0.512	TC	R2
2.835	3.760	0.472	TB2	G2
2.835	3.937	0.394	SC	R2
2.835	3.937	0.394	TC	R2
2.835	3.937	0.472	SA2	GPA

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
2.835	3.937	0.472	SC	R2
2.835	3.937	0.512	TA2	P2
2.835	4.016	0.591	TB2	G2
2.835	4.134	0.512	TA2	G2
2.835	4.134	0.512	TB2	G2
2.835	4.134	0.512	TC	R2
2.835	4.331	0.394	TC	R2
2.835	4.528	0.394	TC	R2
2.844	4.003	0.500	SA2	P2
2.874	3.543	0.315	TB2	G2
2.874	3.543	0.315	TC	R2
2.874	3.543	0.394	TB	G2
2.874	3.858	0.472	TC	R2
2.874	3.937	0.394	TB2	G2
2.874	3.937	0.394	TC	R2
2.875	3.371	0.252	WPB	G4
2.875	3.437	0.295	TB	P2
2.875	3.562	0.469	TC	R2
2.875	3.623	0.374	TA2	P2
2.875	3.625	0.374	SC	R2
2.875	3.625	0.374	TA2	P2
2.875	3.625	0.374	TC	R2
2.875	3.750	0.433	SA2	PS
2.875	3.750	0.500	SC	R2
2.875	3.751	0.374	TA2	P2
2.875	3.751	0.374	TC	R2
2.875	3.751	0.437	SA2	P2
2.875	3.751	0.437	TA2	P2
2.875	3.751	0.469	SA2	P2
2.875	3.751	0.500	SA2	P2
2.875	3.875	0.500	SC	R2
2.875	3.876	0.374	TA2	P2
2.875	3.937	0.453	SB2	C2
2.875	4.000	0.374	SC	R2
2.875	4.000	0.500	SC	R2
2.875	4.000	0.500	TC	R2
2.875	4.003	0.469	SA2	P2
2.875	4.003	0.500	SA2	P2
2.875	4.003	0.591	SB2	G2
2.875	4.331	0.437	TB2	PPA
2.876	3.982	0.374	TB2	C2
2.876	4.016	0.386	TC	R2
2.882	3.431	0.291	TB	P2
2.913	3.543	0.394	SB	CSI
2.913	3.543	0.394	TC	R2
2.913	3.701	0.394	TC	R2
2.913	3.740	0.276	TC	R2
2.913	3.937	0.394	TB2	G2
2.913	3.937	0.394	TBR	G2
2.913	3.937	0.512	TC	R2
2.913	4.488	0.433	SA2	G2
2.937	3.750	0.374	DC	R2
2.937	3.750	0.374	TC	R2
2.937	3.937	0.437	TC	R2

Shaft	Bore	Width	Lip Style	Material
2.937	3.937	0.500	TA2	PPA
2.937	4.000	0.374	TC	R2
2.937	4.000	0.437	TB2	G2
2.937	4.003	0.469	TB2	PPA
2.937	4.125	0.374	TB2	PV
2.937	4.499	0.469	TA2	P2
2.938	3.751	0.374	TB2	P2
2.938	3.751	0.500	SA2	P2
2.953	3.346	0.276	SC	R2
2.953	3.543	0.276	SB	G2
2.953	3.543	0.315	SC	R2
2.953	3.543	0.315	TC	R2
2.953	3.543	0.394	SC	RV
2.953	3.543	0.394	TC	R2
2.953	3.543	0.472	TC	R2
2.953	3.583	0.472	SC	R2
2.953	3.622	0.472	TC	R2
2.953	3.740	0.197	SB	G2
2.953	3.740	0.276	TB2	GV
2.953	3.740	0.315	TC	R2
2.953	3.740	0.394	DC	R2
2.953	3.740	0.394	SC	R2
2.953	3.740	0.394	TB2	G2
2.953	3.740	0.394	TC	R2
2.953	3.740	0.472	SC	R2
2.953	3.740	0.472	TC	R2
2.953	3.740	0.512	SA2	G2
2.953	3.740	0.512	SC	R2
2.953	3.740	0.512	TA2	G2
2.953	3.740	0.512	TBR	G2
2.953	3.740	0.512	TC	R2
2.953	3.780	0.433	TB	G2
2.953	3.780	0.441	TB2	C2
2.953	3.937	0.276	TC	R2
2.953	3.937	0.394	SA2	GPA
2.953	3.937	0.394	SB2	P2
2.953	3.937	0.394	SC	R2
2.953	3.937	0.394	TB2	PS
2.953	3.937	0.394	TC	R2
2.953	3.937	0.472	SC	R2
2.953	3.937	0.472	TC	RS
2.953	3.937	0.472	TC	R2
2.953	3.937	0.512	SB2	G2
2.953	3.937	0.512	TA2	G2
2.953	3.937	0.512	TB2	G2
2.953	3.937	0.512	TC	R2
2.953	4.000	0.630	TA2	G2
2.953	4.016	0.512	TB2	G2
2.953	4.016	0.512	TC	R2
2.953	4.134	0.394	TA2	G2
2.953	4.134	0.472	DC	R2
2.953	4.134	0.472	SC	R2
2.953	4.134	0.472	TA2	G2
2.953	4.134	0.472	TA2	G2
2.953	4.134	0.472	TA2	C2

Shaft	Bore	Width	Lip Style	Material
2.953	4.134	0.512	SC	R2
2.953	4.134	0.512	TA2	G2
2.953	4.134	0.512	TB2	G2
2.953	4.134	0.512	TC	R2
2.953	4.134	0.591	TB2	G2
2.953	4.134	0.591	TC	R2
2.953	4.173	0.394	TC	R2
2.953	4.252	0.512	TA2	G3
2.953	4.252	0.512	TC	R2
2.953	4.331	0.394	TC	R2
2.953	4.331	0.472	SC	R2
2.953	4.331	0.472	TC	R2
2.953	4.331	0.512	SC	R2
2.953	4.331	0.512	TB2	G2
2.953	4.331	0.512	TC	R2
2.953	4.409	0.472	TB2	C2
2.953	4.528	0.315	TC	R2
2.953	4.528	0.374	TC	R2
2.953	4.528	0.394	SC	R2
2.953	4.528	0.394	TC	R2
2.953	4.528	0.472	SC	RV
2.953	4.528	0.512	SA2	G2
2.953	4.528	0.512	TC	R2
2.953	4.646	0.472	TC	R2
2.953	4.724	0.394	TC	R2
2.953	4.724	0.472	SC	R2
2.953	4.724	0.472	TC	R2
2.953	4.724	0.512	TC	R2
2.953	4.764	0.512	TB2	G2
2.953	4.764	0.512	TBR	C2
2.953	4.764	0.512	TC	R2
2.953	4.921	0.512	TC	R2
2.953	5.118	0.394	TC	R2
2.953	5.118	0.512	SC	RV
2.953	5.118	0.512	TC	RV
2.953	5.276	0.394	TC	R2
2.953	5.906	0.472	TC	R2
2.992	3.622	0.394	TC	R2
2.992	3.701	0.472	TC	R2
2.992	3.740	0.394	TC	R2
2.992	4.134	0.472	TC	R2
2.992	4.134	0.512	TC	R2
3.000	3.500	0.252	SB	G2
3.000	3.500	0.252	SC	R2
3.000	3.500	0.252	WPB	G4
3.000	3.750	0.374	DC	R2
3.000	3.750	0.374	SC	R2
3.000	3.750	0.374	TA2	G2
3.000	3.750	0.374	TC	R2
3.000	3.750	0.437	TC	RS
3.000	3.751	0.374	TB2	PPA
3.000	3.751	0.437	TB2	P2
3.000	3.751	0.500	SA2	G2
3.000	3.751	0.500	TA2	PPA

Shaft	Bore	Width	Lip Style	Material
3.000	3.875	0.437	SB2	C2
3.000	3.875	0.437	TA2	P2
3.000	3.875	0.437	TB2	G2
3.000	3.875	0.437	TC	R2
3.000	3.875	0.469	SA2	PV
3.000	3.875	0.469	SA2	GV
3.000	3.875	0.472	SA2	P2
3.000	3.875	0.500	TB2	G2
3.000	3.876	0.311	SB2	PV
3.000	4.000	0.374	SC	R2
3.000	4.000	0.437	TB2	C2
3.000	4.000	0.437	TC	R2
3.000	4.000	0.437	TC	R2
3.000	4.000	0.469	SA2	G2
3.000	4.000	0.469	SB2	G2
3.000	4.000	0.500	SC	R2
3.000	4.000	0.500	TC	R2
3.000	4.003	0.374	SA2	P2
3.000	4.003	0.374	TA2	P2
3.000	4.003	0.437	TA2	CPA
3.000	4.003	0.437	TA2	P2
3.000	4.003	0.454	SA2	P2
3.000	4.003	0.469	SA2	P2
3.000	4.003	0.469	TA2	PPA
3.000	4.003	0.469	TA2	GV
3.000	4.003	0.500	WPB	G4
3.000	4.125	0.437	SA2	P2
3.000	4.125	0.437	SC	R2
3.000	4.125	0.500	SC	R2
3.000	4.249	0.469	TA2	P2
3.000	4.250	0.437	TB2	G2
3.000	4.250	0.500	SC	R2
3.000	4.250	0.625	SA2	G2
3.000	4.331	0.500	TA2	P2
3.000	4.500	0.437	SA2	P2
3.000	4.500	0.437	TA2	P2
3.000	4.500	0.469	TA2	P2
3.000	5.000	0.437	TA2	P2
3.031	3.370	0.189	SB	G2
3.031	3.661	0.394	TB	G2
3.031	3.760	0.374	SC	R2
3.031	3.937	0.394	TC	R2
3.031	3.937	0.512	TB2	G2
3.040	3.937	0.252	SC	R2
3.050	3.437	0.220	VC	RV
3.063	4.125	0.500	TC	R2
3.071	3.740	0.154	VB	G2
3.071	3.740	0.512	TC	R2
3.071	3.878	0.472	TA2	G3
3.071	3.937	0.394	SC	R2
3.071	3.937	0.512	TC	R2
3.071	4.134	0.512	TC	R2
3.071	4.252	0.512	TA2	PPA
3.071	4.331	0.472	SC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
3.071	4.331	0.472	TC	R2
3.071	4.331	0.512	SC	R2
3.071	4.331	0.512	TC	R2
3.071	4.528	0.394	TC	R2
3.109	3.766	0.437	TC	RS
3.109	4.450	0.394	SB2	C2
3.110	3.750	0.437	SC	R2
3.125	3.750	0.313	WPB	G4
3.125	3.875	0.402	TC	R2
3.125	3.898	0.370	SBR	C2
3.125	3.937	0.516	SA2	PV
3.125	4.000	0.469	TA2	CPA
3.125	4.000	0.500	SC	R2
3.125	4.000	0.500	TA2	G2
3.125	4.000	0.790	DA2	C2
3.125	4.003	0.374	TA2	P2
3.125	4.003	0.374	TB2	C2
3.125	4.125	0.374	SC	R2
3.125	4.125	0.437	TA2	CS
3.125	4.125	0.500	SC	R2
3.125	4.125	0.500	TA2	P2
3.125	4.125	0.563	TB2	GS
3.125	4.173	0.291	KB2	C2
3.125	4.250	0.468	SA2	G2
3.125	4.250	0.500	TA2	G2
3.125	4.375	0.500	TA2	P2
3.125	4.500	0.500	SC	R2
3.125	4.500	0.500	TA2	P2
3.125	4.500	0.625	SC	R2
3.125	4.500	0.626	TA2	G2
3.125	4.626	0.437	TA2	P2
3.125	5.000	0.468	TA2	P2
3.125	5.004	0.437	SA2	P2
3.125	5.251	0.437	SA2	P2
3.150	3.543	0.134	VC	RV
3.150	3.543	0.197	VC	RV
3.150	3.543	0.394	TC	R2
3.150	3.740	0.197	SC	R2
3.150	3.740	0.315	TC	R2
3.150	3.740	0.394	TC	R2
3.150	3.858	0.394	TC	R2
3.150	3.937	0.276	VC	RV
3.150	3.937	0.315	TC	R2
3.150	3.937	0.394	DC	R2
3.150	3.937	0.394	SC	RV
3.150	3.937	0.394	SC	R2
3.150	3.937	0.394	TB2	CV
3.150	3.937	0.394	TC	RV
3.150	3.937	0.394	TC	R2
3.150	3.937	0.472	DC	R2
3.150	3.937	0.472	SC	R2
3.150	3.937	0.472	TA2	G2
3.150	3.937	0.472	TC	R2
3.150	3.937	0.512	SB2	G2

Shaft	Bore	Width	Lip Style	Material
3.150	3.937	0.512	SC	R2
3.150	3.937	0.512	TA2	G2
3.150	3.937	0.512	TB2	PS
3.150	3.937	0.512	TC	R2
3.150	4.134	0.394	SC	R2
3.150	4.134	0.394	TC	R2
3.150	4.134	0.472	DC	R2
3.150	4.134	0.472	TC	R2
3.150	4.134	0.512	KC	R2
3.150	4.134	0.512	SB2	GS
3.150	4.134	0.512	SC	R2
3.150	4.134	0.512	TB2	G2
3.150	4.134	0.512	TC	R2
3.150	4.134	0.591	TB2	G2
3.150	4.134	0.787	DB2	G2
3.150	4.252	0.512	TA2	G3
3.150	4.331	0.394	SC	R2
3.150	4.331	0.394	TC	R2
3.150	4.331	0.472	SC	R2
3.150	4.331	0.472	TC	R2
3.150	4.331	0.512	TA2	G2
3.150	4.331	0.512	TB2	GPA
3.150	4.331	0.512	TB2	G2
3.150	4.331	0.512	TC	R2
3.150	4.528	0.236	KB2	C2
3.150	4.528	0.394	SC	R2
3.150	4.528	0.394	TC	R2
3.150	4.528	0.472	TC	R2
3.150	4.528	0.512	TC	R2
3.150	4.528	0.591	TB2	G2
3.150	4.646	0.472	TC	R2
3.150	4.685	0.472	TC	R2
3.150	4.724	0.472	SC	R2
3.150	4.724	0.512	SC	R2
3.150	4.724	0.512	TB2	G2
3.150	4.724	0.512	TC	R2
3.150	4.921	0.394	TC	R2
3.150	4.921	0.472	SC	R2
3.150	4.921	0.472	TC	R2
3.150	4.921	0.512	TC	R2
3.150	4.921	0.551	TC	R2
3.150	5.118	0.512	TA2	G3
3.150	5.118	0.512	TC	R2
3.150	5.197	0.591	TC	R2
3.150	5.512	0.472	TC	R2
3.150	5.512	0.512	TC	R2
3.187	4.250	0.311	SC	R2
3.187	4.250	0.500	SC	R2
3.187	4.625	0.563	SA2	G2
3.187	4.750	0.500	SA2	C2
3.228	3.937	0.512	TB	GPA
3.228	3.937	0.512	TC	R2
3.228	4.134	0.394	TC	R2
3.228	4.134	0.472	TC	R2

Shaft	Bore	Width	Lip Style	Material
3.228	4.134	0.512	TC	R2
3.228	4.252	0.512	TA2	G3
3.228	4.331	0.472	SC	R2
3.228	4.331	0.512	SC	R2
3.228	4.508	0.512	TA2	G3
3.228	4.528	0.512	TC	R2
3.232	4.125	0.563	SA2	P2
3.250	3.625	0.189	VBR	P2
3.250	3.750	0.252	WPB	G4
3.250	3.940	0.252	TB	G2
3.250	4.000	0.374	SB2	C2
3.250	4.000	0.469	TA2	P2
3.250	4.000	0.500	TC	R2
3.250	4.003	0.469	TA2	CPA
3.250	4.240	0.500	TA2	P2
3.250	4.249	0.374	TA2	C2
3.250	4.249	0.437	TA2	P2
3.250	4.249	0.469	TA2	CPA
3.250	4.250	0.374	TB2	P2
3.250	4.250	0.469	SA2	P2
3.250	4.250	0.500	SC	RV
3.250	4.250	0.500	TC	R2
3.250	4.250	0.500	WPB	G4
3.250	4.376	0.500	TA2	P2
3.250	4.500	0.500	SC	R2
3.250	4.500	0.500	TB2	G2
3.250	4.625	0.500	SC	R2
3.250	4.626	0.437	SA2	P2
3.250	4.632	0.500	TA2	P2
3.250	4.750	0.500	SC	R2
3.250	5.500	0.500	TA2	PPA
3.268	4.094	0.354	TC	R2
3.268	4.331	0.512	TC	R2
3.268	4.606	0.551	TC	R2
3.307	3.937	0.394	SC	R2
3.307	3.937	0.394	TB	G2
3.307	3.937	0.394	TC	R2
3.307	4.375	0.661	SA2	P2
3.312	4.751	0.500	TA2	P2
3.313	4.249	0.500	TA2	P2
3.313	4.687	0.437	TC	R2
3.344	4.281	0.421	TB2	CS
3.346	3.740	0.197	WPC	R4
3.346	3.937	0.236	SC	R2
3.346	3.937	0.354	SC	R2
3.346	3.937	0.354	TC	R2
3.346	3.937	0.394	TC	R2
3.346	3.937	0.472	TB	G2
3.346	3.937	0.472	TC	R2
3.346	3.937	0.512	SB	G2
3.346	3.937	0.512	TC	R2
3.346	4.016	0.472	TC	R2
3.346	4.134	0.394	SC	R2
3.346	4.134	0.394	TB2	G2

Shaft	Bore	Width	Lip Style	Material
3.346	4.134	0.394	TC	R2
3.346	4.134	0.472	SB2	GS
3.346	4.134	0.472	TB	G2
3.346	4.134	0.472	TC	R2
3.346	4.134	0.512	SC	R2
3.346	4.134	0.512	TA2	G2
3.346	4.134	0.512	TC	R2
3.346	4.134	0.591	SB2	G2
3.346	4.331	0.394	SC	R2
3.346	4.331	0.472	SC	R2
3.346	4.331	0.472	TC	R2
3.346	4.331	0.512	SB2	G2
3.346	4.331	0.512	SC	R2
3.346	4.331	0.512	TB2	G2
3.346	4.331	0.512	TC	R2
3.346	4.331	0.551	TB2	G2
3.346	4.370	0.394	TC	R2
3.346	4.508	0.472	TC	R2
3.346	4.508	0.512	TA2	G2
3.346	4.528	0.472	TC	R2
3.346	4.528	0.512	SC	R2
3.346	4.528	0.512	TC	R2
3.346	4.528	0.591	SC	R2
3.346	4.528	0.591	TC	R2
3.346	4.724	0.394	TC	R2
3.346	4.724	0.472	SC	R2
3.346	4.724	0.472	TC	R2
3.346	4.724	0.512	TC	R2
3.346	4.724	0.591	TC	R2
3.346	4.921	0.472	TC	R2
3.346	4.921	0.512	TC	R2
3.346	4.921	0.551	TC	R2
3.346	5.000	0.512	TA2	G2
3.346	5.118	0.394	TC	R2
3.346	5.118	0.472	SC	R2
3.346	5.118	0.472	TC	R2
3.346	5.118	0.512	TC	R2
3.346	5.118	0.551	TC	R2
3.346	5.512	0.472	TC	R2
3.346	5.906	0.472	TC	R2
3.375	3.875	0.374	VC	R2
3.375	3.948	0.374	TC	R2
3.375	4.000	0.500	SC	R2
3.375	4.250	0.500	SA2	P2
3.375	4.374	0.437	TA2	CPA
3.375	4.374	0.626	SA2	G2
3.375	4.374	0.626	TA2	G2
3.375	4.375	0.500	SA2	P2
3.375	4.375	0.500	TC	R2
3.375	4.376	0.374	TB2	P2
3.375	4.376	0.374	TB2	P2
3.375	4.376	0.374	TBR	P2
3.375	4.626	0.437	SA2	P2
3.375	4.633	0.374	TC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
3.375	4.751	0.374	TB2	P2
3.375	4.999	0.469	TA2	P2
3.375	5.000	0.469	TB2	GPA
3.375	5.000	0.500	SC	R2
3.375	5.125	0.500	SA2	G2
3.386	3.937	0.394	TC	R2
3.386	3.961	0.236	VC	R2
3.386	4.724	0.394	DC	R2
3.437	4.250	0.374	SC	R2
3.437	4.500	0.500	SC	R2
3.437	4.500	0.500	TB2	G2
3.437	4.501	0.374	TB2	P2
3.437	4.625	0.500	TA2	GV
3.437	4.750	0.500	SC	R2
3.437	4.756	0.562	TA2	P2
3.465	4.094	0.394	TC	R3
3.465	4.173	0.394	TC	R2
3.465	4.252	0.433	TC	R2
3.465	4.331	0.472	SC	R2
3.465	4.528	0.512	TA2	G2
3.465	6.299	0.512	TC	R2
3.500	3.875	0.189	WPB	G4
3.500	4.000	0.311	TC	R2
3.500	4.000	0.311	WPB	G4
3.500	4.003	0.252	WPB	G4
3.500	4.005	0.252	SB	C2
3.500	4.125	0.374	SC	R2
3.500	4.250	0.500	TC	R2
3.500	4.291	0.252	TC	R2
3.500	4.375	0.374	SC	R2
3.500	4.375	0.500	SC	R2
3.500	4.375	0.500	TA2	P2
3.500	4.499	0.469	SA2	P2
3.500	4.500	0.374	SB2	PPA
3.500	4.500	0.437	SB2	P2
3.500	4.500	0.437	TA2	G2
3.500	4.500	0.469	TB2	CPA
3.500	4.500	0.500	SC	R2
3.500	4.500	0.500	TC	R2
3.500	4.500	0.500	WPB	G4
3.500	4.501	0.469	TA2	CPA
3.500	4.625	0.500	SA2	C2
3.500	4.625	0.500	TC	R2
3.500	4.626	0.625	TA2	C2
3.500	4.750	0.500	TC	R2
3.500	4.750	0.625	TB2	G2
3.500	4.750	0.626	TC	R2
3.500	4.751	0.375	TB2	PPA
3.500	4.751	0.437	TA2	PH
3.500	4.752	0.374	TB2	PPA
3.500	4.999	0.437	TA2	PPA
3.500	5.000	0.469	SB2	P2
3.500	5.000	0.469	SC	R2
3.500	5.126	0.500	TA2	P2

Shaft	Bore	Width	Lip Style	Material
3.500	5.126	0.626	TB2	PPA
3.500	5.250	0.437	SA2	P2
3.500	5.250	0.626	SC	R2
3.500	5.375	0.500	SC	R2
3.500	6.375	0.374	SB2	G2
3.504	4.134	0.374	SC	RS
3.543	3.937	0.197	VB	G2
3.543	3.937	0.276	TC	R2
3.543	3.937	0.472	TC	R2
3.543	4.134	0.236	TC	RV
3.543	4.134	0.236	VC	R2
3.543	4.134	0.394	TC	R2
3.543	4.134	0.394	VC	R4
3.543	4.134	0.472	TC	R2
3.543	4.134	0.512	TC	R2
3.543	4.173	0.472	SC	R2
3.543	4.331	0.315	TC	R2
3.543	4.331	0.394	SC	R2
3.543	4.331	0.394	TC	R2
3.543	4.331	0.472	SC	R2
3.543	4.331	0.472	TA2	G2
3.543	4.331	0.472	TC	R2
3.543	4.331	0.512	SC	R2
3.543	4.331	0.512	TA2	G2
3.543	4.331	0.512	TB	G2
3.543	4.331	0.512	TC	R2
3.543	4.331	0.591	TA2	G2
3.543	4.409	0.472	TC	R2
3.543	4.437	0.500	TA2	GS
3.543	4.437	0.512	TA2	G2
3.543	4.437	0.512	TC	R2
3.543	4.528	0.354	SC	R2
3.543	4.528	0.394	TC	R2
3.543	4.528	0.472	TC	R2
3.543	4.528	0.488	TB2	P2
3.543	4.528	0.512	SB2	G2
3.543	4.528	0.512	SC	R2
3.543	4.528	0.512	TB2	G2
3.543	4.528	0.512	TC	R2
3.543	4.528	0.787	DB2	G2
3.543	4.646	0.472	TA2	G2
3.543	4.646	0.472	TA2	C2
3.543	4.646	0.472	TB2	G2
3.543	4.646	0.472	TC	R2
3.543	4.724	0.394	TC	R2
3.543	4.724	0.472	SC	R2
3.543	4.724	0.472	TC	R2
3.543	4.724	0.512	TA2	G2
3.543	4.724	0.512	TB2	G2
3.543	4.724	0.512	TC	R2
3.543	4.724	0.591	TA2	G2
3.543	4.921	0.472	TC	R2
3.543	4.921	0.512	TC	R2
3.543	4.921	0.591	TC	R2

Shaft	Bore	Width	Lip Style	Material
3.543	4.921	0.669	TB2	G2
3.543	5.000	0.512	TB2	G3
3.543	5.118	0.394	TC	R2
3.543	5.118	0.472	SC	R2
3.543	5.118	0.472	TC	R2
3.543	5.118	0.512	TA2	P3
3.543	5.118	0.512	TC	R2
3.543	5.118	0.591	TA2	G2
3.543	5.315	0.512	TC	R2
3.543	5.315	0.591	TA2	G2
3.543	5.512	0.472	TC	R2
3.543	5.512	0.512	SC	R2
3.543	6.299	0.394	TC	R3
3.583	4.370	0.394	TC	R3
3.622	4.252	0.315	TC	R2
3.622	4.331	0.394	SC	R2
3.622	4.331	0.394	TC	R2
3.622	4.724	0.472	TC	R2
3.622	4.744	0.512	TB2	G2
3.625	4.499	0.469	TA2	P2
3.625	4.500	0.500	SC	R2
3.625	4.625	0.500	TC	R2
3.625	4.626	0.437	TA2	C2
3.625	4.750	0.500	TB2	PS
3.625	4.751	0.500	TA2	P2
3.625	4.875	0.626	TA2	G2
3.625	4.999	0.500	TA2	P2
3.625	5.000	0.374	TB2	P2
3.625	5.000	0.500	TC	R2
3.650	4.375	0.437	TC	RV
3.654	4.750	0.370	KBR	C2
3.656	4.750	0.500	TC	R2
3.685	5.622	0.500	SC	R2
3.687	4.750	0.500	SC	R2
3.687	5.125	0.500	TB2	G2
3.687	5.125	0.500	TC	R2
3.687	5.625	0.500	TC	R2
3.701	4.488	0.197	SB2	G2
3.701	4.488	0.276	SB2	G2
3.701	6.693	0.315	TC	R2
3.740	4.134	0.512	TC	R2
3.740	4.331	0.236	SC	R2
3.740	4.331	0.394	SC	R2
3.740	4.331	0.394	TC	R2
3.740	4.331	0.433	TC	R2
3.740	4.331	0.472	SC	RV
3.740	4.331	0.472	TC	R2
3.740	4.331	0.512	TC	R2
3.740	4.528	0.394	SB2	C2
3.740	4.528	0.394	TC	R3
3.740	4.528	0.472	TA2	G2
3.740	4.528	0.472	TB2	P2
3.740	4.528	0.472	TC	R2
3.740	4.528	0.512	SC	R2

Shaft	Bore	Width	Lip Style	Material
3.740	4.528	0.512	TA2	G2
3.740	4.528	0.512	TC	R2
3.740	4.724	0.315	SC	R2
3.740	4.724	0.315	TC	R2
3.740	4.724	0.394	TC	RV
3.740	4.724	0.472	DC	R2
3.740	4.724	0.472	SC	R2
3.740	4.724	0.472	TA2	G2
3.740	4.724	0.472	TC	R2
3.740	4.724	0.512	SB2	G2
3.740	4.724	0.512	SC	R2
3.740	4.724	0.512	TB2	G2
3.740	4.724	0.512	TC	R2
3.740	4.724	0.669	DA2	P2
3.740	4.724	0.689	DA2	GS
3.740	4.921	0.472	SC	R2
3.740	4.921	0.472	TC	R2
3.740	4.921	0.512	DC	R2
3.740	4.921	0.512	SA2	G2
3.740	4.921	0.512	TA2	G3
3.740	4.921	0.512	TB2	G2
3.740	4.921	0.512	TC	R2
3.740	5.000	0.512	TB2	G2
3.740	5.039	0.492	TA2	G2
3.740	5.118	0.472	SC	R2
3.740	5.118	0.472	TC	R2
3.740	5.118	0.512	SA2	G2
3.740	5.118	0.512	TA2	G3
3.740	5.118	0.512	TB2	G2
3.740	5.118	0.512	TC	R2
3.740	5.118	0.591	TBR	G2
3.740	5.118	0.591	TC	R2
3.740	5.315	0.472	TC	R2
3.740	5.315	0.512	TC	R2
3.740	5.315	0.512	VC	R2
3.740	5.354	0.472	TC	R2
3.740	5.709	0.394	SC	R2
3.740	5.709	0.512	TC	R2
3.740	6.693	0.512	TC	R2
3.750	4.500	0.437	TC	R2
3.750	4.500	0.469	TA2	PPA
3.750	4.500	0.500	SC	R2
3.750	4.501	0.362	SC	RV
3.750	4.625	0.492	VB2	G2
3.750	4.626	0.500	TA2	P2
3.750	4.750	0.374	SC	R2
3.750	4.750	0.500	SA2	G2
3.750	4.750	0.500	SB2	G2
3.750	4.750	0.500	SC	R2
3.750	4.750	0.500	TC	R2
3.750	4.751	0.374	TB2	P2
3.750	4.751	0.500	TA2	P2
3.750	4.999	0.374	TB2	PV
3.750	4.999	0.469	SA2	P2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
3.750	5.000	0.500	SC	R2
3.750	5.146	0.303	TC	R2
3.750	5.250	0.437	TA2	P2
3.750	5.375	0.500	TB2	C2
3.750	5.376	0.500	TA2	P2
3.780	4.350	0.236	VC	R2
3.780	4.488	0.472	TB	C2
3.780	5.335	0.472	TB2	G2
3.812	4.876	0.500	TA2	P2
3.813	4.875	0.500	TC	R2
3.819	4.488	0.472	TB	G2
3.858	4.724	0.512	SC	R2
3.858	4.724	0.512	TC	R2
3.858	5.118	0.512	TA2	G2
3.858	5.118	0.512	TA2	G2
3.858	5.709	0.748	TA2	G2
3.875	4.750	0.500	SA2	P2
3.875	4.875	0.500	SA2	P2
3.875	4.875	0.500	TC	R2
3.875	5.000	0.374	SB2	C2
3.875	5.000	0.469	SA2	P2
3.875	5.000	0.500	SC	R2
3.875	5.250	0.437	SA2	G2
3.875	5.251	0.437	TA2	P2
3.875	5.689	0.752	SB2	C2
3.880	5.118	0.787	SB	C2
3.937	4.331	0.394	SC	R2
3.937	4.331	0.472	TC	R2
3.937	4.404	0.354	TC	R2
3.937	4.488	0.276	TB	G2
3.937	4.488	0.394	TC	R2
3.937	4.488	0.472	TB	G2
3.937	4.528	0.354	TC	R2
3.937	4.528	0.394	TC	R2
3.937	4.528	0.472	TC	R2
3.937	4.528	0.512	TC	R2
3.937	4.646	0.394	TC	R2
3.937	4.724	0.295	SC	RV
3.937	4.724	0.315	SB2	G2
3.937	4.724	0.394	SC	R2
3.937	4.724	0.394	TB	G2
3.937	4.724	0.394	TC	R2
3.937	4.724	0.433	SC	R2
3.937	4.724	0.433	TC	RPA
3.937	4.724	0.472	SC	R2
3.937	4.724	0.472	TC	RPA
3.937	4.724	0.472	TC	R2
3.937	4.724	0.512	SC	R2
3.937	4.724	0.512	TC	R2
3.937	4.825	0.394	SC	RS
3.937	4.835	0.787	DBR	C2
3.937	4.921	0.394	TC	R2
3.937	4.921	0.472	SC	R2
3.937	4.921	0.472	TC	R2

Shaft	Bore	Width	Lip Style	Material
3.937	4.921	0.512	SB2	G2
3.937	4.921	0.512	TA2	G2
3.937	4.921	0.512	TB2	G2
3.937	4.921	0.512	TC	R2
3.937	5.000	0.315	SA2	CPA
3.937	5.000	0.394	TC	R2
3.937	5.000	0.472	TA2	GV
3.937	5.000	0.500	DC	R2
3.937	5.000	0.500	TC	R2
3.937	5.000	0.512	TB2	G2
3.937	5.118	0.394	TC	R2
3.937	5.118	0.472	SB2	P2
3.937	5.118	0.472	SC	R2
3.937	5.118	0.472	TC	R2
3.937	5.118	0.512	DC	RV
3.937	5.118	0.512	TA2	G3
3.937	5.118	0.512	TC	R2
3.937	5.118	0.551	TC	R2
3.937	5.315	0.394	TC	R2
3.937	5.315	0.472	TC	R2
3.937	5.315	0.512	TC	R2
3.937	5.315	0.551	SC	R2
3.937	5.315	0.551	TC	R2
3.937	5.315	0.591	TC	R2
3.937	5.376	0.500	TA2	P2
3.937	5.512	0.472	SC	R2
3.937	5.512	0.472	TC	R2
3.937	5.512	0.512	SC	R2
3.937	5.512	0.512	TC	R2
3.937	5.709	0.551	TC	R2
3.937	5.906	0.394	TC	R2
3.937	5.906	0.472	SC	R2
3.937	5.906	0.472	TC	R2
3.937	5.906	0.512	SC	R2
3.937	5.906	0.512	TC	R2
3.937	5.984	0.472	KC	R2
3.937	6.102	0.551	TC	R2
3.937	6.102	0.630	TC	R2
3.937	6.299	0.472	TC	RV
3.937	6.693	0.591	TC	R2
3.937	7.087	0.472	TC	R2
3.976	4.488	0.394	TB	G2
3.990	5.375	0.500	TBR	G2
4.000	4.500	0.252	SB	C2
4.000	4.500	0.252	VB2	P2
4.000	4.562	0.374	SBR	CPA
4.000	4.665	0.087	VB	C2
4.000	4.750	0.500	SC	R2
4.000	5.000	0.311	SA2	CV
4.000	5.000	0.311	SC	R2
4.000	5.000	0.374	TB2	G2
4.000	5.000	0.402	TB2	P2
4.000	5.000	0.417	SA2	CV
4.000	5.000	0.437	TA2	GPA

Shaft	Bore	Width	Lip Style	Material
4.000	5.000	0.500	DC	R2
4.000	5.000	0.500	SA2	P2
4.000	5.000	0.500	SC	R2
4.000	5.000	0.500	TA2	P2
4.000	5.000	0.500	TB2	G2
4.000	5.000	0.500	TC	R2
4.000	5.125	0.311	SA2	CS
4.000	5.125	0.311	SA2	GS
4.000	5.125	0.500	SC	R2
4.000	5.250	0.374	SA2	P2
4.000	5.250	0.374	TA2	P2
4.000	5.250	0.469	TA2	PPA
4.000	5.250	0.626	SC	R2
4.000	5.251	0.437	SA2	P2
4.000	5.375	0.500	TA2	P2
4.000	5.500	0.500	TC	R2
4.000	5.625	0.437	SA2	P2
4.000	5.750	0.500	SC	R2
4.000	5.999	0.500	TA2	P2
4.000	6.250	0.500	TA2	P2
4.016	5.118	0.512	TC	R2
4.094	5.512	0.472	TA2	G2
4.125	4.999	0.469	SA2	P2
4.125	5.000	0.500	TA2	G2
4.125	5.500	0.563	DA2	P2
4.126	5.000	0.437	SA2	G2
4.134	4.724	0.512	SC	R2
4.134	4.724	0.512	TC	R2
4.134	4.921	0.394	TC	R2
4.134	4.921	0.472	TC	R2
4.134	4.921	0.512	SA2	G2
4.134	4.921	0.512	SC	R2
4.134	4.921	0.512	TB	G2
4.134	4.921	0.512	TC	R2
4.134	4.921	0.630	TB2	C2
4.134	5.118	0.472	DC	R2
4.134	5.118	0.472	SC	R2
4.134	5.118	0.472	TC	R2
4.134	5.118	0.512	SA2	G2
4.134	5.118	0.512	TA2	G3
4.134	5.118	0.512	TC	R2
4.134	5.118	0.591	TC	R2
4.134	5.315	0.472	TC	R2
4.134	5.315	0.512	TA2	G3
4.134	5.315	0.512	TC	R2
4.134	5.315	0.551	SB2	G2
4.134	5.315	0.551	TB2	G2
4.134	5.315	0.551	TC	R2
4.134	5.315	0.591	TC	R2
4.134	5.315	0.630	SC	R2
4.134	5.374	0.591	TA2	PPA
4.134	5.512	0.472	SC	R2
4.134	5.512	0.472	TC	R2
4.134	5.512	0.512	TC	R2

Shaft	Bore	Width	Lip Style	Material
4.134	5.512	0.551	SC	R2
4.134	5.512	0.591	TC	R2
4.134	5.709	0.472	TC	R2
4.134	5.709	0.551	TC	R2
4.134	5.709	0.591	TC	R2
4.134	5.906	0.591	SC	R2
4.134	6.299	0.472	SC	R2
4.134	6.299	0.472	TC	R2
4.156	5.000	0.500	SA2	PS
4.173	4.961	0.472	TC	R2
4.187	4.999	0.374	TA2	P2
4.187	5.250	0.500	TC	R2
4.187	5.251	0.469	SA2	C2
4.250	4.756	0.311	WPB	G4
4.250	5.000	0.500	SC	R2
4.250	5.250	0.374	SA2	P2
4.250	5.250	0.500	SC	R2
4.250	5.250	0.500	TA2	C2
4.250	5.250	0.500	WPB	G4
4.250	5.251	0.374	TB2	P2
4.250	5.372	0.500	SC	R2
4.250	5.375	0.500	SA2	G2
4.250	5.376	0.500	TA2	P2
4.250	5.500	0.500	SA2	P2
4.250	5.500	0.500	SC	R2
4.250	5.500	0.563	SC	R2
4.250	5.524	0.366	TC	R2
4.250	5.625	0.500	TB2	P2
4.250	5.999	0.500	TA2	P2
4.250	6.000	0.563	SC	R2
4.250	6.000	0.563	TC	R2
4.250	6.000	0.752	SC	R2
4.252	5.512	0.512	TA2	G2
4.331	4.921	0.315	TBR	G2
4.331	4.921	0.472	TC	R2
4.331	5.039	0.354	TA2	P3
4.331	5.118	0.394	SC	R2
4.331	5.118	0.472	SC	R2
4.331	5.118	0.472	TC	R2
4.331	5.118	0.512	SC	R2
4.331	5.118	0.512	TA2	G3
4.331	5.118	0.512	TB	G2
4.331	5.118	0.512	TC	R2
4.331	5.118	0.551	TC	R2
4.331	5.177	0.425	SC	R2
4.331	5.236	0.512	TA2	G3
4.331	5.315	0.394	TC	R2
4.331	5.315	0.472	SC	R2
4.331	5.315	0.472	TC	R2
4.331	5.315	0.512	TB2	G2
4.331	5.315	0.512	TC	R2
4.331	5.315	0.551	TB2	G2
4.331	5.512	0.472	SC	R2
4.331	5.512	0.472	TC	R2

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
4.331	5.512	0.512	SA2	G2
4.331	5.512	0.512	TA2	G2
4.331	5.512	0.512	TC	R2
4.331	5.512	0.551	TB2	G2
4.331	5.512	0.551	TBR	G2
4.331	5.512	0.551	TC	R2
4.331	5.512	0.866	DB2	GP
4.331	5.591	0.551	TC	R2
4.331	5.709	0.512	TC	R2
4.331	5.709	0.551	TC	R2
4.331	5.709	0.591	TC	R2
4.331	5.709	0.630	TA2	G2
4.331	5.768	0.512	TC	R3
4.331	5.906	0.512	SC	R2
4.331	5.906	0.512	TA2	GV
4.331	5.906	0.512	TC	R2
4.331	5.906	0.551	TC	R2
4.331	5.906	0.591	TA2	G2
4.331	6.004	0.591	TA2	P3
4.331	6.299	0.472	TC	R2
4.331	6.299	0.551	TC	R2
4.331	6.299	0.630	TA2	G2
4.331	6.496	0.472	TC	RV
4.331	6.575	0.669	TC	R2
4.331	6.693	0.472	TC	R2
4.374	6.000	0.500	SA2	P2
4.375	5.375	0.500	DC	R2
4.375	5.375	0.500	SC	R2
4.375	6.000	0.500	TC	R2
4.375	6.250	0.563	SA2	P2
4.409	5.512	0.512	TC	R2
4.409	5.591	0.551	TC	R2
4.488	5.228	0.315	SB2	CV
4.488	5.315	0.512	TB	G2
4.496	5.001	0.252	SB	P2
4.500	5.250	0.374	SC	R2
4.500	5.500	0.252	VB2	C2
4.500	5.500	0.374	SC	R2
4.500	5.500	0.437	TA2	P2
4.500	5.500	0.500	SA2	P2
4.500	5.500	0.500	SC	R2
4.500	5.500	0.500	TC	R2
4.500	5.500	0.563	SA2	G2
4.500	5.501	0.374	TB2	P2
4.500	5.625	0.500	SC	R2
4.500	5.751	0.500	TB2	PPA
4.500	6.000	0.500	SA2	P2
4.500	6.000	0.500	TC	R2
4.500	6.125	0.563	TC	R2
4.500	6.250	0.500	SA2	C2
4.500	6.250	0.500	TA2	P2
4.500	6.250	0.563	SA2	P2
4.500	6.252	0.563	TA2	G2
4.528	5.118	0.472	SC	R2

Shaft	Bore	Width	Lip Style	Material
4.528	5.118	0.472	TC	R2
4.528	5.315	0.394	SC	R2
4.528	5.315	0.512	SB	G2
4.528	5.315	0.512	SC	R2
4.528	5.315	0.512	TC	R2
4.528	5.512	0.394	TB2	G3
4.528	5.512	0.472	SC	RV
4.528	5.512	0.472	SC	R2
4.528	5.512	0.472	TC	R2
4.528	5.512	0.512	SB2	G2
4.528	5.512	0.512	SC	R2
4.528	5.512	0.512	TB2	G2
4.528	5.512	0.512	TC	R2
4.528	5.512	0.551	TC	R2
4.528	5.512	0.591	TC	R2
4.528	5.709	0.512	TC	R2
4.528	5.709	0.551	SB2	G2
4.528	5.709	0.551	TB2	G2
4.528	5.709	0.551	TC	R2
4.528	5.709	0.630	TC	R2
4.528	5.768	0.512	TC	R3
4.528	5.906	0.472	SC	R2
4.528	5.906	0.472	TC	R2
4.528	5.906	0.551	TC	R2
4.528	5.906	0.591	TA2	G2
4.528	5.906	0.591	TC	R2
4.528	5.906	0.630	TC	R2
4.528	6.004	0.591	TA2	G2
4.528	6.260	0.551	TC	R2
4.528	6.299	0.591	TC	R2
4.528	6.693	0.472	TA2	G2
4.528	6.693	0.472	TC	R2
4.528	7.106	0.512	SC	R2
4.562	5.751	0.500	TA2	C2
4.567	5.197	0.472	TC	RPA
4.567	6.102	0.472	TA2	G2
4.623	5.637	0.500	TC	R2
4.625	5.500	0.500	TB2	G2
4.625	5.625	0.500	SC	R2
4.625	6.000	0.500	TC	R2
4.625	6.000	0.874	SB2	G2
4.625	6.250	0.500	SA2	P2
4.625	6.250	0.563	TB2	C2
4.646	5.354	0.512	TB	G2
4.646	5.512	0.512	SC	R2
4.646	5.512	0.512	TB2	G3
4.687	5.750	0.500	SA2	G2
4.687	5.750	0.500	SA2	PS
4.687	5.750	0.500	SA2	PS
4.724	5.512	0.295	TC	RV
4.724	5.512	0.394	SC	R2
4.724	5.512	0.472	TBR	G2
4.724	5.512	0.472	TC	R2
4.724	5.512	0.512	SB	G2

Shaft	Bore	Width	Lip Style	Material
4.724	5.512	0.512	SC	R2
4.724	5.512	0.512	TA2	G2
4.724	5.512	0.512	TB	G2
4.724	5.512	0.512	TC	R2
4.724	5.512	0.551	TC	R2
4.724	5.512	0.591	TC	R2
4.724	5.709	0.472	TC	R2
4.724	5.709	0.512	TA2	G2
4.724	5.709	0.591	TA2	G2
4.724	5.709	0.591	TC	R2
4.724	5.748	0.512	TC	R2
4.724	5.768	0.512	TC	R3
4.724	5.906	0.472	SC	R2
4.724	5.906	0.472	TC	R2
4.724	5.906	0.512	SC	R2
4.724	5.906	0.512	TC	R2
4.724	5.906	0.551	SB2	G2
4.724	5.906	0.551	TB2	G2
4.724	5.906	0.551	TC	R2
4.724	5.906	0.591	TA2	G3
4.724	5.906	0.591	TC	R2
4.724	5.906	0.866	DB2	GP
4.724	6.102	0.551	TC	R2
4.724	6.102	0.591	TC	R2
4.724	6.102	0.630	TC	R2
4.724	6.260	0.551	TC	R2
4.724	6.270	0.591	SA2	P3
4.724	6.299	0.472	SC	R2
4.724	6.299	0.472	TC	R2
4.724	6.299	0.512	SC	R2
4.724	6.299	0.551	TC	R2
4.724	6.299	0.591	TA2	G3
4.724	6.299	0.591	TC	R2
4.724	6.378	0.551	TC	R2
4.724	6.496	0.551	TC	R2
4.724	6.693	0.472	TC	RV
4.724	7.087	0.591	TC	R2
4.724	7.874	0.551	TC	R2
4.724	8.465	0.591	TC	R2
4.750	5.500	0.374	SC	R2
4.750	5.750	0.500	SC	R2
4.750	5.750	0.500	TC	R2
4.750	5.750	0.500	WPB	G4
4.750	5.750	0.563	SA2	G2
4.750	5.751	0.500	TB2	PV
4.750	5.762	0.500	TC	R2
4.750	5.776	0.366	TC	R2
4.750	6.000	0.500	TB2	P2
4.750	6.000	0.563	DA2	P2
4.750	6.000	0.563	SC	R2
4.750	6.000	0.626	TA2	GPA
4.750	6.000	0.875	TB	G2
4.750	6.001	0.500	TA2	P2
4.803	5.512	0.512	TC	R2

Shaft	Bore	Width	Lip Style	Material
4.803	5.984	0.827	DB2	GP
4.813	5.563	0.406	SC	RS
4.813	5.647	0.677	DB2	CS
4.813	5.750	0.579	SA2	PS
4.813	5.750	0.579	SA2	PS
4.813	5.750	0.811	DA2	PS
4.875	5.750	0.437	TC	R2
4.875	6.000	0.374	TC	R2
4.875	6.000	0.500	SA2	P2
4.882	6.102	0.709	DA2	G2
4.882	6.260	0.551	TC	R2
4.882	6.693	0.571	TC	R2
4.921	5.512	0.276	VB	C2
4.921	5.630	0.512	TC	R2
4.921	5.709	0.472	TC	R2
4.921	5.709	0.512	TC	R2
4.921	5.709	0.551	TC	R2
4.921	5.768	0.512	TC	R3
4.921	5.906	0.472	SC	R2
4.921	5.906	0.472	TC	R2
4.921	5.906	0.512	DC	R2
4.921	5.906	0.512	SC	R2
4.921	5.906	0.512	TC	R2
4.921	5.906	0.551	TB2	G2
4.921	5.906	0.551	TC	R2
4.921	5.906	0.591	SA2	G2
4.921	5.906	0.591	TC	R2
4.921	5.984	0.472	TC	R2
4.921	6.000	0.591	TA2	G2
4.921	6.102	0.551	TB2	G2
4.921	6.102	0.551	TC	R2
4.921	6.102	0.866	DB	G2
4.921	6.270	0.551	SA2	P2
4.921	6.299	0.472	SC	R2
4.921	6.299	0.512	SC	R2
4.921	6.299	0.551	TC	R2
4.921	6.299	0.591	TC	R2
4.921	6.299	0.591	TC	R2
4.921	6.299	0.630	SC	R2
4.921	6.693	0.472	TB2	G2
4.921	6.890	0.512	TC	R3
4.937	6.000	0.500	DC	R2
4.937	6.000	0.500	TC	R2
4.937	6.250	0.500	TA2	P2
4.937	6.374	0.500	TA2	P2
4.996	5.500	0.252	VB	G2
5.000	5.750	0.437	TA2	G2
5.000	5.750	0.500	TC	R2
5.000	5.751	0.500	SB	PV
5.000	5.787	0.453	TB	G2
5.000	5.906	0.512	TC	R3
5.000	6.000	0.500	SC	R2
5.000	6.000	0.500	TA2	C2
5.000	6.000	0.500	WPB	G4
5.000	6.000	0.626	DA2	PV

# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
5.000	6.003	0.500	TB2	PS
5.000	6.250	0.500	SA2	P2
5.000	6.250	0.500	TA2	C2
5.000	6.250	0.563	SA2	P2
5.000	6.250	0.563	SC	R2
5.000	6.375	0.500	TB2	G2
5.000	6.500	0.625	SA2	G2
5.000	6.750	0.563	SC	R2
5.000	7.500	0.500	TA2	P2
5.039	5.906	0.512	TC	R2
5.062	6.125	0.500	TB	G2
5.063	6.125	0.500	TC	R2
5.118	5.512	0.472	TC	R2
5.118	5.709	0.276	VB	G2
5.118	5.906	0.394	TB2	G2
5.118	5.906	0.394	TC	R2
5.118	5.906	0.472	TC	R2
5.118	5.906	0.512	TC	R2
5.118	6.102	0.394	SC	R2
5.118	6.102	0.394	TC	R3
5.118	6.102	0.551	TC	R2
5.118	6.299	0.472	SB2	G2
5.118	6.299	0.472	SC	R2
5.118	6.299	0.472	TC	R2
5.118	6.299	0.512	TC	R2
5.118	6.299	0.551	TA2	G2
5.118	6.299	0.551	TB2	G2
5.118	6.299	0.551	TC	R2
5.118	6.299	0.591	TC	R2
5.118	6.496	0.512	TC	R2
5.118	6.496	0.551	TC	R2
5.118	6.496	0.591	TC	R2
5.118	6.693	0.472	SC	R2
5.118	6.693	0.472	TC	R2
5.118	6.693	0.512	TC	R3
5.118	6.693	0.591	TA2	P2
5.118	6.693	0.591	TC	R2
5.118	7.087	0.512	TC	R3
5.118	7.165	0.630	SC	R2
5.118	7.480	0.472	TC	R2
5.118	7.874	0.472	TC	R2
5.118	7.874	0.591	SC	R2
5.125	6.125	0.500	SC	R2
5.157	5.709	0.276	TC	RV
5.197	6.299	0.551	TC	R2
5.250	6.250	0.252	WPB	G4
5.250	6.250	0.500	SA2	P2
5.250	6.250	0.500	SC	R2
5.250	6.500	0.626	SA2	PPA
5.250	6.500	0.626	SC	R2
5.276	5.984	0.433	TB	G2
5.313	6.500	1.031	DA2	PS
5.315	6.102	0.472	TC	R2
5.315	6.102	0.512	TC	R2

Shaft	Bore	Width	Lip Style	Material
5.315	6.299	0.472	SC	R2
5.315	6.299	0.512	SC	R2
5.315	6.299	0.512	TC	R3
5.315	6.299	0.591	SC	R2
5.315	6.299	0.591	TC	R2
5.315	6.378	0.512	TB2	G2
5.315	6.496	0.512	TA2	P2
5.315	6.496	0.512	TC	R2
5.315	6.496	0.551	TB2	G2
5.315	6.496	0.551	TC	R2
5.315	6.496	0.591	TA2	P3
5.315	6.496	0.591	TC	R2
5.315	6.693	0.472	SC	R2
5.315	6.693	0.472	TC	RV
5.315	6.693	0.591	SC	R2
5.315	6.693	0.591	TC	R2
5.315	6.890	0.472	TC	R2
5.315	6.890	0.591	TC	R2
5.374	5.876	0.193	VB	C2
5.375	6.500	0.500	SC	R2
5.375	6.625	0.563	TA2	P2
5.375	6.625	0.626	SA2	C2
5.433	5.984	0.472	TB	G2
5.433	6.299	0.591	TC	R2
5.472	6.693	0.551	TB2	G2
5.500	6.000	0.252	SB	G2
5.500	6.125	0.358	WPB	G4
5.500	6.250	0.500	SC	R2
5.500	6.500	0.500	SC	R2
5.500	6.500	0.500	TB2	G2
5.500	6.500	0.563	TA2	P2
5.500	6.749	0.625	TA2	GV
5.500	7.500	0.563	SA2	P2
5.512	6.299	0.394	TC	R2
5.512	6.299	0.472	SC	R2
5.512	6.299	0.472	TC	R2
5.512	6.299	0.512	SA2	G2
5.512	6.299	0.512	TC	R2
5.512	6.299	0.551	TB	G2
5.512	6.299	0.551	TC	R2
5.512	6.299	0.591	TC	R2
5.512	6.496	0.512	TC	R2
5.512	6.496	0.591	TC	R2
5.512	6.496	0.630	TB	G2
5.512	6.614	0.591	TA2	P3
5.512	6.614	0.591	TC	R2
5.512	6.693	0.472	SC	R2
5.512	6.693	0.472	TC	R2
5.512	6.693	0.512	TC	R2
5.512	6.693	0.551	SA2	G2
5.512	6.693	0.551	SB2	G2
5.512	6.693	0.551	TB2	G2
5.512	6.693	0.551	TC	R2
5.512	6.693	0.591	SC	R2

Shaft	Bore	Width	Lip Style	Material
5.512	6.693	0.591	TA2	P3
5.512	6.693	0.591	TC	R2
5.512	6.752	0.591	TA2	P3
5.512	6.890	0.512	TC	R2
5.512	6.890	0.591	TC	R2
5.512	7.087	0.394	SC	R2
5.512	7.087	0.472	SC	R2
5.512	7.087	0.472	TC	R2
5.512	7.087	0.591	TB2	G2
5.512	7.087	0.591	TC	R2
5.512	7.087	0.630	TB2	G2
5.512	7.283	0.630	TC	R2
5.512	7.874	0.472	TC	R2
5.512	8.465	0.472	SC	R2
5.512	9.843	0.591	TC	R2
5.563	6.625	0.500	TC	R2
5.591	6.181	0.394	TC	R2
5.591	6.614	0.551	TB2	G2
5.591	6.614	0.551	TC	R2
5.625	6.624	0.500	TA2	P2
5.625	6.625	0.374	SC	R2
5.630	6.496	0.394	SC	R2
5.630	6.496	0.394	TB2	P2
5.630	6.614	0.630	TB2	G2
5.669	6.299	0.472	SC	R2
5.709	6.299	0.276	SB	G2
5.709	6.299	0.472	TC	R3
5.709	6.496	0.394	TB	G2
5.709	6.496	0.512	TC	R2
5.709	6.496	0.551	TC	R2
5.709	6.575	0.512	TC	R2
5.709	6.606	0.453	TC	R2
5.709	6.614	0.394	TC	R2
5.709	6.614	0.512	TC	R3
5.709	6.614	0.591	TA2	P3
5.709	6.693	0.512	TB2	G3
5.709	6.693	0.512	TC	R2
5.709	6.693	0.591	SC	R2
5.709	6.693	0.591	TB	G2
5.709	6.693	0.591	TC	R2
5.709	6.890	0.315	TB2	G2
5.709	6.890	0.512	SA2	G2
5.709	6.890	0.512	SC	R2
5.709	6.890	0.512	TC	R2
5.709	6.890	0.551	TB2	G2
5.709	6.890	0.551	TC	R2
5.709	6.890	0.591	SC	R2
5.709	6.890	0.591	TC	R2
5.709	7.087	0.472	TC	R2
5.709	7.087	0.591	TC	R2
5.709	7.283	0.591	TA2	P2
5.709	9.055	0.669	TC	R2
5.750	6.625	0.500	SA2	P2
5.750	6.625	0.500	SC	R2

Shaft	Bore	Width	Lip Style	Material
5.750	6.750	0.500	SA2	C2
5.750	6.875	0.500	TB2	C2
5.750	7.000	0.626	SA2	C2
5.750	7.500	0.563	SC	R2
5.750	7.500	0.563	TA2	P2
5.827	6.693	0.571	TA2	C2
5.827	6.693	0.591	TC	R2
5.875	6.875	0.500	TC	R2
5.906	6.614	0.512	TB	G2
5.906	6.614	0.512	TC	R2
5.906	6.693	0.472	SC	R2
5.906	6.693	0.512	TC	R3
5.906	6.693	0.591	SA2	P3
5.906	6.693	0.591	TA2	G3
5.906	6.693	0.591	TC	R2
5.906	6.772	0.472	TC	R2
5.906	6.772	0.591	SC	R2
5.906	6.890	0.394	TC	R2
5.906	6.929	0.591	TC	R2
5.906	7.087	0.472	SC	R2
5.906	7.087	0.472	TC	R2
5.906	7.087	0.512	SC	R2
5.906	7.087	0.512	TC	R2
5.906	7.087	0.551	TB2	G2
5.906	7.087	0.551	TC	R2
5.906	7.087	0.591	SC	R2
5.906	7.087	0.591	TC	R2
5.906	7.283	0.630	TC	R2
5.906	7.480	0.591	TC	R2
5.906	7.874	0.394	SC	R2
5.906	7.874	0.512	TC	R2
5.906	8.268	0.591	TC	R2
5.906	8.858	0.472	TC	R2
5.906	8.858	0.591	SC	R2
5.937	7.000	0.500	SC	R2
5.984	6.764	0.512	TB	G2
6.000	6.750	0.469	TBR	GS
6.000	6.750	0.500	SB2	P2
6.000	7.000	0.500	SC	R2
6.000	7.000	0.500	TC	R2
6.000	7.001	0.626	SA2	C2
6.063	6.772	0.551	TB	G2
6.063	6.772	0.551	TC	R2
6.063	7.087	0.709	TC	R2
6.102	6.772	0.551	TC	R2
6.102	6.850	0.472	TC	R2
6.102	6.890	0.472	SC	R2
6.102	6.890	0.512	TB	C3
6.102	7.087	0.394	TC	R2
6.102	7.087	0.472	TC	R2
6.102	7.087	0.512	TC	R2
6.102	7.087	0.591	SC	R2
6.102	7.087	0.591	TA2	G2
6.102	7.087	0.591	TC	R2



# Tobar

## oil seal size listing

Shaft	Bore	Width	Lip Style	Material
6.102	7.283	0.551	TB2	G2
6.102	7.283	0.551	TC	R2
6.102	7.283	0.630	TC	R2
6.102	7.480	0.591	SC	R2
6.102	7.480	0.591	TC	R3
6.125	7.125	0.626	SA2	P2
6.187	7.500	0.563	SA2	PPA
6.203	7.028	0.283	SC	RS
6.203	7.125	0.437	SA2	PS
6.250	7.000	0.374	TC	R2
6.250	7.187	0.625	TC	R2
6.250	7.187	0.626	SC	R2
6.250	7.187	0.626	TB2	G2
6.250	7.250	0.500	TC	R2
6.250	7.500	0.752	SC	R2
6.250	7.750	0.500	SA2	P2
6.299	7.087	0.394	TC	R2
6.299	7.087	0.512	TB	G3
6.299	7.087	0.512	TC	R2
6.299	7.087	0.551	TC	R2
6.299	7.087	0.591	SA2	C2
6.299	7.087	0.591	TB2	G2
6.299	7.087	0.591	TC	R2
6.299	7.165	0.709	TC	R2
6.299	7.283	0.394	SC	R2
6.299	7.283	0.394	TC	R2
6.299	7.283	0.472	SC	RV
6.299	7.283	0.512	TC	R2
6.299	7.480	0.512	SC	R2
6.299	7.480	0.512	TC	R2
6.299	7.480	0.551	TC	R2
6.299	7.480	0.591	SC	R2
6.299	7.480	0.591	TA2	G2
6.299	7.480	0.591	TC	R2
6.299	7.480	0.630	SB2	G2
6.299	7.677	0.591	TC	R2
6.299	7.677	0.827	DB2	GP
6.299	7.874	0.472	SC	R2
6.299	7.874	0.472	TC	R2
6.299	7.874	0.551	TC	R2
6.299	7.874	0.591	TC	R2
6.299	7.874	0.630	TC	R2
6.299	8.465	0.591	TC	R2
6.299	8.661	0.472	SC	R2
6.299	8.661	0.591	TC	RV
6.299	9.449	0.591	TC	R2
6.299	11.417	0.709	TC	R2
6.375	7.500	0.500	TC	R2
6.375	7.874	0.563	TA2	P2
6.378	7.165	0.551	TB	G2
6.496	7.087	0.315	SC	R2
6.496	7.323	0.551	TC	R2
6.496	7.480	0.512	SC	R2
6.496	7.480	0.512	TC	R2

Shaft	Bore	Width	Lip Style	Material
6.496	7.480	0.551	TC	R2
6.496	7.480	0.591	TC	R2
6.496	7.677	0.591	TC	R2
6.496	7.874	0.551	TC	R2
6.496	7.992	0.748	TA2	G3
6.496	8.012	0.748	TA2	G2
6.500	7.500	0.500	TC	R2
6.500	7.500	0.563	TA2	P2
6.500	7.625	0.626	SA2	P2
6.500	7.750	0.500	SC	R2
6.500	8.000	0.750	SC	R2
6.693	7.480	0.276	SC	R2
6.693	7.480	0.335	TC	R3
6.693	7.480	0.394	TC	R2
6.693	7.480	0.551	TC	R2
6.693	7.480	0.591	SC	R2
6.693	7.677	0.591	TC	R2
6.693	7.874	0.472	SC	R2
6.693	7.874	0.512	TC	R2
6.693	7.874	0.591	DC	R2
6.693	7.874	0.591	SC	R2
6.693	7.874	0.591	TA2	P2
6.693	7.874	0.591	TC	R2
6.693	7.953	0.472	TC	R2
6.693	8.071	0.591	TC	R2
6.693	8.071	0.669	TC	R2
6.693	8.268	0.591	SC	R2
6.693	8.268	0.591	TC	R2
6.750	7.657	0.500	TB2	P2
6.750	7.750	0.500	TC	R2
6.750	7.998	0.591	TA2	G3
6.750	8.000	0.500	TB2	G2
6.811	7.756	0.315	TC	RV
6.875	7.875	0.625	SA2	P2
6.890	7.480	0.591	TC	R2
6.890	7.874	0.591	SC	R2
6.890	7.874	0.591	TA2	G2
6.890	7.874	0.591	TC	R2
6.890	8.268	0.591	SC	R2
6.890	8.268	0.591	TC	R2
6.890	8.465	0.591	TC	R2
6.890	9.055	0.787	TC	R2
6.969	8.165	0.965	DB2	G2
6.969	8.189	0.512	TC	R2
7.000	8.000	0.500	TC	R2
7.000	8.000	0.500	WPB	G4
7.000	8.000	0.626	TA2	P2
7.000	8.500	0.500	TB2	P2
7.087	7.874	0.276	SC	R2
7.087	7.874	0.472	TB	G2
7.087	7.874	0.551	TC	R2
7.087	7.874	0.591	SC	R2
7.087	7.874	0.591	TB	G2
7.087	7.874	0.591	TC	R2

Shaft	Bore	Width	Lip Style	Material
7.087	7.874	0.630	TB	G2
7.087	8.071	0.591	TC	R2
7.087	8.197	0.807	DB	C2
7.087	8.268	0.492	SC	R2
7.087	8.268	0.591	TA2	G2
7.087	8.268	0.591	TC	R2
7.087	8.465	0.591	TC	R2
7.087	8.465	0.630	TA2	G3
7.087	8.661	0.591	SC	R2
7.087	8.661	0.591	TC	R2
7.087	8.661	0.630	TC	R2
7.125	8.625	0.563	TC	R2
7.250	8.750	0.563	SC	R2
7.283	8.268	0.512	SC	R2
7.283	8.268	0.512	TC	R2
7.283	8.268	0.591	TC	R2
7.283	8.465	0.591	TC	R2
7.283	8.465	0.630	TC	R2
7.323	7.992	0.315	SC	R2
7.375	8.875	0.750	SA2	P2
7.480	8.268	0.394	TC	R2
7.480	8.268	0.591	TC	R2
7.480	8.465	0.630	SC	R2
7.480	8.661	0.591	SA2	G2
7.480	8.661	0.591	SC	R2
7.480	8.661	0.591	TA2	G3
7.480	8.661	0.591	TC	R2
7.480	8.858	0.472	TC	R2
7.480	8.858	0.630	TC	R2
7.480	8.858	0.709	TC	R2
7.480	9.055	0.591	TC	R2
7.480	9.055	0.630	TC	R2
7.500	8.625	0.626	SC	R2
7.500	9.000	0.563	SC	R2
7.500	9.000	0.750	TA2	P2
7.598	8.268	0.315	SC	R2
7.625	8.625	0.563	SA2	C2
7.625	9.125	0.563	TC	R2
7.677	8.858	0.630	TC	R2
7.677	9.055	0.591	TC	R2
7.677	9.055	0.630	TC	R2
7.677	9.055	0.787	TC	R2
7.677	9.252	0.630	TC	R2
7.750	9.500	0.752	SC	R2
7.874	8.661	0.472	TC	R2
7.874	8.858	0.591	SC	R2
7.874	8.858	0.591	TC	R2
7.874	9.055	0.512	TC	R2
7.874	9.055	0.591	SC	R2
7.874	9.055	0.591	TC	R2
7.874	9.055	0.630	SC	R2
7.874	9.252	0.591	TC	R2
7.874	9.449	0.591	DB2	GV
7.874	9.449	0.591	TC	R2

Shaft	Bore	Width	Lip Style	Material
7.874	9.449	0.787	TC	R2
7.874	9.843	0.591	SC	R2
7.874	9.843	0.591	TC	R3
7.874	9.843	0.630	TC	R2
7.874	9.843	0.787	TC	R2
8.000	9.000	0.626	TA2	P2
8.000	9.000	0.750	TBR	G2
8.071	8.858	0.709	TC	R2
8.071	9.055	0.630	SC	R2
8.071	9.055	0.630	TC	R2
8.071	9.252	0.709	TC	R2
8.250	9.250	0.500	SA2	P2
8.250	9.250	0.626	SBR	C2
8.250	10.250	0.689	SC	R2
8.268	9.449	0.591	SC	R2
8.268	9.449	0.591	TC	R2
8.268	9.646	0.709	TC	R2
8.268	9.843	0.591	SC	R2
8.268	9.843	0.591	TC	R2
8.268	9.843	0.630	TC	R2
8.268	10.039	0.630	TC	R2
8.268	10.236	0.630	TC	R2
8.268	10.630	0.630	TC	R2
8.375	9.875	0.563	SC	R2
8.465	9.449	0.472	SC	R2
8.465	9.449	0.591	TC	R2
8.465	9.449	0.709	TC	R2
8.500	10.000	0.752	SC	R2
8.524	9.740	0.965	DB2	C2
8.661	9.724	0.591	TC	R2
8.661	9.843	0.591	TC	R2
8.661	9.843	0.630	TA2	P3
8.661	9.843	0.787	TC	R2
8.661	10.039	0.630	TC	R2
8.661	10.236	0.551	TC	R2
8.661	10.236	0.630	TC	R2
8.661	10.630	0.669	TC	R2
8.740	9.646	0.512	TC	R2
9.000	10.000	0.626	SA2	G2
9.000	10.087	0.625	TA2	P2
9.000	10.384	0.625	SA2	G4
9.055	10.000	0.472	SB	G2
9.055	10.236	0.591	SC	R2
9.055	10.236	0.591	TC	R2
9.055	10.630	0.591	TC	R2
9.134	10.512	0.827	DB	GP
9.250	11.250	0.625	TA2	P2
9.252	10.236	0.394	KB	P2
9.252	10.827	0.630	TC	R2
9.449	10.630	0.591	SC	R2
9.449	10.630	0.591	TC	R2
9.449	11.024	0.591	SC	R2
9.449	11.024	0.709	TC	R2
9.449	11.024	0.787	TC	R2

# Tobar

oil seal size listing

Shaft	Bore	Width	Lip Style	Material
9.843	11.024	0.591	SC	R2
9.843	11.024	0.591	TC	R2
9.843	11.220	0.709	TC	R2
9.843	11.417	0.591	TC	R2
9.910	10.997	0.626	SB	G2
10.236	11.417	0.591	SC	R2
10.236	11.417	0.591	TC	R2
10.236	11.811	0.709	TC	R2
10.236	11.811	0.787	SC	R2
10.236	11.811	0.787	TC	R2
10.236	12.598	0.787	TC	R2
10.236	12.598	0.984	TC	R2
10.433	11.417	0.630	TC	R2
10.630	12.205	0.709	TC	R2
11.024	12.205	0.591	SC	R2
11.024	12.205	0.591	TC	R2
11.024	12.205	0.630	SA2	G2
11.024	12.598	0.787	TC	R2
11.220	12.598	0.787	TC	R2
11.250	12.250	0.687	TB	G2
11.417	12.992	0.709	TC	R2
11.811	13.386	0.709	SC	R2
11.811	13.386	0.709	TC	R2
11.811	14.173	0.984	TC	R2
12.205	13.071	0.394	KB	P2
12.205	13.071	0.394	TC	R2
12.205	13.780	0.709	TC	R2
12.375	13.484	0.701	TB	G2
12.598	13.780	0.787	TC	R2
12.598	14.173	0.709	TC	R2
12.598	14.173	0.787	SC	R2
12.598	14.173	0.787	TC	R2
13.386	14.961	0.709	SC	R2
13.386	14.961	0.787	TC	R2
13.780	15.354	0.709	TC	R2
14.173	15.748	0.709	TC	R2
14.173	15.748	0.787	SC	R2
14.173	15.748	0.787	TC	R2
14.961	16.535	0.787	SC	R2
14.961	16.535	0.787	TC	R2
15.748	16.732	0.591	SC	R2
15.748	17.323	0.787	TC	R2
16.535	18.110	0.787	TC	R2
16.929	17.835	0.394	KB	P2
16.929	18.898	1.181	SC	R2
17.323	18.898	0.787	TC	R2